

KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

(See Instructions on Reverse Side)

Type Test:

- Open Flow
 Deliverability

Test Date:
5/17/2014

API No. 15
15-119-20330-0000

Company Samson Resources Company		Lease Adams		Well Number 1-5	
County Meade	Location NWSW	Section 5	TWP 34	RNG (E/W) 29W	Acres Attributed
Field Horace South		Reservoir Morrow	Gas Gathering Connection Western Resources, Inc		
Completion Date 12/14/1978		Plug Back Total Depth 5940	Packer Set at 5771		
Casing Size 4.5	Weight 10.5	Internal Diameter 4.052	Set at 6249	Perforations 5815	To 5860
Tubing Size 2.375	Weight 4.7	Internal Diameter 1.995	Set at 5771	Perforations	To
Type Completion (Describe) Single (Casing Perforations)		Type Fluid Production None	Pump Unit or Traveling Plunger?		Yes / No No
Producing Thru (Annulus / Tubing) Tubing		% Carbon Dioxide	% Nitrogen	Gas Gravity - Gg 0.682	
Vertical Depth (H) 6249		Pressure Taps Pipe		(Meter Run) (Prover) Size 4.000	
Pressure Buildup: Well on Line:		Shut-in Started	May-17 20	14 at	(AM/PM) Taken May-18 20
					(AM/PM) Taken 20 at (AM/PM)

OBSERVED SURFACE DATA

Static / Dynamic Property	Orifice Size inches	Circle one: Meter or Prover Pressure psig	Pressure Differential in (h) Inches H2O	Flowing Temperature t	Well Head Temperature t	Casing Wellhead Pressure (Pw) or (Pt) or (Pc)		Tubing Wellhead Pressure (Pw) or (Pt) or (Pc)		Duration (hours)	Duration of Shut-in Hours	Liquid Produced (Barrels)
						psig	psia	psig	psia			
Shut-in								470	484.4	24		
Flow												

FLOW STREAM ATTRIBUTES

Plate Coefficient (Fb)(Fp) Mcfd	Circle one: Meter or Prover Pressure psia	Press Extension (Pm x Hw)^2	Gravity Factor Fg	Flowing Temperature Factor FL	Deviation Factor Fpv	Metered Flow R (Mcfd)	GOR (Cubic Feet/ Barrel)	Flowing Fluid Gravity Gm

(OPEN FLOW) (DELIVERABILITY) CALCULATIONS

(Pc)2 = 234.643 (Pw)2 = _____ Pd = _____ % (Pc-14.4)+14.4 = _____ (Pa)2 = 0.207
(Pd)2 = _____

(Pc)2 - (Pa) or (Pc)2 - (Pd)2	(Pc)2 - (Pw)2	$\left[\begin{matrix} Pc2 - Pa2 \\ Pc2 - Pd2 \\ Pc2 - Pw2 \end{matrix} \right]$	LOG $\left[\quad \right]$	Backpressure Curve Slope = "n" or Assigned Standard Slope	n x LOG $\left[\quad \right]$	ANTILOG	Open Flow Deliverability Equals R x Antilog Mcfd

Open Flow Mcfd @ 14.65 psia Deliverability Mcfd @ 14.65 psia

The undersigned authority, on behalf of the Company, states that he is duly authorized to make the above report and that he has knowledge of the facts stated therein, and that said report is true and correct.

Executed this the 23 day of May, 2014.

David Williams SRC
For Company

Witness (if any)

For Company

For Commission

Computer

Checked by

7010-0780-0001-3731-1388

KCC WICHITA

JUN 02 2014

RECEIVED


I declare, under penalty or perjury under the laws of the state of Kansas that I am authorized to request exempt status under Rule K.A.R. 82-3-304 on behalf of the operator Samson Resources Company and that the foregoing information and statements contained on this application form are true and correct to the best of my knowledge and belief based upon gas production records and records of equipment installation and/or type completion or upon use of the gas well herein named.

I hereby request a permanent exemption from open flow testing for the Adams 1-5 gas well on the grounds that said well:

(Check one)

- is a coalbed methane producer
- is cycled on plunger lift due to water
- is a source of natural gas for injection into an oil reservoir undergoing ER
- is on vacuum at the present time; KCC approval Docket No.
- is incapable of producing at a daily rate in excess of 250 mcf/D

Date: 5/23/2014

Signature: 
Title: Gas Meas. Specialist

Instruction All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.