

Tq: 1 041212
STATE CORPORATION COMMISSION
Wichita State Office Bldg. - PLUGGING SECTION 75'S of NW SW NWSEC. 34, T 26 S, R 12 W/E
130 S. Market, Room 2078
Wichita, KS 67202

API NUMBER 15- 151-22,146 -0000
1725 feet from N E section line
330 feet from W E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5046
Operator: Raymond Oil Co., Inc.
Name:
Address P.O. Box 48788
Wichita, KS 67201

Lease Name Mardis Well # 1 A
County Pratt 145.43
Well Total Depth 4475 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 10 3/4 feet 303

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Duke Drilling Co. License Number 5929
Address 310 W. Central, Wichita, KS 67202

Company to plug at: Hour: 7:15 p.m. Day: 15 Month: 10 Year: 19 96

Plugging proposal received from John
(company name) Duke Drilling Co. (phone) 316-267-1331

- Work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite Base 700'
- 1st plug at 700' with 50 sx cement, 2nd plug at 340' with 75 sx cement,
- 3rd plug at 40' with 15 sx cement,
- 4th plug to circulate rathole with 15 sx cement,
- 5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Pfeifer
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 8:30 p.m. Day: 15 Month: 10 Year: 19 96

- ACTUAL PLUGGING REPORT 1st plug at 700' with 50 sx cement,
- 2nd plug at 340' with 75 sx cement,
- 3rd plug at 40' with 15 sx cement,
- 4th plug to circulate rathole with 15 sx cement,
- 5th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by United.
(if additional description is necessary, use BACK of this form.)

INVOICED
Observe this plugging.

DATE 10-21-96
WV. NO. 46767
10-15

Signed Stephen J. Pfeifer
(TECHNICIAN)

Stamp: OCT 21 1996
10-21-96
10-15

EFFECTIVE DATE: 9-17-96

DISTRICT # 1
55A7 Yes No

State of Kansas

NOTICE OF INTENTION TO DRILL 151-22,146-0000 ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

Spot 75'S OF NW SW NW East
1725 FNL 330 FNL Sec 34. Twp 26.S S, Rg 12.X West

Expected Spud Date 10-15-96
month day year

OPERATOR: License # 5046
Name: Raymond Oil Co, Inc.
Address: P.O. Box 48788
City/State/Zip: Wichita, KS, 67201
Contact Person: Pat Raymond
Phone: 316-2674214

CONTRACTOR: License #: 5929
Name: Duke Drilg Co

Well Drilled For: Well Class: Type Equipment:
XX Oil: ... Enh Rec ... Infield XX Mud Rotary
XX Gas ... Storage ... Pool Ext. ... Air Rotary
... OWWO ... Disposal XX Wildcat ... Cable
... Seismic: ... # of Holes ... Other
... Other
If OWWO: old well information as follows:
Operator:
Well Name:
Comp. Date: Old Total Depth

1725 feet from South (North) line of Section
330 feet from East (West) line of Section
IS SECTION XX REGULAR IRREGULAR?

(NOTE: Locate well on the Section Plat on Reverse Side)
County: Pratt
Lease Name: Mardis Well #: 11A!
Field Name: Wildcat
Is this a Prorated/Spaced Field? ... yes XX no
Target Formation(s): LKC MISS. VIOLA SIMP.
Nearest lease or unit boundary: 330
Ground Surface Elevation: 1897 est feet MSL
Water well within one-quarter mile: ... yes XX no
Public water supply well within one mile: ... yes XX no
Depth to bottom of fresh water: 240
Depth to bottom of usable water: 240
Surface Pipe by Alternate: XX 1 2
Length of Surface Pipe Planned to be set: 280
Length of Conductor pipe required: N/A
Projected Total Depth: 4500
Formation at Total Depth: Arbuckle
Water Source for Drilling Operations:
... well ... farm pond XX other

DWR Permit #: ...
Will Cores Be Taken?: ... yes XX no
If yes, proposed zone: ...

Directional, Deviated or Horizontal wellbore? ... yes XX no
If yes, true vertical depth:
Bottom Hole Location:
Exp. 3/12/97

AFFIDAVIT

260' Alt. I Req.

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-

Pusher John
SPUD DATE 10/17/96 INIT. PJ
LENGTH SURFACE PLANNED 300 to 310
RESERVE PIT STATUS- REMOVE FLUID LINED
after salt sect. bbls. when done bbls.
RATHOLED AHEAD? Y N SIZE HOLE
SURFACE PIPE 10 3/4 @ 30 1/2 CONDUCTOR
ANHYDRITE T- B-700 ELEVATION
(41366)
TD 4475 FORMATION
RAN PIPE @ SX DV TOOL ALT II DONE
Arbuckle Plug @ Top Ft. W/ 40 SX
Hug./Council @ Ft. W/ SX
Anhydrite Base @ Ft. W/ SX
1/2 Base Anhy. @ 700 Ft. W/ 50 SX
1/2 Plug @ 340 Ft. W/ 75 SX
Bottom Surface @ 340 Ft. W/ 75 SX
40' Plug @ 40 Ft. W/ 15 SX
RAT HOLE CIRC/W 15 SX MOUSE HOLE W/ 10 SX
WATER WELL SX (Irr. Well Pond
TECHNICIAN S.P. DATE 10-14-96 Hauling
TYPE OF CEMENT 60/40 for 6" gel
STARTING TIME 7:15 (AM/PM) DATE 10-15-96
COMPLETION TIME 8:30 (AM/PM) DATE 10-15-96
CEMENT COMPANY United Cement