

To: 1 061013  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

9-25-87  
API NUMBER 15-033-20,713-0000  
C NE NW, SEC. 8, T 35 S, R 19 W/X  
4620 feet from S section line  
3300 feet from E section line  
Lease Name Box Ranch Well # 1-8  
County Comanche 178.75  
Well Total Depth 5500 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 460

TECHNICIAN'S PLUGGING REPORT

Operator License # 3080

Operator: Jack Exploration, Inc.  
Name & Address P.O. Box 60  
Sulphur, OK 73086

Well # 1-8  
County Comanche 178.75  
Well Total Depth 5500 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 460

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor H-30 Drilling, Inc. License Number 5107

Address 251 North Water, Suite 10, Wichita, KS 67202

Company to plug at: Hour: 5 p.m. Day: 25 Month: 9 Year: 19 87

Plugging proposal received from Kenneth Mayfield

(company name) Crown Consulting (phone) 316-624-0156

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 1768'  
Anhydrite 2400-2500'

1st plug at 1020' with 50 sx cement,

2nd plug at 500' with 50 sx cement,

3rd plug at 40' with 10 sx cement, 4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 15 sx cement.

Plugging Proposal Received by Duane Rankin  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 8:30 p.m. Day: 25 Month: 9 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 1020' with 50 sx cement,

2nd plug at 500' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION  
SEP 29 1987  
9-29-87  
CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.  
(if additional description is necessary, use BACK of this form.)

**INVOICED**  
(If additional description is necessary, use BACK of this form.)

Signed Paul A. Luthi  
(TECHNICIAN)

DATE 10-6-87

INV. NO. 18390

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date September 1, 1987 month day year

API Number 15-033-20713-0000

OPERATOR: License # 03080 Name Jack Exploration, Inc. Address P.O. Box 60 City/State/Zip Sulphur, OK 73086 Contact Person Keith Hill Phone (316) 624-0156

East X West C. NE. NW. Sec. 8 Twp. 35 S, Rg. 19 4620 Ft. from South Line of Section 3300 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # H-30 Name Unknown - will call City/State

Nearest lease or unit boundary line 660 feet County Comanche

Lease Name Box Ranch Well # 1-8

Well Drilled For: X Oil SWD Infield X Mud Rotary X Gas Inj Pool Ext Air Rotary OWWO Expl X Wildcat Cable

Ground surface elevation 2050+ feet MSL

Domestic well within 330 feet: yes X no

Municipal well within one mile: yes X no

Depth to bottom of fresh water 300' 150'

Depth to bottom of usable water 200'

Surface pipe by Alternate: 1 X 2

If OWWO: old well info as follows:

Surface pipe planned to be set 450'

Conductor pipe required 130'

Projected Total Depth 5500' feet

Formation Mississippian

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 8-6-87 Signature of Operator or Agent Keith Hill Title Agent

For KCC Use:

Conductor Pipe Required 200 feet; Minimum Surface Pipe Required 200 feet per Alt. 2

This Authorization Expires 2-6-88 Approved By [Signature] 8-6-87

SPUP 9-17-87 150' - 8 3/8" 460-88

40 W W AN 2400 2500

C. NE. NW. Sec. 8 Twp. 35 S, Rg. 19 X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ Base Anhydrite feet depth with 50 sxs of 60/40, 6% gel
2nd plug @ 30' below surface feet depth with 50 sxs of " " "
3rd plug @ 40' to 0' feet depth with 10 sxs of " " "
4th plug @ feet depth with sxs of
5th plug @ feet depth with sxs of
(2) Rathole with 15 sxs (b) Mousehole with 10 sxs

cream consultant

PUSHER Kenneth Mayfield TD 5300 FORMATION SURFACE PIPE 8 5/8 @ 460 ANHYDRITE 2400 2500 ELEVATION 1768 STARTING TIME & DATE 9-26-87 5:00 PM COMPLETION TIME & DATE 9-26-87 8:30 PM 1st PLUG @ 2400 FT. W/ 50 SX 2nd PLUG @ 2100 FT. W/ 50 SX 3rd PLUG @ 500 FT. W/ 50 SX 4th PLUG @ 40 FT. W/ 10 SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ 15 SX WATER WELL PLUGGED W/ CEMENT COMPANY 60-40-690 TECHNICIAN Paul Smith saw all

RECEIVED STATE CORPORATION COMMISSION

SEP 29 1987 9-29-87 CONSERVATION DIVISION Wichita, Kansas

17-30