

**Kansas Corporation Commission**

**District Plugging Report**

API Well Number: 15-001-23450-0001  
 Spot: NENWNE Sec 24 Twp 26 S Rng 20  E /  W  
4855 Feet from  N /  S Line of Section  
1385 Feet from  E /  W Line of Section  
 GPS: Lat: 37.774963 Long: 95.165244 Date: 3/27/14 2/13/14  
 Lease Name: Beggs II Well #: BEG 03 (512)  
 County: Allen Total Vertical Depth: 700 feet

Operator License No: <u>101</u>	String	Size	Depth	Pulled	Comments
Op Name: <u>State of Kansas</u>	<u>SURF - Casing</u>	<u>6.250</u>	<u>20</u>	<u>0</u>	<u>EST.</u>
Address 1: <u>130 S. Market</u>	<u>STRL - Casing</u>	<u>2.500</u>	<u>700</u>	<u>0</u>	
Address 2: _____					
City: <u>Wichita</u>					
State: <u>Ks</u> Zip Code: <u>67202</u>					

Well Type: EOR - Enhanced Oil Recovery - Injection UIC Docket No.: \_\_\_\_\_ Date/Time to Plug: 3/20/14 / \_\_\_\_\_  
 Plug Co License No.: 6372 Plug Co. Name: Splane Pulling and Roustabout Services, Inc.  
 Proposal Rcvd from: Keith Splane Company Name: SAME Phone: (620) 431-1359

Proposed Plugging Report: Clean out well to TD. Perforate in at least two depths if not documented Alt. II. Pump Portland cement from TD to surface.

Plugging Proposal Received By: Frank Guilfoyle Witness Type: COMP - Complete 100%  
 Date/Time Plugging Completed: 3/20/14 / \_\_\_\_\_ KCC Agent: Frank Guilfoyle

Actual Plugging Report:	Perfs:	Top	Bottom	Thru
Clear around location. Drill by hand to 75 ft and ran 1" to 525 ft. Pull 1" out. Perforate casing. Run 1" to 700 ft. Pump Portland cement from TD to surface. Pull pipe and top off well. Squeeze well with cement and shut in at 200 PSI. Pump total of 30 sacks of cement. Well plugged.		<u>175</u>	<u>300</u>	<u>CSG - Casing</u>

Remarks: Contract # 37622. Control # 20130030-003. GPS NAD 27. Regular Section. GPS'ed by X Tony A.

Plugged Thru: TBG - Tubing Plugged Due to Compliance Issue:  Yes  No  
 District: 03 RECEIVED KANSAS CORPORATION COMMISSION  
APR 02 2014 Frank Guilfoyle (Technician)  
 CONSERVATION DIVISION WICHITA, KS Form: District Plugging Report - \_\_\_\_\_