

CARDS MUST
BE TYPED

STATE OF KANSAS
NOTICE OF INTENTION TO DRILL

CORRECTION

C-1
M-131

TO BE FILED WITH THE STATE CORPORATION COMMISSION
5 DAYS PRIOR TO COMMENCEMENT OF WELL

*API Number 15-185-246260000
(For office use only)

1. Operator F. G. Holl
Mailing Address 6427 East Kellogg
Street Address _____
City-State Wichita, Kansas Zip Code 67207
Contact person Elwyn H. Nagel Phone # 684-8481

Starting Date 6 / 28 / 1982
Month Day Year
County STAFFORD

2. Contractor Sterling Drilling Company
Street Address P. O. Box 129
City-State Sterling, Kansas Zip Code 67579

Sec. 15 Twp. 24 S. Rng. 15 West
2640 ft. from (N) (S) Line
Circle Correct Direction
1320 ft. from (E) (W) Line

3. Type of Equipment: Rotary: Air: _____ Cable Tools: _____
4. Well to be Drilled for: Oil: Gas: _____ SWD: _____ Input: _____
5. Well Classification: Infield: _____ Pool Exp: Wildcat: _____
6. Depth of Deepest Fresh Water within 1 mile: 100 ft.
7. Depth of Municipal Water Well within 3 miles: 130 ft.
8. Depth to Protect all Fresh Water (Table 1): 450 ft.
9. Amount of Surface Casing to be set: 250 ft.
10. (Surface Casing) Alternate No. 1: _____ Alternate No. 2:

Exact Spot Location C E/2
Nearest Lease Line 1320
Lease Name CUMMINS
Well No. 5-15
Est. Total Depth 4230

\$40.00 FEE PAID 6-21-82
REMARKS: Per # 29580

OPERATOR STATES THAT HE WILL COMPLY WITH K.S.A. 55-128
Signature of Operator Elwyn H. Nagel
Elwyn H. Nagel, Geologist

MAILED
JUL 19 1982
CONSERVATION DIVISION
WICHITA, KANSAS

RECEIVED
STATE CORPORATION COMMISSION

OCT 28 1983

CONSERVATION DIVISION
Wichita, Kansas

7 1/2 Hall

STERLING DRILLING CO.

BOX 129

STERLING, KANSAS 67579

WELL LOG ----- CUMMINS #5-15

Located: C E/2, Section 15-24S-15W, Stafford County, Kansas

OWNER: F. G. Holl

ROTARY DRILLING CONTRACTOR: Sterling Drilling Company

COMMENCED: June 24, 1982

COMPLETED: July 1, 1982

TOTAL DEPTH: 4265'

<u>LOG</u>	<u>CASING RECORD</u>
0 - 40 Surface Soil and Sand	Ran 6 joings 8 5/8", 24# new casing.
40 - 268 Shale	252.62' pipe set at 265' K.B. Cemented
268 - 706 Shale and Sand	with 210 sacks 60/40 Pozmix with 3% cc.
706 - 973 Shale, Sand, Red Beds	Plug down at 12:15 PM, 6-24-82, by
973 - 988 Anhydrite	Howco.
988 - 1650 Shale	
1650 - 4265 Lime and Shale	Plugged.

Deviation Surveys: 1/4° at 2168'
2° at 3799'

RECEIVED
STATE CORPORATION COMMISSION

OCT 28 1983

CONSERVATION DIVISION
Wichita, Kansas