

STATE OF KANSAS
STATE CORPORATION COMMISSION

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division,
State Corporation Commission,
800 Bittling Building,
Wichita, Kansas.

15-191-00853-0000

WELL PLUGGING RECORD

RECEIVED
04-08-30
APR 8 1936
Strike out upper line
when reporting plug-
ging of formations.

FORMATION PLUGGING RECORD

*paid
4/8/36
MA*

NORTH

| | | | |
|--|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |

Locate well correctly on above
640 A. Plat

Sumner County. Sec. 27 Twp. 32s. R. 2 (E) E (W).

Lease Name Veail Bailey **WELL NO. 1**
Lease Owner G. D. Robinson
Office Address Miami, Oklahoma
Character of Well (Oil, Gas or Dry) Dry Total Depth of Well 3415 Feet
Date, well, completed March 20, 1936
Application for plugging and log of well filed March 24th., 1936 193.
Application for plugging approved March 24th., 1936 193.
Plugging Commenced March 25th., 1936 193.
Plugging Completed March 31, 1936 193.
Reason for abandonment of well or producing formation Hole full of water
at 3415ft.

If a producing well is abandoned, date of last production XXXXXXXXXXXXXXXXXXXX
Was permission obtained from the Conservation Division or its agents before plugging was com-
menced? yes

Name of Conservation Officer who supervised plugging of this well W. G. Buffington
Producing formation Chatt Depth to top 3355ft. Bottom 3415

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

| Formation | Content | From | To | Size | Put In | Pulled Out |
|---------------|-------------|------|------|---------|--------|------------|
| Sand & Gravel | Fresh water | 115 | 120 | 15 1/2" | 146' | 63' |
| Sand | Salt water | 1865 | 1885 | | | |
| Sand | " " | 2346 | 2455 | 8 1/2" | 2463 | 2250' |
| Sand | " " | 2811 | 2824 | 6 5/8" | 2947 | 2905' |
| | | | | 12 1/2" | 766 | 760 |
| | | | | 10" | 1710 | 1710 |

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Filled 6" hole with mud 500' and pulled 6 5/8" casing, filled 8" hole with mud 300ft and pulled 8 1/2" casing, Filled 10" hole to bottom of 10" casing and pulled 10" casing, filled 10" hole with mud to bottom of 12 1/2" casing and pulled 12 1/2" casing, filled 15" hole with mud up to 190' and plugged in wood plug and filled with mud.

PLUGGING
FILE 27-32-2E
BOOK PAGE 29 LINE 25

(If additional description is necessary use BACK of this sheet)

Does the above conform strictly to the Conservation Division regulations? YES
Was exception made? NO If so describe _____
Correspondence regarding this well should be addressed to G. D. Robinson
Address Miami, Oklahoma.

STATE OF Oklahoma, COUNTY OF Ottawa, SS.

G. D. Robinson (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) G. D. Robinson
Miami Okla
(Address)

SUBSCRIBED AND SWORN to before me this 7 day of April, 1936

My commission expires Feb. 19, 1940 Esie Brown
Notary Public.

Robinson Drilling Company

Well - Baily #1

SE Cor SW $\frac{1}{4}$ NE $\frac{1}{4}$ Sec 27 Twp 32 R 2E Sumner County, Kansas

Drilling Commenced 12/26/35 Completed 3/22/36 D&A

| | | | | | | | |
|--------|------|--------------------|-----|--------|------|------|-----|
| Casing | 146' | 15 $\frac{1}{2}$ " | 70# | Pulled | 63' | Left | 83' |
| | 760 | 12 $\frac{1}{2}$ | 50 | | 760 | | |
| | 1710 | 10 | 40 | | 1710 | | |
| | 2463 | 8 $\frac{1}{4}$ | 32 | | 2253 | | 210 |
| | 2947 | 6 5/8 | 24 | | 2910 | | 37' |

| | | | |
|---------------------------------|------|---|------|
| Surface Soil & Clay | 30 | Blue Shale (1 $\frac{1}{2}$ BW @ 1005') | 1010 |
| Clay & Sand | 35 | Sandy Lime | 1015 |
| Red Mud | 62 | Broken Sand & Shale | 1035 |
| Yellow Clay | 85 | Blue Shale | 1065 |
| Blue Mud | 115 | Broken Sand | 1075 |
| Sand & Gravel (Fresh Water) | 120 | Sandy Lime | 1085 |
| Blue Shale | 133 | Blue Shale | 1096 |
| Lime | 135 | Gray Lime | 1108 |
| Blue Shale | 150 | Blue Shale | 1170 |
| Chalky Lime | 164 | Shale & Lime & Shells | 1190 |
| Gray Lime | 222 | Sand & Shale | 1239 |
| Broken Lime & Shale | 247 | Gray Lime | 1245 |
| Blue Shale | 257 | Blue Shale | 1260 |
| Lime | 285 | Sandy Lime | 1282 |
| Blue Shale | 301 | Blue Shale | 1298 |
| Red Rock | 312 | Brown Lime (Hard) | 1328 |
| Blue Mud | 314 | Blue Shale | 1350 |
| Lime | 348 | White Lime | 1365 |
| Blue Mud | 356 | Blue Shale | 1371 |
| Lime | 410 | Broken Lime & Shale | 1380 |
| Sand Lime (Showing Oil 1415-75) | 420 | Lime (Hard) | 1405 |
| Gray Lime & Chat (L BW Hr 450) | 475 | Red Shale | 1409 |
| Blue Mud | 480 | Sand (2 $\frac{1}{2}$ BW Hre Hr) | 1417 |
| Gray Lime | 490 | Sandy Lime | 1432 |
| Blue Shale | 513 | Blue Shale | 1436 |
| Red Rock | 519 | Gray Lime | 1443 |
| Gray Lime Hard | 537 | Blue Shale | 1450 |
| Blue Shale | 539 | Sand & Shale | 1480 |
| Gray Lime Hard | 561 | Sandy Lime | 1492 |
| Blue Shale (4 BW @ 550') | 574 | Gray Lime | 1505 |
| Red Mud | 585 | Blue Shale | 1510 |
| White Lime | 598 | Gray Lime (Hard) | 1528 |
| Blue Mud | 604 | White Lime | 1532 |
| Gray Lime | 612 | Gray Lime | 1562 |
| Shale & Lime Shells | 620 | Shale & Lime Shells | 1570 |
| Gray Lime | 630 | Black Slate | 1577 |
| Shale & Lime Shells | 640 | Blue Shale | 1585 |
| Gray Lime | 652 | Sandy Shale | 1630 |
| Red Rock | 657 | Gray Lime (Hard) | 1633 |
| Lime & Shale | 677 | Blue Shale | 1637 |
| Blue Shale | 685 | White Lime | 1655 |
| Gray Lime | 720 | Gray Lime | 1739 |
| Red Mud (Hole Caving) | 755 | Black Slate | 1742 |
| White Lime | 761 | Lime | 1770 |
| Gray Lime | 795 | Blue Shale | 1774 |
| Blue Slate | 825 | Gray Lime (Crevice @ 1798) | 1863 |
| Blue Mud (Soft) | 828 | White Sand (HFW @ 1863) | 1885 |
| Gray Lime | 848 | Blue Shale | 1903 |
| Blue Shale | 852 | Lime | 1913 |
| Gray Lime | 895 | White Sand | 1917 |
| Blue Shale | 906 | Blue Shale | 1934 |
| Gray Lime | 915 | Sand & Shale (Show of Oil) | 1944 |
| Blue Shale | 922 | Sandy Shale | 2026 |
| Lime Chert & Fossils | 929 | Shale & Lime Shells | 2050 |
| Blue Shale | 936 | Black Slate | 2055 |
| Gray Lime | 942 | Lime | 2057 |
| Sandy Shales | 949 | Blue Shale | 2077 |
| Gray Lime | 955 | Red Mud | 2082 |
| Green & Blue Shale | 974 | Gray Lime | 2107 |
| Sandy Lime | 1003 | Gray Sand (Water) | 2117 |

PLUGGING
 FILE SEC 27 TWP 32 R 2E
 BOOK PAGE 39 LINE 25

| | | |
|---------------------|------|-----------------------|
| Blue Shale | 2122 | |
| Gray Sand | 2125 | |
| Lime | 2140 | |
| Shale | 2145 | |
| Sandy Shale | 2150 | |
| Hard Gray Sand | 2158 | |
| Sandy Shale | 2179 | |
| Gray Sand Shale | 2253 | |
| Blue Shale | 2310 | |
| Lime | 2313 | |
| Sandy Shale | 2346 | |
| Gray Sand | 2455 | HFV 2390 |
| Shale | 2505 | |
| Sandy Shale | 2663 | |
| Black Slate | 2772 | |
| Sand | 2794 | Show of Oil 2772 |
| Blue Shale | 2805 | |
| Sandy Lime | 2811 | |
| Sandy | 2824 | HFV 2817 |
| Lime | 2897 | |
| Sandy Shale | 2925 | |
| Lime | 2945 | |
| Black Slate | 2952 | |
| Lime | 2991 | |
| Shale | 3008 | |
| Lime | 3014 | |
| Blue & Green Shale | 3021 | |
| Lime | 3038 | |
| Green Shale | 3047 | |
| Sand & Shale | 3077 | |
| Shale | 3088 | |
| Lime | 3120 | |
| Sandy Shale | 3130 | |
| Lime | 3221 | |
| Shale | 3277 | |
| Lime | 3284 | |
| Black Shale | 3292 | |
| Sand & Shale | 3310 | |
| Red Shale | 3315 | |
| Black, Blue & Green | | |
| Shale | 3355 | |
| Chatt | 3415 | Show Oil & Water 3404 |
| Total Depth | 3415 | HFV |