Kansas Corporation Commission One Point Stabilized Open Flow or Deliverability Test

| Type Test | : | | | | 0 | See Instruc | tions on Re | verse Side |) | | | | | |
|---|--------------------------|--------|--|---|---|-------------------------------|---|---|---------------------------------|--|--------------|-----------------------------|----------------------|---|
| ✓ Op | en Flow | , | | | Test Date | | | | ΔĐIJ | No. 15 | | | | |
| De | liverabil | ty | | | 10/23/14 | | | | | -20920 - | 7000 | | | |
| Company BEREXO | | ; | | | | | Lease G & G | | | | | 3 | Vell Nu | mber |
| County STANT | ON | | Location SE NE | | Section 21 | | TWP 30S | | RNG (E/V | V) | | | | ttributed |
| Field BEAUC | HAM | — Р | | • | Reservoir U. MOI | | | | | ering Conne | ection | | KC | 2 WICH |
| Completio | n Date | , | | | Plug Bac 5558' | k Total Dep | th | | Packer Se NONE | et at | | | ÛEC | 12 201 |
| Casing Si 4 1/2" | ize | | Weight 11.6 | | Internal D 4.000 | Diameter | Set : 560 | | Perfora 5118 | | | то 5130' | RE | CEIVED |
| Tubing Si 2 3/8" | ze | | Weight 4.7 | | Internal E 1.995 | Diameter | Set : 508 | | Perfor | ations | | То | | |
| Type Con | | | | | | d Productio | - | | Pump Uni YES-PI | t or Traveling | Plunger? | Yes | / No | |
| Producing | • | (Anr | nulus / Tubing) | | % C | arbon Diox | ide | | % Nitroge | n | | Gas Gra | avity - G | j _o |
| Vertical D | |) | | | | | sure Taps | | | | <u> </u> | (Meter F | | over) Size |
| 5124' | | | 40/0 | | 11 5 | | NGE | | | | | 3.068 | _ | |
| Pressure | Buildup |); { | Shut In | 2 z | 0 14 at 8 | <u>AM</u> | (AM) (PM) | Taken_10 |)/23 | 20 | 14 at 8 | 8 AM | (, | AM) (PM) |
| Well on L | ine: | ; | Started | 2 | 0 at | | (AM) (PM) | Taken | | 20 | at _ | | (| AM) (PM) |
| | | | | | | OBSERVE | D SURFAC | E DATA | | | Duration | of Shut- | _{in_24} | Hours |
| Static / Dynamic Property | Orific Size (inche | | Circle one: Meter Prover Pressure psig (Pm) | Pressure Differential in Inches H,0 | Flowing Temperature t | Well Head Temperature t | Welihead (P _w) or (F | | Wellhea (P _w) or | bing d Pressure (P _t) or (P _c) | Dura (Hou | | 1 ' | d Produced Barrels) |
| Shut-In | | | psig (1 iii) | menes 1120 | | | 165 | psia | psig 140 | psla | 24 | | | |
| Flow | | | | | | | | | | | | - | | |
| | | | | | | FLOW STE | REAM ATTR | IBUTES | | | | | | |
| Plate Coeffiec (F _b) (F Mcfd | ient ,) | Pro | Circle one: Meter or ver Pressure psia | Press Extension P _m xh | Grav Faci F _s | tor | Flowing Temperature Factor F ₁₁ | Fa | iation ctor : | Metered Flow R (Mcfd) | | GOR (Cubic Fe Barrel) | et/ | Flowing Fluid Gravity G _m |
| | | | | | | | | | | | | | | |
| (P _c) ² = | | | (P _w) ² = | | (OPEN FLO | , , | 'ERABILITY % (I | ') CALCUL P _e - 14.4) + | | | | (P _a); | ² = 0.20 | 07 |
| (P _c) ² - (I | • | (F | P _c) ² - (P _w) ² | hoose formula 1 or 2 1. $P_c^2 - P_d^2$ 2. $P_c^2 - P_d^2$ wided by: $P_c^2 - P_d^2$ | LOG of formula 1, or 2. and divide | P.2 - P.2 | Backpre Sto | essure Curve pe = "n" - or ssigned dard Slope | | og [] | Antii | | Op Deli Equals | en Flow verability R x Antilog Mcfd) |
| | | | | | | | | | _ | | | | | |
| Open Flo | w | | | Mcfd @ 14 | .65 psia | | Deliverat | oility. | | | Mcfd @ 1 | 4.65 psi | a a | |
| The | undersi | | d authority, on n, and that sai | d report is tru | | | - | | _ | e above repo | | | s know | ledge of 20 14 . |
| | | _ | For Commis | sion | | | | | | Chec | ked by | | | |

| exempt status und and that the fore | der Rule K.A.R. 82-3-304 on behalf of the ope going pressure information and statements | contained on this application form are true and |
|--|--|--|
| of equipment inst | allation and/or upon type of completion or up | ailable production summaries and lease records on use being made of the gas well herein named. |
| | est a one-year exemption from open flow tes rounds that said well: | KCC WICHITA |
| _ | is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into is on vacuum at the present time; KCC app is not capable of producing at a daily rate | oroval Docket Noin excess of 250 mcf/D all supporting documents deemed by Commission |
| | Signature: | J.H. B.L. eum Engineer |

instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.