

15-119-10065-0001

STATE OF KANSAS
STATE CORPORATION COMMISSION
CONSERVATION DIVISION
200 Colorado Derby Building
Wichita, Kansas 67202

Rev. 12-4-81
FORM CP-1

WELL PLUGGING APPLICATION FORM
File One Copy

API NUMBER 15-0WWO (of this well) See 5421
(This must be listed; if no API# is available, please note drilling completion date.)

LEASE OWNER Sage Drilling Co., Inc.

ADDRESS 202 S. St. Francis, Wichita, KS 67202 PHONE # (316)-263-6139

LEASE (FARM NAME) Jennings WELL NO. 1

WELL LOCATION C SW NE SEC. 9 TWP. 33 RGE. 30 (~~East~~) (West)
(OWWO 6155)

COUNTY Meade TOTAL DEPTH 5400 FIELD NAME _____

OIL WELL X GAS WELL _____ INPUT WELL _____ SWD WELL _____ D&A _____

WELL LOG ATTACHED WITH THIS APPLICATION AS REQUIRED? yes ACO-1 filed? yes
(If not, state reason why)

DATE AND HOUR PLUGGING IS DESIRED TO BEGIN After 11/1/84 and before 12/31/84

PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K.S.A. 55-128 OF THE RULES AND REGULATIONS OF THE STATE CORPORATION COMMISSION.

NAME OF COMPANY REPRESENTATIVE AUTHORIZED TO BE IN CHARGE OF PLUGGING OPERATIONS:

(1) Harold Frauli ADDRESS (1) P.O. Box 1884, Liberal, KS 67901
(2) Casey Coats (2) 202 S. St. Francis, Wichita, KS 67202
PHONE # (1) (316)-624-8388 (2) 316-263-6139

PLUGGING CONTRACTOR Sargent's Casing Pulling Service LICENSE NO. _____

ADDRESS 620 S. Lincoln, P.O. Box 506, Liberal, KS 67901 PHONE # (316) 624-7455

INVOICE COVERING ASSESSMENT FOR PLUGGING THIS WELL SHOULD BE SENT TO:

NAME Sage Drilling Co., Inc.

ADDRESS 202 S. St. Francis, Wichita, KS 67202 PHONE # (316)-263-6139

AND PAYMENT WILL BE GUARANTEED BY APPLICANT /OR ACTING AGENT.

PROCEDURE IS ATTACHED

SIGNED: Casey Coats
Applicant /or Acting Agent
Casey Coats, Production Engineer
DATE: October 29, 1984

RECEIVED
OCT 30 1984
10-31-84
CONSERVATION DIVISION
Wichita, Kansas

1

State of Kansas



JOHN CARLIN
MICHAEL LENNEN
R. C. (PETE) LOUX
PHILLIP R. DICK
JUDITH McCONNELL
BRIAN J. MOLINE

GOVERNOR
CHAIRMAN
COMMISSIONER
COMMISSIONER
EXECUTIVE SECRETARY
GENERAL COUNSEL

State Corporation Commission

CONSERVATION DIVISION

(Oil, Gas and Water)
200 Colorado Derby Building
202 West 1st Street
WICHITA, KANSAS 67202-1286

THIS NOTICE

October 31, 1984

JAN 31 1985

WELL PLUGGING NOTICE

EXPIRES

Jennings #1
C SW NE
Sec. 9-3S-30W
Meade County

Sage Drilling Co., Inc.
202 S. St. Francis
Wichita, KS 67202

Gentlemen:

This is your notice to plug the above subject well in accordance with the Rules and Regulations of the State Corporation Commission.

This notice is void after ninety (90) days from the above date.

Sincerely,

Jack M. McCord, Director

Please submit your proposal for plugging the above captioned well to
DIST. #1 302 West McArtor Dodge City, KS 67801

five days prior to plugging the well (KAR-82-3-113).



Sage Drilling Co., Inc.

202 SOUTH ST. FRANCIS
WICHITA, KANSAS 67202
316/263-6139

October 26, 1984

State Corporation Commission
Conservation Division
200 Colorado Derby Bldg.
Wichita, Kansas 67202

Re: Jennings #9-1 Plugging Procedure
C SW NE Sec. 9-33S-30W
Meade Co., KS

Gentlemen:

The following is the proposed procedure for the abandonment of the referenced well as obtained from Mr. Paul Luthi on October 24, 1984, with an addition on the recovery of some of the 8-5/8" casing, with increased cement amounts.

WELL DATA

Elevations: 2740.1' GL 2750.1' KB
Total Depth: (6155' OWWO) Washdown: 5400' PBTD-CIBP @ 5196'
Perforations: 5146-5151' (Marmaton)

Casing Size (In.)	Wt: #/ft.	Grade	Thread	Setting Depth - Ft.
13-3/8"	48	H-40	ST&C	631
8-5/8"	24	K-55	ST&C	2689 (800 sx. Probable TOC-1300')
4 1/2"	10.5	J-55	ST&C	5318 (TOC @ 4780')

PROCEDURE

1. Move in and rig up Sargent's Casing Pulling Service.
2. Unflange wellhead and weld on pull joint.
3. Pump 2 sx of hulls followed by 15 sx. cement down casing w/9 ppg. mud as displacement fluid.
4. Rig up jacks, work pipe to determine free point, and shoot 4 1/2" casing.
5. Pull 4 1/2" casing out of hole until the bottom is at 2740'. Pump 25 sx. of cement for the plug in and out of the 8-5/8" casing w/9 ppg. mud as displacement fluid.
6. Pull 4 1/2" casing the rest of the way out of the hole.
7. Weld on pull joint, work 8-5/8" casing, and shoot off.
8. Pull 8-5/8" casing out of the hole until bottom is at 1320'. Pump 50 sx. cement w/9 ppg. mud as displacement fluid.
9. Pull 8-5/8" casing out of the hole until bottom is at 650'. Pump 50 sx. cement to protect fresh water zones w/9 ppg. mud as displacement fluid. in and out of the 13-3/8" casing.
10. Pull 8-5/8" casing out of the hole.
11. Dump a 35 sx plug of cement from 40' to 0'.
12. Cut off 13-3/8" casing. Weld on a steel cap.

RECEIVED
STATE CORPORATION COMMISSION
OCT 30 1984
CONSERVATION DIVISION
Wichita, Kansas