FORM CP-2/3 Rev.01-84

|  | ( 1:0×00.45  | 15-119-10164-00                                 |
|--|--|---|
|  | 1060245  |   |
| To:<br>STATE CORP  | ORATION COMMISSION   | API NUMBER 15- Completed 7-28-55                |
| CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 |  | , sec. <u>18</u> , † <u>33</u> s, R <u>30</u> . |
|  |  | 1980 feet from M/S section il                   |
| TECHNICIAN   | 'S PLUGGING REPORT   | feet from M/E section li                        |
| Operator L   | Icense # 9123  | Lease Name Langhofer Well # 1                   |
| Operator:<br>Name&<br>Address  | Diamond Shamrock Exploration Co.                                       |   |
|  | P. O. Box 631  | Well-Total Depth 5700 185. 2                    |
|  | Amarillo, TX 79173   | Conductor Pipe: Sizefeet                        |
|  |  | Surface Casing: Size 9 5/8 feet 2630            |
| Abandoned  | Oll Well Gas Well_X  | Input Well D&A                                  |
| ·<br>Other well  | as hereinafter indicated   |   |
| Plugging C   | ontractor Sargent's Casing Puller                                      | License Number 6547                             |
| _  | Box 506, Liberal, KS 67901   |   |
| • •  |  | 4 Month: June Year:19 84                        |
|  | roposal received from  |   |
| -  | ame) Sargents  | (phone) 316-624-745                             |
|  | pump 2 sx hulls and 35 sx cement                                       |   |
|  | at 2650' with 30 sx cement   | JUN 07 1984                                     |
| 3rd plug   | at 1625' with 50 sx cement   | CONSERVATION DIVISION Wighting to               |
| 4th plug   | at 820' with 30 sx cement  | Wichita, Kansas                                 |
|  | solid bridge Plugging Propo<br>hulls - plug at 40 cement to<br>cement. |   |
| Plugging C   | perations attended by Agent?: Al                                       |   |
| Operations   | Completed: Hour: 2:00 pm Day:  | 6 Month: June Year:19 84                        |
| ACTUAL PLU   | IGGING REPORT 5 1/2 set at 5693'                                       | 13 3/8 set at 638' Perfs 5654-75'               |
| 1st plug   | pumped 2 sx hulls and 35 sx cemer                                      | t to bottom, 2nd plug at 2650' with 30 sx       |
| cement,  | 3rd plug at 1625' with 50 sx cemer                                     | at, 4th plug at 820' with 30 sx cement, 5th     |
| plugs - s  | solid bridge = hulls - plug at 40                                      | cement to surface with 10 sx cement.            |
|  |  |   |
|  |  |   |
|  | <del></del>  |   |
|  | yew recovered 2658 of 5 1/2" eacin                                     | g. Used Common Sacked cement by Sargent's.      |
| Remarks: Th  |  | DOCCCORN NO DAOY of Abia for                    |
|  | (If additional description is  | necessary, use BACK of this form.)              |
|  |  | signed Paul a. Luthe                            |