AFFIDAVIT OF COMPLETION FORM

This form shall be filed in duplicate with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ten days after the completion of the well, regardless of how the well was completed. Attach separate letter of request if the information is to be held confidential . If confidential, only file one copy. Information on side one will be of public record and side two will then be held confidential.
Circle one: Oil, Gas, Dry SWD, OWWO, Injection. Type and complete ALL sections. Applications must be filed for dual completion, commingling, SWD and injection, T.A. X Attach wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.).

KCC # (316) 263-3238. (Rules 82-2-105 & 82-2-125) API NO. 15-175-20,612-0000 OPERATOR Anadarko Production Company ADDRESS P. O. Box 351 COUNTY Seward Liberal, Kansas 67901 FIELD Shuck **CONTACT PERSON Mr. Paul Gatlin PROD. FORMATION DRY HOLE RECEIVED PHONE 316-624-6253STATE CORPORATION COMMISSION FINCHAM "B" PURCHASER MAY 1 1 1982 WELL NO. ADDRESS CONSERVATION DIVISION LOCATION C NW SW Wichita, Kansas 660 Ft. from West Line and DRILLING Johnson Drilling Co., Inc. CONTRACTOR 1980 Ft. from South Line of ADDRESS __ 3535 NW 58th Street, Suite 710 the SW/4SEC - 28 TWP - 335 RGE - 34W Oklahoma City, Oklahoma 73112 WELL PLAT PLUGGING Johnson Drilling Co., Inc. CONTRACTOR KCC ADDRESS KGS 3535 NW 58th Street, Suite 710 (Office Oklahoma City, Oklahoma 73112 Use) TOTAL DEPTH 6400' PBTD___NA -28 -SPUD DATE 4/15/82 DATE COMPLETED_4/28/82 ELEV: GR 2924' DF 2934' KB 2936' DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS Amount of surface pipe set and cemented 1668'. DV Tool Used? No AFFIDAVIT STATE OF KANSAS , COUNTY OF SEWARD SS, I, Paul OF LAWFUL AGE, BEING FIRST DULY SWORN UPON HIS OATH, <u> Campbell</u> DEPOSES THAT HE ISDivision Operations Manager (FOR)(OF) Anadarko Production Company OPERATOR OF THE FINCHAM "B" LEASE, AND IS DULY AUTHORIZED TO MAKE THIS AFFIDAVIT FOR AND ON THE BEHALF OF SAID OPERATOR, THAT WELL NO. 2 ON SAID LEASE HAS BEEN COMPLETED AS OF THE 28th DAY OF April , 19 82 , AND THAT ALL INFORMATION ENTERED HEREIN WITH RESPECT TO SAID WELL IS TRUE, AND CORRECT. FURTHER AFFIANT SAITH NOT. XWMII 14 SUBSCRIBED AND SWORN BEFORE ME THIS DAY OF BEVERLY J. WILLIAMS MY COMMISS Seward County, Kensas

IMP Appt. ExNovember 21, 1982

**The person who can be reached by phone regarding any questions concerning this information. Within 45 days of completion, a witnessed initial test by the Commission is required if the well produces more than 25 BOPD or is located in a Basic Order Pool.

	ING	WELL LOG	SHOW GEOLOGICAL MARKERS, LOGS F
Show	all important zones of porosity and	contents thereof; cored intervals, and all drill-stem tests, in-	OR OTHER DESCRIPTIVE INFORMAT
cludin	g depth interval tested, cushion used,	time tool open, flowing and shut-in pressures, and recoveries.	

	N DESCRIPTION;	CONTENTS, ETC		ТОР	res, and reco	том	NAME		DEPTH
								-	
Surface, Cla Sand & Redbe Redbed, Sand Anhydrite	eđ			0' 344' 1659'	7 16	44' 75' 69'			
Lime & Shale	e			1669' 2884'	· 28 64	84' 00'	•		·
			•				•		
						. }			
	•		•			}			
						Ì	• ,	·	•
	•						• • • • • • •		
	•		e Sengaran	1.	: 40.50	İ	-		
				W X	ł				
	,			j .					
			with Might	Maria 1					
	•							ļ	
,						ł		·	
						ł		i	
					-				
						j			
	,			1		Ì	•		
•	•			1		ĺ		Í	
						1	•		
		•		ł					
								1	
			;						
			;						
			;				,		
Report of all string	s set — surface,			c CASING	RECORD	(<u>New</u>) or (Used		
Report of all string	s set — surface, Size hale drilled	intermediate, Size casing set (in O.D.)			Туре с	ement	Sacks	Тур	e and percent additives
Purpose of string						ement		4% G	el
Purpose of string	Size hole drilled	Size casing set	Weight lbs/ft.	Setting depth	Type c Pozmia	ement	Sacks 550	Тур	el
Purpose of string	Size hole drilled	Size casing set (in 0.b.) 8-5/8"	Weight lbs/ft.	Setting depth	Type c Pozmia	ement	Sacks 550	4% G	el
Purpose of string	Size hole drilled	Size casing set (in 0.b.) 8-5/8"	Weight lbs/ft.	Setting depth	Type c Pozmia	ement	Sacks 550	4% G	el
Purpose of string	Size hole drilled	Size casing set (in 0.b.) 8-5/8"	Weight lbs/ft.	Setting depth	Type c Pozmia	ement	Sacks 550	4% G	el
Purpose of string Surface	Size hole drilled 12-1/4" LINER RECOR	Size casing set (in 0.D.) 8-5/8"	Weight Ibs/ft.	Setting depth	Type c Pozmia	ement	Sacks 550	4% G 3% C	el
Purpose of string Surface	Size hole drilled 12-1/4"	Size casing set (in O.D.)	Weight Ibs/ft.	Setting depth 1668'	Type c Pozmia	PERFOR	\$acks 550 200	4% G 3% C	el
Purpose of string Surface	Size hole drilled 12-1/4" LINER RECOR	Size casing set (in O.D.) 8-5/8"	Weight Ibs/ft.	Setting depth 1668'	Type c Pozmiz Commor	PERFOR	Sacks 550 200	4% G 3% C	el aCl
Purpose of string Surface	Size hole drilled 12-1/4" LINER RECOR	Size casing set (in O.D.) 8-5/8"	Weight Ibs/ft. 24#	Setting depth 1668'	Type c Pozmiz Commor	PERFOR	Sacks 550 200	4% G 3% C	el aCl
Purpose of string Surface	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co	Weight Ibs/ft. 24# ement	Setting depth 1668'	Pozmix Commor	PERFOR	Sacks 550 200	4% G 3% C	el aCl
Purpose of string Surface	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co	Weight Ibs/ft. 24# ement set at URE, SHOT,	Setting depth 1668'	Pozmix Commor	PERFOR	Sacks 550 200 RATION RECORDER Type	7ypc 4% G 3% C	el aCl pth interval
Purpose of string Surface	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co	Weight Ibs/ft. 24# ement set at URE, SHOT,	Setting depth 1668'	Pozmix Commor	PERFOR	Sacks 550 200 RATION RECORDER Type	4% G 3% C	el aCl pth interval
Purpose of string Surface	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co	Weight Ibs/ft. 24# ement set at URE, SHOT,	Setting depth 1668'	Pozmix Commor	PERFOR	Sacks 550 200 RATION RECORDER Type	7ypc 4% G 3% C	el aCl pth interval
Purpose of string Surface	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co	Weight Ibs/ft. 24# ement set at URE, SHOT,	Setting depth 1668'	Pozmix Commor	PERFOR	Sacks 550 200 RATION RECORDER Type	7ypc 4% G 3% C	el aCl pth interval
Purpose of string Surface	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co	Weight Ibs/ft. 24# ement set at URE, SHOT,	Setting depth 1668'	Pozmix Commor	PERFOR	Sacks 550 200 RATION RECORDER Type	7ypc 4% G 3% C	el aCl pth interval
Purpose of string Surface , ft. B	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co Packer: ACID, FRACT, ant and kind of	Weight lbs/ft. 24# ement vet at URE, SHOT, material used	Setting depth 1668'	Type c Pozmix Commor	PERFOR	Sacks 550 200 RATION RECOR	Type 4% G 3% C	el aCl pth interval
Purpose of string Surface	LINER RECOR	Size casing set (in O.D.) 8-5/8" RD Sacks co Packer: ACID, FRACT, ant and kind of	Weight lbs/ft. 24# ement vet at URE, SHOT, material used	Setting depth 1668' Shots CEMENT SQ	Type c Pozmix Commor	PERFOR SI	Sacks 550 200 RATION RECOR	Type 4% G 3% C	el aCl pth interval