

8-8-87

To: 1 030838
 STATE CORPORATION COMMISSION
 CONSERVATION DIVISION - PLUGGING SECTION
 200 COLORADO DERBY BUILDING
 WICHITA, KANSAS 67202

API NUMBER 15- 129-20,881-0000

S/2 NE SE, SEC. 3, T 33 S, R 43 W/X

1830 feet from S section line

660 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5447

Lease Name Soupiset D Well # 1

Operator: Cities Service Oil & Gas Corp.

County Morton 152.25

Name & Address

3545 NW 58th Street

Well Total Depth 4700 feet

Oklahoma City, OK 73112

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 1371

Abandoned Oil Well Gas Well Input Well SHD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Exeter Drilling Company License Number 3098

Address Denver, CO

Company to plug at: Hour: 7 a.m. Day: 8 Month: 8 Year: 19 87

Plugging proposal received from Steve Milinichik

(company name) Cities Service Oil & Gas Company (phone) 316-675-2293

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 4700' with 50 sx cement, 2nd plug at base of surface pipe plus 30' with

50 sx cement, 3rd plug at 700' with 50 sx cement,

4th plug at 40' with 10 sx cement, 5th plug to circulate rathole with 10 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by James Kapp

(TECHNICIAN)

Plugging Operations attended by Agent: All Part None X

Operations Completed: Hour: 1:05 p.m. Day: 8 Month: 8 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 4758-4600' with 60 sx cement,

2nd plug at 1420-1300' with 50 sx cement,

3rd plug at 700-560' with 40 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Remarks: Used Class H cement by Halliburton.

(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 8-12-87

Signed Steve Kapp

(TECHNICIAN)

INV. NO. 17799 SEP 17 1987

FORM CP-2/3
Rev. 01-84

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date

July 20, 1987

API Number 15

129-20,881

OPERATOR License #

5447

Belly Booner/Chen

S/2 NE/4 SE/4

Sec. 3

Twp. 33

S. Rg. 43

East

X West

Name

Cities Service Oil and Gas Corp.

1830

Ft. from South Line of Section

Address

3545 NW 58th Street

660

Ft. from East Line of Section

City/State/Zip

Oklahoma City, OK 73112

(Note: Locate well on Section Plat on reverse side)

Contact Person

Raymond Hui

Nearest lease or unit boundary line

660

feet

Phone

(405) 949-4268

County

Morton

CONTRACTOR License #

316-677-4427

Lease Name

Soupsiet D

Well # 1

Name

Unknown at this time

Ground surface elevation

3595

feet MSL

City/State

Exeter

Domestic well within 590 feet

yes

X no

Well Drilled For

X Oil

Storage

Infield

Type Equipment

X Mud Rotary

Gas

Inj

X Pool Ext.

Air Rotary

OWWO

Expl

Wildcat

Cable

Municipal well within one mile

yes

X no

Depth to bottom of fresh water

300'

Depth to bottom of usable water

700' 400'

Surface pipe by Alternate

1 X 2

Surface pipe planned to be set

1320'

Conductor pipe required

20'

Projected Total Depth

5100

feet

(Producing) Upper Morrow L-1 and L-2 Sand

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date

7/20/87

Signature of Operator or Agent

Raymond Hui

Raymond Hui, Accounting Control Analyst

For KCC Use:

Conductor Pipe Required

feet; Minimum Surface Pipe Required

420

feet per Alt.

①

This Authorization Expires

7-21-88

Approved By

R.H. 7-21-87

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep

4700

or formation with

50

feet of

60/40 Pozmix

2nd plug @ ft. deep

2900 30' 30"

or formation with

50

feet of

60/40 Pozmix

3rd plug @ ft. deep

1400 700

or formation with

50

feet of

60/40 Pozmix

4th plug @ ft. deep

750 40

or formation with

50

feet of

60/40 Pozmix

5th plug @ ft. deep

40

or formation with

10

feet of

60/40 Pozmix

(2) Rathole to surface minus 5 feet

10

(b) Mousehole to surface minus 5 feet

10

PUSHER

TD 4700

SURFACE PIPE 878 @ 1371

ANHYDRITE

STARTING TIME & DATE

11:00 AM 8-8-87

COMPLETION TIME & DATE

4:58 PM 8-8-87

1st PLUG @

4758 4700 FT. W/ 60 SX

2nd PLUG @

1420 1300 FT. W/ 50 SX

3rd PLUG @

750 40 FT. W/ 40 SX

4th PLUG @

40 10 FT. W/ 10 SX

RAT HOLE CIRCULATED W/ 10

MOUSE HOLE CIRCULATED W/ 10

WATER WELL PLUGGED W/

CEMENT COMPANY Class H

TECHNICIAN

Class H

Wallace

STATE OF KANSAS

AUG 11 1987

CHIEF SURVEILLANCE DIVISION
Wichita, Kansas