	TYPE	· AFF	IDAVIT OF COMPLETI	ON FOR	um ',	ACO-1 WE			
	SIDE ONE						Ç	Ompt	
F	Two (2) copies of this form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within thirty (30) days after the completion of a well, regardless of how the well was completed.  Attach separate letter of request if the information is to be held confidential. If confidential, only file one copy. Information on Side One will be of public record and Side Two will then be held confidential.  Applications must be made on dual completion, commingling, salt water disposal,							30) l. idential. lic	
С	injection a	rjection and temporarily abandoned wells.  X Attach one copy only wireline logs (i.e. electrical log, sonic log, gamma ray leutron log, etc.). (Rules 82-2-105 & 82-2-125) KCC# (316) 263-3238 No Log							
		<u>6568</u>							
	OPERATOR	PERATOR KAISER-FRANCIS OIL COMPANY				15-129	<u>-20690 1</u>	00 <u>00</u>	
	ADDRESS	P.O. BOX 21468			COUNTY_	MORTON	<u> </u>	<del></del>	
		TULSA, OKLAHOMA	74121-1468		FIELD	MUSTAN	<u>IG</u>		
÷	PHONE 1 (918) 494-0000					PROD. FORMATION MORROW			
	PURCHASER_	COLORADO INTERST	ATE GAS		LEASE	SIMPSO	IN .		
	ADDRESS	P.O. BOX 1087			WELL NO.	3		<u> </u>	
	COLORADO SPRINGS, COLORADO 80944				WELL LOCATION 150' SW OF C NE SE				
	DRILLING	GABBERT - JONES	DRILLING		3406 Ft.	. from	N	Line and	
	CONTRACTOR, ADDRESS	830 SUTTON PLACE			766 Ft.	from	E	Line of	
	ADDRESS	MICHITA VANCAC			the SE	(Qtr.)SEC	llTWP	33 RGE43 (W	
		WICHITA, KANSAS	67202			WELL PLA		(Office	
	PLUGGING CONTRACTOR				<del></del>		<del></del>	Use Only	
	ADDRESS				1 1		·	KCC /	
					<b> </b>			KGS	
	TOTAL DEPTH	4750	PBTD470	<u> </u>	1 1			SWD/REP_ PLG.	
•	SPUD DATE_	<u>2-14-84</u> DATE	COMPLETED 4-27-	84	<b> </b>	ij		1	
	ELEV: GR 3564 DF 3567 KB 3569								
		H (CABLE) (ROTAR)	-		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			7	
	DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE N/A								
	Amount of surface pipe set and cemented [33]' DV Tool Used? NO .								
	THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Gas) Shut-in Gas, Dry, Disposal, Injection, Temporarily Abandoned, OWWO. Other								
	ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.								
	•		AFFTDAVT	т					
	A F F I D A V I T  GEORGE B. KAISER , being of lawful age, hereby certifies								
•	that:  I am the Affiant, and I am familiar with the contents of the foregoing Affidavit.								
	The stateme	enţs and allegation	as contained there	in are	true and	d correct	regoing	Afridavit.	
	SUBSCRIBED AND SWORN TO BEFORE ME this 17th day of MAY								
	19 84 . 1		_		~ -			- <del></del> ,	
	•				á	$\sim 1$	(n. )	11.	
	· · · · · · · · · · · · · · · · · · ·				(NOTARY PUBLIC)				
	MY COMMISSI	ON EXPIRES:	10-4-87				•	SUE MILLS	
	MY COMMISSION EXPIRES: 10-4-87  ** The person who can be reached by phone regarding any question Eleoncerning this information.  **MAY 2 3 1984  **COMMISSION								
			•	C	/UNon	ישאטי	-10/ <b>V</b>		
				,	CONSERVATION Wighlia, Ka	V DIVIO	<b>C</b> 2		
					~, Ka	nsas ISION			
	* ***	* *** ***	•					y's	

. 51.155

SIMPSON

SEC. 11 TWP, 33 RGE. 43 (W)

OPERATOR WELL NO FILL IN WELL INFORMATION AS REQUIRED: SHOW GEOLOGICAL MARKETS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION. Show ell important zones of porceity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries. FORMATION DESCRIPTION, CONTENTS, ETC. NAME BOTTOM DEPTH X Check if no Drill Stem Tests Run. LANSING 3305 KANSAS CITY 3460 \_ MARMATON 3603 CHEROKEE 4054 MORROW SHALE 4440 MORROW SD 4490 If additional space is needed use Page 2, Side 2 Report of all strings set - surface, intermediate, production, etc. CASING RECORD (New) or (Used) Size cosing set Type and percent additives Size hole drilled Purpose of string Weight Ibs/ft. Setting depth Socks 2% CC HALL.LITE 500 SURFACE 12 1/4 8 5/8 24 1331 3% CC CLASS H 200 HALL. THIX 7 7/8 5 1/2 15.5 4746 PROD. SET 150 LINER RECORD PERFORATION RECORD Size & type GEO-/8" VANN Bettom, ft. Secks coment Shots per ft. Depth interval NONE 3 3/8" 4494 - 4520 (EVERY OTHER TUBING RECORD FOOT) etting depth Packer set at 2 3/8 4441 4441 ACID, FFACTURE, SHOT, CEMENT SQUEEZE RECORD Depth interval treated Amount and kind of material used NONE 0.3.114 0 Date of first preduction Producing method (flowing, pumping, gas lift, etc.) Gravity WOPL FLOWING Estimated % Gas-oll ratio Production -I.P. CFPB 1,500 Disposition of gas (vented, used on lease or sold) Perforations TO BE SOLD 4494 - 4520