

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
266 N. Main St., Ste. 220  
Wichita, KS 67202-1513

API Well Number: 15-051-05979-00-00  
Spot: NWSWSE Sec/Twnshp/Rge: 29-11S-17W  
1022 feet from S Section Line, 2281 feet from E Section Line  
Lease Name: GLATHART Well #: 1  
County: ELLIS Total Vertical Depth: 3606 feet

Operator License No.: 30606  
Op Name: MURFIN DRILLING CO., INC.  
Address: 250 N WATER STE 300  
WICHITA, KS 67202

String	Size	Depth (ft)	Pulled (ft)	Comments
L1	5.5	3615		
L2	4.5	3460		
PROD	7	3597		150 SX
SURF	15.5	62		50 SX

Well Type: OIL UIC Docket No: \_\_\_\_\_ Date/Time to Plug: 02/12/2015 12:30 PM  
Plug Co. License No.: 30606 Plug Co. Name: MURFIN DRILLING CO., INC.  
Proposal Rcvd. from: CRAIG HERTEL Company: MURFIN DRILLING CO., INC. Phone: (785) 623-0123

Proposed Plugging Method: 2 7/8" tubing and packer stuck in hole at 3402. Perforations: 3591' - 3597'

Plugging Proposal Received By: PAT STAAB WitnessType: COMPLETE (100%)  
Date/Time Plugging Completed: 02/12/2015 3:15 PM KCC Agent: PAT STAAB

Actual Plugging Report:

Perf Tech perforated at 1850', 1332' and 750'. Has cement to there according to log. Murfin ran in hole with tubing to top of fish at 3300'. Quality rigged to tubing and mixed and pumped 90 sx cement w/250 # hulls mixed in. Pulled tubing to 1850' and pumped 125 sx cement w/250 # hulls mixed in to circulate cement to surface. Pulled tubing. Rigged to 4 1/2" casing and pumped 15 sx cement to pressure with 300 psi. Shut in pressure 300 psi. Rigged to 7" casing and pumped 5 sx cement to pressure with 150 psi. Shut in pressure 150 psi. 15 1/2" casing full of cement.

GPS: 39.06243 -099.23089  
1022' FSL 2281' FEL  
NE NW SW SE

Perfs:

Top	Bot	Thru	Comments
3591	3597		

Remarks: QUALITY OILWELL CEMENTING TICKET # 922

Plugged through: TBG

MAR 04 2015 *CM*

District: 04

KCC WIC *Signed*

*[Signature]*

(TECHNICIAN)

*CM*

FEB 25 2015

RECEIVED

FEB 13 2015