To:. 1 1 1 0 1 2 7 5 - 7 5 STATE CORPORATION COMMISSION Whichita State Office Bidg Plugging Section 130 S. Market, Room 2078 Whichita, KS 67202 TECHNICIAN'S PLUGGING REPORT		API NUMBER 15-	89-20,751 - 5000
		C SW SW, SEC.	14 , T 34 s, R 35 W/X
		660 feet from S section line	
			feet from E section line
	License / 5447		elter A Well 1 2
U ?	OXY USA Inc.	CountySteven	219.38
Address	P.O. Box 300	Well Total Dept	6750 feet
	Tulsa, OK 74102	Conductor Pipe:	Sizefeet
		Surface Casing:	Size 8 5/8 feet 1754
Abandoned	d OII Well Gas WellX		,
	Il as hereinafter indicated		
	Contractor Halliburton & J.W. Gibs		Managar Number
			Cicense Number
	11:30 a.m.	13	
Company	to plug at: Hour: 11:30 a.m. Day:	Month:	5 Year:19 97
Plugging	proposal received from Reid W	11son	
(company	Halliburton Services		(phone) 316-629-3578
were:	5½" at 6749' w/225 sx cement, PBTD 6	220', Perfs at 6304	-05, 6231-38, 6242-51, 6100-01,
	set CIBP at 6050', 2nd plug spot 10		(1// 7(1
3rd plug	s spot 50 sx cement at 1780,		
	s spot 40 sx cement at 600°,		E 11.91
	s spot 10 sx cement at 40'.		5-16-97
Jul plug			
-	Plugging Propo	osal Received by	Mike Maier (TECHNICIAN)
Blunging	One-tions attended by Agent?	X 2+	1.5 %
	g Operations attended by Agent?: A		7 6
Operatio	ons Completed: Hour: 7:15p.m. Day:		
ACTUAL P	PLUGGING REPORT 1st plug set CIBP	at 6050° with 2 sx	cement on top,
Ran free	point, 2nd plug perforated at 3200-2	305', squeezed off	Hugoton/Council Grove with 200 st
eement,	3rd plug pulled to 1779 and spotte	d 50 sx cement, dis	placed with gel,
4th plug	pulled to 627 and spotted 40 sx ce	ment, displaced wit	th gel,
5th plug	pulled to 40° and spotted 10 sx cem	ent.	
9 -	Ugod Halliburtan Lita coment 2% as	hy Hallihanton E	lacerrand 10001 of FbII agains
Remarks	: Used Halliburton Lite cement 2% cc		
L.M	MATAMA	/	3
r Christ.	/Vaxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	\$1	Il a leas
DATE .	MAY 2 0 1997	Signed Sam	(TECHNICIAN)

FORM CP-2/3