

1050876

JAN 25 1987

API NUMBER 15-025-20,975-0000

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 5654

Operator: Rine Drilling Company
Name & Address: 300 West Douglas, Suite 600
Wichita, KS 67202

C SW SW, SEC. 15, T 34 S, R 24 W/E

660 feet from S section line

4620 feet from E section line

Lease Name Gabbert 1-15 Well # 1

County Clark 190.13

Well Total Depth 5850 feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 850

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Rine Drilling Company License Number 5654

Address 300 West Douglas, Suite 600, Wichita, KS 67202

Company to plug at: Hour: 3 p.m. Day: 25 Month: 1 Year: 19 87

Plugging proposal received from Lloyd Evert

(company name) Rine Drilling Company (phone) 316-267-1333

Remarks: were: to fill hole with heavy mud and spot cement through drill pipe Elevation 1953' GL
1st plug at Base Anhydrite with 50 sx cement, 2nd plug at 30' below base of surface pipe
with 50 sx cement, 3rd plug at 450' with 25 sx cement, 4th plug at 40-0' with 10 sx cement,
5th plug to circulate rathole with 10 sx cement, 6th plug to circulate mousehole with
10 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 4:30 p.m. Day: 25 Month: 1 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 1500' with 50 sx cement,

2nd plug at 870' with 50 sx cement, 3rd plug at 450' with 25 sx cement,

4th plug at 40 to 0' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement,

6th plug to circulate mousehole with 10 sx cement.

STATE CORPORATION COMMISSION

JAN 30 1987

CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.

(If additional description is necessary, use BACK of this form.)

INVOICED

(check) did not observe this plugging.

DATE 2-2-87

Signed Richard M. Lacey (TECHNICIAN)

INV. NO. 16047

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date January 10, 1987 month day year

API Number 15-025-20,975-0000

OPERATOR: License # 5654 Name Rine Drilling Company Address 300 W. Douglas, Suite 600 City/State/Zip Wichita, KS 67202 Contact Person E. J. Rine Phone 316-267-1333

C SW SW Sec. 15 Twp. 34 S, Rg. 24 660' Ft. from South Line of Section 4620' Ft. from East Line of Section

CONTRACTOR: License # 5654 Name Rine Drilling Company City/State Wichita, KS 67202

(Note: Locate well on Section Plat on reverse side) Nearest lease or unit boundary line 660' feet County Clark

Well Drilled For: Oil SWD Infield X Mud Rotary X Gas Inj X Pool Ext. Air Rotary OWWO Expl Wildcat Cable

Lease Name Gabbert 1-15 Well # 1 Ground surface elevation 1953' feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no

If OWWO: old well info as follows: Operator N/A Well Name Comp Date Old Total Depth

Depth to bottom of fresh water 100' Depth to bottom of usable water 200' Surface pipe by Alternate: 1 X 2 Surface pipe planned to be set 800' Conductor pipe required 90' Projected Total Depth 5,950' feet Formation Chester

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 12/31/86 Signature of Operator or Agent E. J. Rine Title President

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 200 feet per Alt. This Authorization Expires 7-1-87 Approved By 12-31-86

Handwritten notes: 1-13-87 Set 800-850'

C SW SW Sec. 15 Twp. 34 S, Rg. 34 X East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 1,200' B Any. feet depth with 50 sxs of Halliburton 60/40 pozmix. 2nd plug @ 900' 30' B = 1.0 sp feet depth with 50 sxs of " 6% gel " 3rd plug @ 40' 4.50' feet depth with 10 sxs of Solid Plug 4th plug @ 40-0 feet depth with 10 sxs of 5th plug @ feet depth with sxs of (2) Rathole with 10' (b) Mousehole with .10'

Table with columns for PUSHER, TD, SURFACE PIPE, ANHYDRITE, STARTING TIME & DATE, COMPLETION TIME & DATE, 1st PLUG @, 2nd PLUG @, 3rd PLUG @, 4th PLUG @, RAT HOLE CIRCULATED W/, MOUSE HOLE CIRCULATED W/, WATER WELL PLUGGED W/, CEMENT COMPANY, TECHNICIAN. Includes handwritten entries like 'Lloyd Sweet', '5850 FORMATION', '8 1/2 @ 850', '14 3/8' ELEVATION', '3:00 PM 1-25-87', '4:30 PM 1-25-87', '1500 FT. W/ 50 SX', '270 FT. W/ 50 SX', '450 FT. W/ 20 SX', '40 FT. W/ 10 SX', '10', 'W.W.', 'H. J. Rine', '6/40 Poz 6%'.

STATE CORPORATION COMMISSION JAN 30 1987 CONSERVATION DIVISION Wichita, Kansas