

STATE OF KANSAS  
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
212 No. Market  
Wichita, Kansas

Stevens County. Sec. 34 Twp. 33S Rge. 37 (E) W (W)

Location as "NE/CNWSW" or footage from lines 1370' FNL & 1370' FEL

Lease Owner Anadarko Production Company

Lease Name Brubaker "A" Well No. 2

Office Address Box 351 Liberal, Kansas 67901

Character of Well (completed as Oil, Gas or Dry Hole) Oil

Date well completed 9-20 19 69

Application for plugging filed 6-12 19 69

Application for plugging approved 6-16 19 69

Plugging commenced 7-17 19 69

Plugging completed 7-17 19 69

Reason for abandonment of well or producing formation non-economical

If a producing well is abandoned, date of last production April 19 19 69

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well Edgar Eves

Producing formation St. Louis Depth to top 6562' Bottom 6575' Total Depth of Well 6600 Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
St. Louis	Oil	6562'	6575'	8 5/8"	1711'	None
* Morrow	Dry	5880'	5882'	4 1/2"	6600'	2350'
* Morrow	Dry	5875'	5877'			
* This zone perforated during attempted work over in April, 1969.						

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.


Baker CIBP set @ 5950'  
Mixed 15 sacks of cement and pumped plug to 5620'  
Spotted 35 sacks cement from 900' - 800'  
Spotted 15 sacks cement from 45' - 0'  
Plugging completed at 5:00 P.M. 7-17-69

RECEIVED  
STATE CORPORATION COMMISSION  
JUL 29 1969  
CONSERVATION DIVISION  
Wichita, Kansas

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor Sargent's Casing Pulling Service

Address 102 W. Walnut Liberal, Kansas 67901



Kansas, COUNTY OF Seward, ss.

V. K. Downey (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) *V. K. Downey*

Box 351 Liberal, Kansas 67901 (Address)

SUBSCRIBED AND SWORN TO before me this 24th day of July, 19 69

My commission expires My Commission Expires April 21, 1973

*John E. Shockley*  
John E. Shockley Notary Public.

15-189-00040-0000

DRILLER'S LOG

WELL NAME Drubaker "A" #2 COMPANY OPERATING Anadarko Production Company  
 ADDRESS of COMPANY Box 351, Liberal, Kansas  
 WELL LOCATION C 1/2 NE 1/2  
1259 ft. North of South line,  
1259 ft. East of West line; Sec. 35 Twp. 33 Rge. 37, Stevens County, Kansas  
 DRILLING STARTED August 30, 1962 DRILLING COMPLETED September 21, 1962  
 WELL COMPLETED September 29, 1962 WELL CONNECTED \_\_\_\_\_, 19\_\_\_\_  
 ELEVATION 2104.2 ft. Ground Level CHARACTER OF WELL (Oil, Gas, or Dry Hole) Oil

OIL OR GAS SANDS OR ZONES - PERFORATIONS - ACIDIZING AND FRACTURING INFORMATION						
Name	From	To	No. of Shots	Gallons Used	Kind Used	
St. Louis	6572	6574	12			
St. Louis	6562	6565	16	750	Acid	

RECEIVED  
 STATE CORPORATION COMMISSION  
 JUN 16 1969  
 CONSERVATION DIVISION  
 Wichita, Kansas

CASING RECORD

Size	Amount Set	Sacks of Cement	Amount Pulled
8 5/8"	1711	700	00
5 1/2"	6803	305	00

FORMATION RECORD

Formation	Top	Bottom	Formation	Top	Bottom
Sand	0	122	Lime & Chert	5188	5283
Sand & Red Mud	122	1521	Lime	5283	5552
Red Mud & Anhydrite	1521	1712	Lime & Sand	5652	5872
Sand & Red Mud	1712	2003	Sand	5872	5962
Anhydrite & Sand	2003	2072	Lime & Sand	5962	6136
Sand, Anhydrite & Lime	2072	2500	Lime & Sand	6136	6143
Sand & Lime	2500	4333	Lime	6143	6600
Lime	4333	4570	Total Depth	6600	
Lime & Sand	4570	4611			
Lime	4611	4615			
Lime & Sand	4615	4703			
Sand	4703	5136			

RESULTS of INITIAL PRODUCTION TEST: Flowed 153 BB in 9 hrs.