o: ,	1 031420	AP1 NUMBER 13-173 21, 370;
TATE CORPO	RATION COMMISSION	NW NE , SEC. 31 , T 33 S, R 34 W/XX
Vichita State	Office Bldg PLUGGING SECTION Room 2078 //-/9	
Wichita, K	Room 2078 S 67202	Teat those a section time
	S PLUGGING REPORT	1980 feet from E section line
	4549	Lease Name_Van Auken A Well 5 1
	Anadarko Petroleum Corporation	County Seward 214.5%
perator: _		
Address _	P.O. Box 351	Well Total Depth 6600 feet
_	Liberal, KS 67905-0351	Conductor Pipe: Sizefeet
		Surface Casing: Size 8 5/8 feet 1686
-	Can Wall	
		Input Well SWD Well D&A X
	as hereinafter indicated	
Plugging C	ontractor Cheyenne Drilling, I	Inc. License Number 5382
		46
	-	
		19 Month: 11 Year:19 <u>96</u>
Plugging P	proposal received from John Sch	nilling
(company n	Anadarko Petroleum Corp.	(phone) 316-624-6253
	o fill hole with heavy mud and spo	
1st plug a	at 3000° with 100 sx cement, 2nd	plug at 1710' with 50 sx cement,
3rd plug a	at 720° with 40 sx cement, 4th pl	Lug at 40-0' with 10 sx cement,
5th plug t	to circulate rathole with 15 sx ce	ement,
6th plug t	to circulate mousehole with 10 sx	cement.
		posal Received by Steve Durrant
	Flugging FF0	(TECHNICIAN)
Blucalna	Operations attended by Agent?:	AllPartNoneX
		: 19 Month: 11 Year:1996
ACTUAL PL	LUGGING REPORT 1st plug at 3000'	with 100 sx cement,
2nd plug a	at 1710, with 50 sx cement,	
3rd plug a	at 720' with 40 sx cement,	· ·
/th plug a	at 40-0' with 10 sx cement,	
	to circulate rathole with 15 sx ce	omont
Jul prug t		ment,
6th plug t	to circulate mousehole with 10 sx	cement.
Dansele.	Used 60/40 Pozmix 6% gel by Hall	liburton.
Manal Ka	(If additional description	is necessary, use BACK of this form.)
11 NaV	Quality of this plugging.	St. Danout
. L. Laker	NOV 2.6 1006	Signed Care month
DATE -	1101 0-1000	(TECHNICIAN)