

15-175-00104-00-00

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission
Conservation Division
800 Bitting Building
Wichita, Kansas

FILE NO. 38-23

LOCATION C-7E-200

SEC. 16 TWP. 34 RGE. 31-00

Dry Hole X Abandoned Oil Well _____ Abandoned Gas Well _____

I have today completed supervision of plugging of:

Well No. _____ Lease E. H. Hood

Operator Lanskan Co. Inc. W. H. Riggian Address 305 W. 10th St. Liberal - Kans.

Field _____ County Seward.

Total Depth 5959 Feet.

(Describe briefly the manner in which the well was plugged)

Surface Pipe 13'-577ft. Circulated with cement
9" casing set at 247ft - 400 sacks of cement. Plugged
back with mud to 247ft - Set Plug & 30 sacks of cement
at 247ft. Shot off & pulled 100ft of 9" casing - Pumped
in 40 sacks of heavy Plug & 450 sacks of cement.
Total cement Plug in the 13' surface Pipe - 550.5 -
Completed & turned over to Mr. E. H. Hood to be used
as water Well - Pumped in by Halliburton
Barnes & Sons. Plugging Contractors

RECEIVED
STATE CORPORATION COMMISSION

SEP 24 1952

9-24-52
CONSERVATION DIVISION
Wichita, Kansas

C. M. Stasch
District Conservation Agent

Date 9-20-52

PLUGGING

FILE SEC 16 T 34 R 31-23
BOOK PAGE 37 LINE 23