

6 030429-

API NUMBER 15-063-20,897-00-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

C 5/2 SWDE SEC. 15, T 11 S, R 31 WF

2970 feet from (S) section line

1980 feet from (E) section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5198

Lease Name Tatum Well # 1

Operator: A Scott Ritchie

County Gove 151.06

Name & Address 125 N. Market, Ste 950

Well Total Depth 4648 feet

Wichita, Kansas

Conductor Pipe: Size \_\_\_\_\_ feet

67202

Surface Casing: Size 8 5/8 feet 302 ✓

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Murfin Drlg. License Number 6033

Address Wichita, Kansas

Company to plug at: Hour: A.M. Day: 21 Month: MAY Year: 19 85

Plugging proposal received from Ployd

(company name) Murfin Drlg. (phone) 5-06-85

were: 8 5/8 act @ 302 With hole full of no less than 36 lbs. mud  
and no loss of fluid. Spot Cement plugs with 4 1/2" O.P.  
Order 190 at 50/50 pg 6 bag 3 pec 1st. flo. seal 8 5/8 W.P. Allied  
Cement.

Plugging Proposal Received by Carl Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 7:30 AM Day: 21 Month: 4 Year: 19 85

ACTUAL PLUGGING REPORT Spot O.P. @ 2540 displace 25 act Cement mix. laydown  
O.P. to 1600 displace 100 act Cement. 1st. flo. Seal. laydown O.P.  
to 300' displace 40 act. Cement laydown O.P. Push W.P. to  
Kelly depth. fill hole to base of Celler with 10 act Cement mix.  
displace 15 act Cement mix in cathole with joint of O.P.  
Plug complete.

Remarks: Elev. 29876h Only 2516-45 Mississippi 4648 no near prod.  
(If additional description is necessary, use BACK of this form.)

I (did / did not) observe this plugging.

DATE 5-21-85

Signed Carl Goodrow  
(TECHNICIAN)

INV. NO. 8079