

To: 1 090266  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

4-10  
API NUMBER 15- 175-21,305-0000 19 ✓  
C SE \_\_\_\_\_, SEC. 11, T 31 S, R 32 W/E

TECHNICIAN'S PLUGGING REPORT

Operator License # 4742  
Operator: Texaco E&P, Inc.  
Name & Address P.O. Box 2700  
Pampa, TX 79066-2700

1320 feet from S section line  
1320 feet from E section line  
Lease Name M. Collingwood Well # 3  
County Seward  
Well Total Depth 5800 188.50 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 1711

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor H-40 Drilling Inc. License Number 30692

Address 251 N. Water, Ste. 10, Wichita, KS 67202

Company to plug at: Hour: 7:30 a.m. Day: 10 Month: 4 Year: 19 93

Plugging proposal received from John Schlenz  
(company name) H-40 Drilling Inc. (phone) 316-263-2043

work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1710'  
1st plug at 5500-5300' with 75 sx cement, 2nd plug at 2820' with 100 sx cement,  
3rd plug at 1720' with 50 sx cement, 4th plug at 700' with 50 sx cement,  
5th plug at 40' with 10 sx cement, 6th plug to circulate rathole with 15 sx cement,  
7th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 2 p.m. Day: 10 Month: 4 Year: 19 93

ACTUAL PLUGGING REPORT 1st plug at 5500-5300' with 70 sx cement,  
2nd plug at 2850' with 100 sx cement, 3rd plug at 1715' with 50 sx cement,  
4th plug at 600' with 50 sx cement,  
5th plug at 40' with 10 sx cement,  
6th plug to circulate rathole with 15 sx cement,  
7th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel By Halliburton.

(If additional description is necessary, use BACK of this form)  
I (XXX) did not observe this plugging.

INVOICED  
DATE 4-20-93  
REV. NO. 37594

APR 15 1993  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION  
Wichita, Kansas  
Signed \_\_\_\_\_ (TECHNICIAN)

EFFECTIVE DATE: DISTRICT # 3547

State of Kansas NOTICE OF INTENTION TO DRILL 175-21,305 - 0000 ALL BLANKS MUST BE FILLED FORM MUST BE SIGNED

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 3-15-93 month day year

Spot 0 SE Sec 11 Twp 31 S. Rg 32 East West

OPERATOR: License # 4742 Texaco E&P, Inc. Name: P. O. Box 2700 Address: Pampa, TX 79066-2700 City/State/Zip: J. M. Barnum Contact Person: 806-665-1876 Phone:

1,320 feet from South / North line of Section 1,320 feet from East / West line of Section IS SECTION: X REGULAR IRREGULAR

(NOTE: Locate well on the Section Plat on Reverse Side) County: Seward

Lease Name: M. Collingwood well # 3 Field Name: Cheney One SW Wildcat

Is this a Prorated/Spaced Field? yes XX no Target Formation(s): Morrow

CONTRACTOR: License # Unknown at this time #40 Name:

Well Drilled For: Well Class: Type Equipment:

- Oil ... Enh Rec ... Infield ... Mud Rotary
Gas ... Storage ... Pool Ext. ... Air Rotary
GUVU ... Disposal ... Wildcat ... Cable
Seismic; ... # of Holes ... Other

Nearest lease or unit boundary: 1,320' Ground Surface Elevation: 2,835' feet MSL

Water well within one-quarter mile: yes X no Public water supply well within one mile: yes X no

Depth to bottom of fresh water: 405' Depth to bottom of usable water: 550'

Surface Pipe by Alternate: X 1 2 Length of Surface Pipe Planned to be set: 1,700' 1,400'

Length of Conductor pipe required: 5,800' Projected Total Depth: St. Genevieve

Formation at Total Depth: St. Genevieve Water Source for Drilling Operations: well farm pond X other

If GUVU, old well information as follows:

Operator: Well Name: Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes X no If yes, true vertical depth:

DNR Permit #: Will Cores Be Taken? yes X no If yes, proposed zone:

Bottom Hole Location:

570' Alt. I Req.

Exp. 9/4/93

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

It is agreed that the following minimum requirements will be met:

Pusher John Schlegel SPUD DATE 4-3-93 INIT. mlw LENGTH SURFACE PLANNED 1715 RESERVE PIT STATUS- REMOVE FLUID LINED after salt sect. bbls. when done bbls. RATHOLED AHEAD? Y N SIZE HOLE SURFACE PIPE 8 1/2 @ 1717 CONDUCTOR ANHYDRITE T- B-1710 ELEVATION TD 5800 FORMATION RAN PIPE @ DV TOOL ALT II DONE SX Y 70 N 5500 Ft. W/ 75 SX 5320 Ft. W/ 2820 Ft. W/ 100 SX Anhydrite Base @ 600 Ft. W/ 1/2 Base Anhyd. @ 700 Ft. W/ 50 SX 1/2, 1/2 Plug @ 1715 Ft. W/ 50 SX Bottom Surface @ 1720 Ft. W/ 50 SX 40' Plug @ 40 Ft. W/ 10 SX RAT HOLE CIRC/W 15 SX MOUSE HOLE W/10 SX WATER WELLS SX (Irr. Well Pond Hauling) STATE CORPORATION COMMISSION RECEIVED APR 1 1993 REGISTRATION DIVISION DATE 4-10-93 COMPLETION TIME 2: (AM/PM) DATE 4-10 CEMENT COMPANY Hall