To: 1 020476 STATE GORPORATION COMMISSION	2/5 API NUMBER 15- Drilled 11/12/55 1 3 P
CONSERVATION DIVISION - PLUGGING SECTION 20G-COLORADO DERBY BUILDING	NE SW , SEC. 20 , T 34 S, R 43 WARK
WICHITA, KANSAS 67202 TECHNICIAN'S PLUGGING REPORT	1980 feet from S section line
Operator License # 4549	3300 feet from E section line
Operator: Anadarko Petroleum Corporation	Morton
Name& Address P.O. Box 351	County Morton
Liberal, KS 67905-0351	Well Total Depth 4224 /37.28 feet
HIBERAL, KB 07705-0351	
About and Oll Mall	Surface Casing: Size 8 5/8 feet 1016
	Input Well D&A
Other well as hereinafter Indicated	
	License Number 6547
Address 620 S. Lincoln, Liberal, KS 6790	
Plugging proposal received from Don Horto	on
(company name) Sargent's	(phone)316-624-7455
vere: 5½" at 4222' w/600 sx cement, PBTD	4197', Perfs at 4162-81'
1st plug pump 1 sx hulls and 20 sx cement	at 4162-4030',
2nd plug pump 50 sx cement at 1050',	
3rd plug pump 40 sy cement at 650!	
4th plug pump 10 sx cement at 40 to -4^{\dagger} .	
Plugging Prop	osal Received by Glenn Barlow
	(TECHNICIAN)
Plugging Operations attended by Agent?: A	
•	15 Honth: 7 Year: 19 92
2nd plug pumped 50 sx cement at 1050',	thulls and 20 sx cement at 4162-4030',
3rd plug pumped 40 sx cement at 650',	
4th plug pumped 10 sx cement at 40 to -4'.	
Heavy mud between all plugs.	STATE RECOVERY
	Recovered 1225' of 5½" casing.
Remarks: Used common cement by Sargent's.	Recovered 1225' of 5½" casing.
I MY OLCE D	Recovered 1225' of 5½" casing. Necessary, use BACK of this toring Necessary Necessa
$X = \{0^{-1}\}$	Signed Sensi & Barbar 1919N
WY. NO. 35873.	(TECHNICTAN)
WY, NO.	FORM CP-2/3