

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bitting Building
Wichita, Kansas

NORTH

X			

Locate well correctly on above
Section Plat

Seward County. Sec. 36 Twp. 34 Rge. 32 (H) (W)
 Location as "NE/CNW/SW" or footage from lines C SW NW
 Lease Owner LANSEKAN COMPANY, INC.
 Lease Name Wood Well No. 3-B
 Office Address 714 West Olympic Blvd., Los Angeles 15, Calif.
 Character of Well (completed as Oil, Gas or Dry Hole) Dry Hole
 Date well completed November 8, 19 53
 Application for plugging filed November 7, 19 53
 Application for plugging approved _____ 19 _____
 Plugging commenced November 8, 19 53
 Plugging completed November 14, 19 53
 Reason for abandonment of well or producing formation _____
No oil or gas producing formations encountered.
 If a producing well is abandoned, date of last production _____ 19 _____
 Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well Mr. M. A. Rives
 Producing formation None Depth to top _____ Bottom _____ Total Depth of Well 6092' Feet
 Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
<u>Sand</u>	<u>Water</u>	<u>0'</u>	<u>440'</u>	<u>13-3/8</u>	<u>668'</u>	<u>None</u>
				<u>9-5/8"</u>	<u>2,631'</u>	<u>697'</u>

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Halliburton mixed and spotted through D/P 50 sks. common cement: 6063' - 5901'; heavy rotary drlg. mud from 5901' to 2552'; Halliburton mixed and spotted through D/P 40 sks. common cement: 2552' - 2451'; Heavy drlg. mud from 2451' to 547'; Halliburton mixed and spotted through D/P 30 sacks common cement: 547' - 509'; Halliburton mixed and spotted common cement from 20' to surface.

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor Schafer Drilling Company
 Address 612 Liberty Bank Bldg., Oklahoma City, Oklahoma

STATE OF Kansas, COUNTY OF Seward, ss.
W. H. Riggins (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) W. H. Riggins
918 N. Grant St., Liberal, Kansas
 (Address)

SUBSCRIBED AND SWORN TO before me this 16th day of November, 1953

My commission expires 12-18-56

Helen Beckman
 Notary Public.

24-7366-5 3-53-20M

PLUGGING
 FILE SEC 36 T 34 R 32W
 BOOK PAGE 143 LINE 6

STATE OF KANSAS
 NOV 20 1953
 CONSERVATION DIVISION
 WICHITA, KANSAS

WELL LOG

LANSEKAN COMPANY, INC.
 Wood #3-B
 C. SW NW Sec. 36, 34-S, 32-W,
 Seward County

Drilling Contractor:
 Schafer Drilling Company
 612 Liberty Bank Building
 Oklahoma City, Oklahoma

0'	-	200'	-	Sand, Shale, Shells
200'	-	440'	-	Shells, Sand, Gravel
440'	-	665'	-	Shale and Red Beds
665'	-	1270'	-	Red Beds, Shale, Sand
1270'	-	1475'	-	Shale and Shells
1475'	-	1828'	-	Anhydrite and Shale
1828'	-	1950'	-	Shale and Shells
1950'	-	2132'	-	Anhydrite and Lime
2132'	-	2277'	-	Shale and Shells
2277'	-	2367'	-	Anhydrite and Shale
2367'	-	2470'	-	Shale and Lime
2470'	-	2512'	-	Anhydrite and Lime
2512'	-	2634'	-	Lime and Shale
2634'	-	2640'	-	Lime
2640'	-	3664'	-	Lime and Shale
3664'	-	3817'	-	Lime
3817'	-	4098'	-	Shale and Lime
4098'	-	4264'	-	Shale
4264'	-	4574'	-	Shale and Lime
4574'	-	4580'	-	Shale
4580'	-	4792'	-	Lime
4792'	-	4918'	-	Lime and Shale
4918'	-	4944'	-	Lime
4944'	-	5030'	-	Lime and Shale
5030'	-	5221'	-	Lime
5221'	-	5288'	-	Lime and Shale
5288'	-	5385'	-	Lime
5385'	-	5422'	-	Lime and Chert
5422'	-	5637'	-	Lime and Shale
5637'	-	5676'	-	Shale
5676'	-	6102'	-	Lime and Shale
6102'	-		-	T. D.

NOTE: All above depths Drillers' K. B. measurements.
 K.B. - 10' above G.L.
 Elevation - 2729' G.L.

