1091032 STATE CORPORATION COMMISSION

API NUMBER	15-189-22,3	29-0000	)			
180'N E/2 NE SE	SEC. 4	, Т 33	s,	R	35	W

CONSERVATION DIVISION - PLUGGING SECTION 2160 FEET FROM SOUTH SECTION LINE
WICHITA STATE OFFICE BLDG., 130 S. MARKET 330 FEET FROM EAST SECTION LINE
WICHITA, KANSAS 67202 LEASE NAME <u>HJV CENTRAL LIFE "A"</u> WELL # 1
TECHNICIAN'S PLUGGING REPORT   5 COUNTY STEVENS 2/1.25
OPERATOR LICENSE # 4549 WELL TOTAL DEPTH 6500 FEET
OPERATOR: ANADARKO PETROLEUM CORPORATION PRODUCTION CSG: SIZE @' WITHSX
NAME AND <u>PO BOX 351</u> SURFACE CASING: SIZE <u>8%"</u> @ <u>1729</u> ' WITHSX
ADDRESS LIBERAL, KS 67905-0351
ABANDONED OIL WELLGAS WELLINPUT WELLSWD WELLD/AX
OTHER WELL AS HEREINAFTER INDICATED
PLUGGING CONTRACTOR NORSEMAN DRILLING, INC. LICENSE NUMBER 3779
ADDRESS 200 E FIRST ST., SUITE 307 WICHITA, KS 67202
COMPANY TO PLUG AT: HOUR: 4:00 PM DAY: 05 MONTH: 01 YEAR: 2000
PLUGGING PROPOSAL RECEIVED FROM KEN
(COMPANY NAME) NORSEMAN DRILLING, INC. (PHONE) 316-265-9408
WERE:
1ST PLUG AT 3140' WITH 100 SX CEMENT. 2ND PLUG AT 1760' WITH 50 SX CEMENT.
3RD PLUG AT 650' WITH 40 SX CEMENT. 4TH PLUG AT 40' WITH 10 SX CEMENT.
5TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.
6TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.
PLUGGING PROPOSAL RECEIVED BYSTEVE MIDDLETON
PLUGGING OPERATIONS ATTENDED BY AGENT?: ALLPARTNONEX
OPERATIONS COMPLETED: HOUR: 9:00 PM DAY: 05 MONTH: 01 YEAR: 2000
ACTUAL PLUGGING REPORT LOAD HOLE WITH HEAVY MUD SPOT PLUGS THRU DRILL PIPE
1ST PLUG AT 3140' WITH 100 SX CEMENT. 2ND PLUG AT 1760' WITH 50 SX CEMENT.
3RD PLUG AT 650' WITH 40 SX CEMENT. 4TH PLUG AT 40' WITH 10 SX CEMENT. RECEIVED STATE CORPORATION COMMISSION
5TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CEMENT.
6TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.
REMARKS: USED 60/40 POZMIX 6% GEL BY HALLIBURTON. CONSERVATION DIVISION Wichita, Kansas
hill of MIF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I (DID/NOT) OBSERVE THIS PLUGGING.

SIGNED

(TECHNICIAN)