STATE OF KANSAS S 2 (

WELL PLUGGING RECORD

00 Colorado Derby Bullding ich&ta, Kansas 67202	TYPE OR PRINT	LEASE 1	
•	TYPE AD BOINT		NAMEBeal
		WELL NO	JMBER <u>#1</u>
	NOTICE: Fill out completed and return to Cons. Div office within 30 days.	5. DIV. 4980_	Ft. from S Section Line
	office Within 30 (2970	Ft. from E Section Line
EASE OPERATOR Jay Boy Oil,	Inc.		8 TWP. 30 RGE. 3 (E) or (W)
ooress 224 E. Douglas, Su	ite 425, Wichita,	Ks.67202 _{county}	Sumner
HONE#(316 <u>-264-3700</u> OPER#	ATORS LICENSE NO. 45	69 Date We	all Completed
haracter of Well Oil	•	Pluggli	ng Commenced <u>3-9-90</u>
Oll, Gas, D&A, SWD, Input, Wa	ater Supply Well)	Pluggli	ng Completed 4-11-90
he plugging proposal was appr	oved on <u>April</u>	11, 1990	(date)
y Johnny Sander			CC District Agent's Name).
s ACO-1 filed?	f not, is well log atta	achod? With a	pplication
roducing Formation	Depth to Top_	Bot	tom
how depth and thickness of a			
OIL, GAS OR WATER RECORDS		CASING REC	ORD
Formation Content	From To S	lze Put In	Pulled out
		5/8" 222	None 3,200
·	4	1/2" 4334 '	3,200
	hods used in introduct	na It into the b	ting where the mud fluid was
laced and the method or methore used, state the charace Dumped sand to 4200' and 2518" Pulled 100 joints cement at 1000', 3 sacks	ter of same and dept 4 sacks cement. Sl of 4-1/2" casing. I at 600' and 60 sac Rockhold Engineering	th placed, from hot casing at Halliburton pl cks circulated	feet tofeet each set. 3520',3210',3000',2700'& lugged well with 35 sacks I to surface from 270'.
laced and the method or methore used, state the charace Dumped sand to 4200' and 2518" Pulled 100 joints cement at 1000', 3 sacks lame of Plugging Contractor ddressBox_698, Gt	ter of same and dept 4 sacks cement. Si of 4-1/2" casing. I at 600' and 60 sac Rockhold Engineering d, Kansas 67530	th placed, from hot casing at Halliburton placed circulated ng, Inc.	feet tofeet each set. 3520',3210',3000',2700'8 lugged well with 35 sacks to surface from 270'.
laced and the method or methor used, state the character of Pulled 100 joints cement at 1000', 3 sacks lame of Plugging Contractor Box 698, Gt. Bendiame of PARTY RESPONSIBLE FOR	ter of same and dept 4 sacks cement. Si of 4-1/2" casing. I at 600' and 60 sac Rockhold Engineering d. Kansas 67530 PLUGGING FEES:	th placed, from hot casing at Halliburton placed with the Halliburton placed with the hold of the hold	feet tofeet each set. 3520',3210',3000',2700'& lugged well with 35 sacks to surface from 270'.
laced and the method or methors are used, state the charac Dumped sand to 4200' and	ter of same and dept 4 sacks cement. Si of 4-1/2" casing. I at 600' and 60 sac Rockhold Engineering d, Kansas 67530	th placed, from hot casing at Halliburton placed with the	feet tofeet each set. 3520',3210',3000',2700'& lugged well with 35 sacks to surface from 270'.