

To: <sup>2</sup> 040394  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

2-17-88  
API NUMBER 15- 191-22,051-0000  
SEC. 18, T. 30 S, R. 2 W/EX  
3630 feet from S section line  
990 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5146

Lease Name Har El Acres Well # 1

Operator: Rains & Williamson

County Sumner 109.20

Name & Address 220 W. Douglas, Suite 435

Well Total Depth 3360 feet

Wichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 374

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Rains & Williamson License Number \_\_\_\_\_

Address Wichita, KS 67202

Company to plug at: Hour: \_\_\_\_\_ Day: 17 Month: 2 Year: 19 88

Plugging proposal received from Mel White

(company name) Rains & Williamson (phone) \_\_\_\_\_

were: 35 sxs @1250', 35 sxs @425', 25 sxs @60', 10 sxs in rathole

Plugging Proposal Received by District #2 Office  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 23:15 Day: 17 Month: 2 Year: 19 88

ACTUAL PLUGGING REPORT Drill pipe was run to 1250' where 35 sxs cement was spotted

in place. The drill pipe was pulled to 425' where 35 sxs cement was spotted.

The drill pipe was pulled from hole. A wiper plug was pushed to 50' and

circulated the hole with 25 sxs cement. The rathole was circulated w/10 sxs.

RECEIVED  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION

Remarks: 60/40 202  
(if additional description is necessary, use BACK of this form.)

MAR 21 1988

INVOICED observe this plugging.

CONSERVATION DIVISION  
Wichita, Kansas

Signed \_\_\_\_\_  
(TECHNICIAN)

DATE 3-25-88

WK

WV. NO. 20208