

R

DISTRICT CONSERVATION AGENT'S REPORT

TO:

State Corporation Commission
Conservation Division
800 Bitting Building
Wichita, Kansas

FILE NO. 10-12

LOCATION NE-C

SEC. 16 TWP. 35 RGE. 33

Dry Hole X Abandoned Oil Well _____ Abandoned Gas Well _____

I have today completed supervision of plugging of:

Well No. 1 Lease SWarth

Operator Standard Oil Co. Address W. Lysses - Kans. Bldg. #291

Field _____ County Seward

Total Depth 6345 Feet.

(Describe briefly the manner in which the well was plugged)

Surface Pipe 13" - 645 ft. Circulated with Cement
8 1/2" casing - 2482 ft. Circulated with cement - 100 sacks
of cement Pumped on bottom of hole. Mud to 2810 ft
100 sacks cement - 250 bbls of mud Pumped in at 2810 ft.
Mud to within 25 ft of the surface Plug & 10 sacks
of cement. Halliburton Oil Well Cementing Co
Pumped in all Cement & Heavy Mud.

PLUGGING
FILE SEC 16 TWP 35 R 33
BOOK PAGE 10 LINE 12

C. M. Stoughton 1-22-48
District Conservation Agent
Date 1-18-48
JAN 23 1948
CONSERVATION DIVISION