API	NUMBER	15-129	-21,6	504- 0 0	200				
c n/	2 NE NE	SEC.	26	. Т	32	s.	R	4.0	W

CONSERVATION DIVISION - PLUGGING SECTION330 FEET FROM NORTH SECTION LINE
WICHITA STATE OFFICE BLDG., 130 S. MARKET <u>660</u> FEET FROM EAST SECTION LINE
WICHITA, KANSAS 67202 LEASE NAME <u>SPEAKMAN</u> WELL # <u>1-126</u>
TECHNICIAN'S PLUGGING REPORT COUNTY MORTON 202.3/
OPERATOR LICENSE # 32468
OPERATOR: PIONEER OIL COMPANY PRODUCTION CSG: SIZE " FEET
NAME AND RR 4, BOX 142B SURFACE CASING: SIZE 856 @ 1530' WITHSX
ADDRESS LAWRENCEVILLE, IL 62439
ABANDONED OIL WELLGAS WELLINPUT WELLSWD WELLD/A X
OTHER WELL AS HEREINAFTER INDICATED
PLUGGING CONTRACTOR NORSEMAN DRILLING LICENSE NUMBER 3779
ADDRESS 200 E FIRST ST, STE., 307 WICHITA, KS 67202
COMPANY TO PLUG AT: HOUR: 11:00 AM DAY: 06 MONTH: 07 YEAR: 2000
PLUGGING PROPOSAL RECEIVED FROM DICK
(COMPANY NAME) NORSEMAN DRILLING (PHONE) 316-265-9408
WERE:
1ST PLUG AT 3000' WITH 100 SX CEMENT. 2ND PLUG AT 1530' WITH 50 SX CEMENT. 3RD PLUG AT 690' WITH 25 SX CEMENT. 4TH PLUG AT 40' WITH 10 SX CEMENT. 5TH PLUG CIRCULATE RAT HOLE WITH 15 SX CEMENT. 6TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT.
PLUGGING PROPOSAL RECEIVED BY STEVE DURRANT
plugging operations attended by agent?: Allpartnone _X
OPERATIONS COMPLETED: HOUR: 2:00 PM DAY: 06 MONTH: 07 YEAR: 2000
ACTUAL PLUGGING REPORT LOAD HOLE WITH HEAVY MUD SPOT PLUGS THRU DRILL PIPE
1ST PLUG AT 3000' WITH 100 SX CEMENT. 2ND PLUG AT 1530' WITH 50 SX CEMENT. 3RD PLUG AT
690' WITH 25 SX CEMENT. 4TH PLUG AT 40' WITH 10 SX CEMENT. 5TH PLUG TO CIRCULATE RAT HOLE
WITH 15 SX CEMENT. 6TH PLUG TO CIRCULATE MOUSE HOLE WITH 10 SX CEMENT. KANSAS CORPORATION COMMISSION
AUG 16 2000
REMARKS: USED 60/40 POZMIX 6% GEL BY ALLIED. (IF ADDICTIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.) CLOREST SHOW BIVISHON OATER CONTROL OF THIS PLUGGING. SIGNED SIGNED (TECHNICIAN) FORM CP-2/3
$\frac{10000 \text{ Grad}}{100000000000000000000000000000000000$