

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
266 N. Main St., Ste. 220
Wichita, KS 67202-1513

API Well Number: 15-153-20525-00-00
Spot: NENWSWNW Sec/Twnshp/Rge: 20-1S-32W
1520 feet from N Section Line, 645 feet from W Section Line
Lease Name: WILHELM UNIT Well #: 21
County: RAWLINS Total Vertical Depth: 4310 feet

Operator License No.: 34530
Op Name: BOW CREEK OIL COMPANY, GENERA
Address: 1304 EISENHOWER RD.
HAYS, KS 67601

String	Size	Depth (ft)	Pulled (ft)	Comments
PROD	7	4303		590 SX
SURF	10.75	357		250 SX

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 04/24/2015 1:00 PM
Plug Co. License No.: 33755 Plug Co. Name: QUALITY PLUS OILFIELD SERVICES, LLC
Proposal Rcvd. from: TONY STROUP Company: BOW CREEK OIL Phone: (785) 650-1738

Proposed Plugging Method: Ordered 560 sx 60/40 pozmix 4% gel cement, 16 sx gel, 4 sx CC and 800 # hulls.
10 3/4" surface casing set at 357' w/250 sx cement. 7" production casing set at 4303' w/590 sx cement. TD 4310'. PBTD
4157'. Perforations: 3818' - 3822' and 3915' - 4096'.

Plugging Proposal Received By: CASE MORRIS Witness Type: COMPLETE (100%)
Date/Time Plugging Completed: 04/24/2015 9:30 PM KCC Agent: DARREL DIPMAN

Actual Plugging Report:

Ran tubing to 3980'. Pumped 16 sx gel followed by 75 sx cement with 3% CC mixed with 500 # hulls. Pulled tubing to 2725'. WOC for 2 1/2 hours. Connected to tubing and pumped 200 sx cement. Pulled tubing to 1685' and pumped 150 sx cement w/100 # hulls. Pulled tubing to 700' and pumped 120 sx cement. Cement to surface. Pulled tubing to surface. Topped 7" production casing with 15 sx cement. Visible cement in 10 3/4" casing.

GPS: 39.95470N -100.94209W

Perfs:

Top	Bot	Thru	Comments
4048	4052		
4022	4026		
4007	4009		
3949	3952		
3924	3937		
3915	3917		LKC
3818	3822		OREAD

Remarks: QUALITY OILWELL CEMENTING TICKET # 1259

Plugged through: TBG

District: 04

Signed Darrel Dipman (TECHNICIAN) CM

5/6/15 CPM

APR 27 2015

Received KANSAS CORPORATION COMMISSION Form CP-2/3

MAY 01 2015

CONSERVATION DIVISION WICHITA, KS