STATE CORPORATION COMMISSION OF KANSAS

3 STATE CORPORATION COMMISSION OF KANSAS OIL & GAS CONSERVATION DIVISION WELL COMPLETION FORM ACO-1 WELL HISTORY DESCRIPTION OF WELL AND LEASE	API NO UFRIGINA 189-20,434-0001
Operator: License #4549	1250 Feet from %(N)(circle one) Line of Section
Name:ANADARKO PETROLEUM CORPORATION	660 Feet from ### (circle one) Line of Section
AddressP. O. BOX 351	Footages Calculated from Nearest Outside Section Corner: NE, SE, NW or SW (circle one)
City/State/ZipLIBERAL, KANSAS 67905-0351	Lease NameNELL "A" Well # _1 Field NameGENTZLER FIELD
Purchaser:	Producing Formation _COUNCIL GROVE
Operator Contact Person:J. L. ASHTON	Elevation: Ground3132.8 KBNA
Phone (_316_)624-6253	Total Depth6210
Contractor: Name:NA	Amount of Surface Pipe Set and Cemented at1705 Fee
	Multiple Stage Cementing Collar Used?X Yes N
Wellsite Geologist:NA	If yes, show depth set3157 Fee
Designate Type of Completion New Well Re-EntryX Workover	If Alternate II completion, cement circulated from
Oil SWD SICW Temp. Abd SIGW	feet depth to w/ sx cmt
Dry Other (Core, WSW, Expl., Cathodic, etc)	Drilling Fluid Management Plan REWORK 94 2-21-95 (Data must be collected from the Reserve Pir)
If Workover:	NOT APPLICABLE
Operator:ANADARKO PETROLEUM CORPORATION	Chloride contentbbl
Well Name: _NELL "A" NO. 1	Dewatering method usedNATURAL EVAPORATION
Comp. Date2/15/79Old Total Depth6210XABANDONED LOWER ZONE; No LONGER DUALLY COM	Location of fluid disposal if hauled offsite:
5/28/85 NA 6/2/85 Date of START Date Reached TD Completion Date of WORKOVER WORKOVER	County Docket No
- Room 2078, Wichita, Kansas 67202, within 120 days of the Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information on 12 months if requested in writing and submitted with the months). One copy of <u>all</u> wireline logs and geologist well	be filed with the Kansas Corporation Commission, 130 S. Market spud date, recompletion, workover or conversion of a well. side two of this form will be held confidential for a period of e form (see rule 82-3-107 for confidentiality in excess of 12 report shall be attached with this form. ALL CEMENTING TICKETS lls. Submit CP-111 form with all temporarily abandoned wells.
with and the statements herein are complete and correct to the	· .
Signature 10hh // 108 cm JOHN M. DOLAN TitleSENIOR TECHNICAL ASSISTANT Date 5 Subscribed and sworn to before me this 19th day of () 19 90.	K.C.C. OFFICE USE ONLY Letter of Confidentiality Attached C Wireline Log Received Geologist Report Received Distribution
Notary Public Delna S. Schoeder	KCC SWD/Rep NGPA Cher (Specify)
Date Commission Expires 7/8/94 KANSAS	CORPORATION CO AMISSION

DEBRA S. SCHROEDER
Notary Public - State of Kansas My Appl. Expires

MAY 2 2 1995

Form ACO-1 (7-91)

SIDE	TWO
------	-----

Operator NameANAD			Lease Name	NELL "A"_		_ Well #	1	
- 40 - 77		East	County	STEVENS				
Sec19 Twp335	S_ Rge37	[x] West						
INSTRUCTIONS: Show interval tested, ti hydrostatic pressures if more space is nee	me tool open a , bottom hole to	nd closed, flowing emperature, fluid reco	and shut-in pre	ssures, whet	her shut-in pre	ssure reacl	hed static level,	
Drill Stem Tests Tak (Attach Additiona		Yes X No	Log	Formatio	n (Top), Depth a	and Datums	X] Sample	
Samples Sent to Geological Survey Yes X No		Name		Тор		Datum		
Cores Taken Yes X No			SEE	SEE ORIGINAL DRILLERS LOG (ATTACHED)				
Electric Log Run (Submit Copy.)		Yes X No						
List All E.Logs Run:				.**				
			. ,	a go en desemberar y sel de				
		,						
	<u> </u>	CASING RECORD	' 		INAL COMPLETION			
	Report al	ll strings set-condu	U ل∟ New ل∟ ctor, surface, î		production, etc	:.		
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs./Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives	
SURFACE	12-1/4	8-5/8	24.0	1705	POZ/COMMON	550/200	4% GEL, 2% CACL 3% CACL	
PRODUCTION	7-7/8	5-1/2	15.5	6209	SS POZ/LT.WT. SS POZ	160/450 - 150 +	.5% CFR-2 -4% GEL -	
L	ADDITIONAL C	EMENTING/SQUEEZE REC	nph .		· .			
Dunnagas	Depth	ENCHT HOY SHOLLEE REC	I I I I I I I I I I I I I I I I I I I	Τ		-		
Purpose:	Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives				
Perforate Protect Casing Plug Back TD	6010 - 6090	LWL/COMMON	25/25		,			
_X Plug Off Zone					<u> </u>			
Shots Per Foot		N RECORD - Bridge Plu ge of Each Interval N			Fracture, Shot, d Kind of Materi		eeze Record Depth	
CMT. RTNR. SET @ 6030'			50 SXS U	SED TO PLUG OFF	(SEE ABOVE) 60%01-60901		
2	2863 - 29	175						
	-					_	<u> </u>	
TUBING RECORD	Size 2-1/16"	Set At 3013*	Packer At	Liner Run	☐ Yes [X]	No		
Date of First, Resu SI FROM 6/85 -9/85		SWD or Inj. Produ 10/85	ucing Method	lowing □ _{Pur}	mping 🗆 Gas Li	ft Ooth	er (Explain)	
Estimated Production Per 24 Hours	n Oil	Bbls. Gas	Mcf Wate		Gas-Oil		Gravity	
Disposition of Gas:	METHOD OF	COMPLETION		Pro	oduction Interva	ıt		
Vented X Sold (If vented, su			Hole X Perf.		<u>-</u>	_	2863'-2975' OA	
,,		U Other	r (Specify)		19 (C. 3011 17 300 19 (dillo - Slatu el III	Ashed Fraish	•	
				E and an	اراتي) در در در منطقه و المراطة الهراوي معود دود	iged Peck vi.	.)	