

1100372

TO: STATE CORPORATION COMMISSION

API NUMBER 15-119-20,820 - 0000  
SW NE NE SEC. 22, T 33 S, R 29 W

CONSERVATION DIVISION - PLUGGING SECTION 4280 FEET FROM NORTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 1000 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202 LEASE NAME CALHOON WELL # 1-22

TECHNICIAN'S PLUGGING REPORT COUNTY MEADE 191.75

OPERATOR LICENSE # 4951 7/5 WELL TOTAL DEPTH 5900 FEET

OPERATOR: CLAASSEN OIL & GAS PRODUCTION CSG: SIZE 4 1/2" @ 5900' WITH 425 SX

NAME AND PO BOX 417 SURFACE CASING: SIZE 8 5/8" @ 1610' WITH 600 SX

ADDRESS ESTES PARK, CO 80517

ABANDONED OIL WELL  GAS WELL  X INPUT WELL  SWD WELL  D/A

OTHER WELL AS HEREINAFTER INDICATED \_\_\_\_\_

PLUGGING CONTRACTOR SARGENT & HORTON PLUGGING, INC LICENSE NUMBER 31151

ADDRESS RT. 1, BOX 49BA, TYRONE, OK 73951-9731

COMPANY TO PLUG AT: HOUR: 10:00 AM DAY: 05 MONTH: 07 YEAR: 2000

STATE CORPORATION COMMISSION

PLUGGING PROPOSAL RECEIVED FROM DON HORTON

(COMPANY NAME) SARGENT & HORTON PLUGGING, INC (PHONE) 580-854-6515

JUN 14 2000

7-14-00

CONSERVATION DIVISION  
Wichita, Kansas

WERE: PERFS AT 4814-4820

1ST PLUG SPOT 100# HULLS & 20 SX CEMENT AT 4814-4614 AT 800 PSI. CIRCULATE HOLE. 2ND

PLUG SPOT 50 SX CEMENT AT 1640' TO 1340'. 3RD PLUG AT 550' WITH 40 SX CEMENT.

4TH PLUG AT 40-0' WITH 10 SX CEMENT. GOOD CIRCULATION OF ALL PLUGS.

PLUGGING PROPOSAL RECEIVED BY GARY WITNERS

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL  PART  NONE

OPERATIONS COMPLETED: HOUR: 3:00 PM DAY: 05 MONTH: 07 YEAR: 2000

ACTUAL PLUGGING REPORT \_\_\_\_\_

1ST PLUG SPOT 100# HULLS AND 20 SX CEMENT AT 4814 TO 4614' AT 800 PSI. CIRCULATE HOLE.

2ND PLUG AT 1640-1340' WITH 50 SX CEMENT. 3RD PLUG AT 550' WITH 40 SX CEMENT.

4TH PLUG AT 40-0' WITH 10 SX CEMENT. GOOD CIRCULATION OF ALL PLUGS.

REMARKS: USED COMMON CEMENT BY SARGENTS. RECOVERED 2620' OF 4 1/2" CASING.  
(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I (DID) OBSERVE THIS PLUGGING

**INVOICED**

SIGNED

Gary Winters  
(TECHNICIAN)

FORM CP-2/3

DATE

7/18/00

INSTR. NO.

1060084