| (v   |   |                               |                          |
|--|---|-------------------------------|--------------------------|
| To:<br>STATE CORPO                         | ORATION COMMISSION                      | API NUMBER 15- 119-20,739     | -8000                    |
| CONSERVATION DIVISION - PLUGGING SECTION S |   | SE NE , SEC. 9 , T            | 33 s, R 29 W             |
|  | DO DERBY BUILDING<br>ANSAS 67202        | feet from                     | S section line           |
| TECHNICIAN                                 | 'S PLUGGING REPORT                      | 890 feet from                 | E section line           |
| Operator L                                 | lcense <b>Ø</b> 47 <u>55</u>            | Lease Name Cottrell We        | 9-1                      |
| Operator: _                                | Toklan Oil Corporation                  | County Meade                  | 190.13                   |
| Name&<br>Address _                         | 15 W. 6th Street, Suite 1510            | Well Total Depth 5850         | feet                     |
| _  | Tulsa, OK 74119                         | Conductor Pipe: Size          | •                        |
| _  |   | Surface Casing: \$1ze 8 5/8   | _feet1600                |
| Abandoned (                                | Oll Well X Gas Well !                   |                               | -                        |
| Other well                                 | as hereinafter indicated                |                               |                          |
|  | ontractor Sargent's Casing Pulling      |                               |                          |
| Address                                    | P. O. Box 506, Liberal, KS 6790         | 1                             |                          |
| Comp <b>any</b> to                         | plug at: Hour: 8:00 am Day: 1           | Month: May                    | Year:19 86               |
|  | roposal received from Bob               |                               |                          |
| (company ne                                | ame) Sargent's                          | (phon                         | e) 316-624-7455          |
| wara: 4 1/                                 | /2" at 3880 PBTD 3842 Perfs at 37       | 71-75; Pump through 4 1/2"    | casing with              |
| 1st plug p                                 | oump 1 sack hulls and 20 sx cement t    | to bottom                     | <del></del> -            |
| 2nd plug a                                 | at 1630' with 50 sx cement              |                               |                          |
| 3rd plug a                                 | at 700° with 40 sx cement               |                               | -                        |
| 4th plug f                                 | from 40 to surface with 10 sx cemer     | nt                            |                          |
|  | Plugging Proposa                        | I Received by Richard W. Lace | ey                       |
| <u> </u>                                   |   |                               | INICIAN)<br>X            |
|  | perations attended by Agent?: All_      |                               | one                      |
| Operations                                 | Completed: Hour: 5:00 pm Day:           | L Month: May                  | Year:1986                |
| ACTUAL PLU                                 | GGING REPORT 1st plug pumped 1 sack     | k hulls and 20 sx cement to 1 | botťom, 2nd plug         |
| at 1630' w                                 | with 50 sx cement, 3rd plug at 700'     | with 40 sx cement, 4th plug   | from 40° to              |
| surface wi                                 | ith 10 sx cement.                       |                               |                          |
|  |   |                               | MAY OF 100               |
|  |   |                               | MAN COMMING              |
|  |   | <del></del>                   | - 1906 1906              |
| Danaska. Re                                | ecovered 3200 4 1/2 casing. Used of     | common cement by Sargent's    | CONSERVATION DIVISION    |
|  | (If additional description is ne        | cessary, use BACK of this fo  | rm.)                     |
|  | ld (not) observe this plugging.         | Signed Richard W. Luc         | ly                       |
| ave  | mananananananananananananananananananan | (TECHNICIAN)                  | <del>-</del> y .         |
| Valla                                      |   |                               | FORM CP-2/3<br>Rev.01-84 |
|  |   |                               |                          |