

7-16

To: STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, KS 67202

API NUMBER 15-119-20,430-0000

W/2 W/2 SE, SEC. 30, T 33 S, R 28 ~~W/2~~

1320 feet from S section line

2420 feet from E section line

Lease Name Mohler Well # 13

County Meade 186.94

TECHNICIAN'S PLUGGING REPORT  
Operator License # 4570

Operator: Samedan Oil Corporation  
Name:  
Address 9400 N. Broadway, Ste. 700  
Oklahoma City, OK 73114

Well Total Depth 5752 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 1709

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sargent's Casing Pullers License Number 6547

Address P.O. Box 506, Liberal, KS 67905-0506

Company to plug at: Hour: 9:30 a.m. Day: 16 Month: 7 Year: 19 97

Plugging proposal received from Kirby Lillard

(company name) Sargent's Casing Pullers (phone) 316-624-7455

logs: 5 1/2" at 5752' w/136 sx cement, PBTD 5697', Perfs at 5640-54'

1st plug set CIBP at 5590' with 2 sx cement on top,

2nd plug at 1800' with 80 sx cement,

3rd plug at 650' with 40 sx cement,

4th plug at 40' with 10 sx cement.

Plugging Proposal Received by Steve Middleton  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 3:30 p.m. Day: 16 Month: 7 Year: 1997

ACTUAL PLUGGING REPORT 1st plug set CIBP at 5590' with 2 sx cement on top,

2nd plug spotted 80 sx cement at 1812', displaced with gel,

3rd plug spotted 40 sx cement at 660'; displaced with gel,

4th plug spotted 10 sx cement at 40-0'.

Remarks: Used common cement by Sargent's. Recovered 2625' of 5 1/2" casing.  
(If additional description is necessary, use BACK of this form.)

I (did / ~~XXXXXX~~) observe this plugging.

48649

Signed Gary Winter  
(TECHNICIAN)