| SIDE ONE | AFFIDAVIT OF COMP | LETION FORM | (KEA) VCO-I |
|--|--|--------------------------------|-------------------------|
| rado Derby Building the well, regardles | filed in duplicate with the land with the land with the land with the land was completed the land was completed the land was a supplementation of request if the land was completed with the land was completed with the land was a supplementation of request if the land was a supplementation with the land was a supplemen | thin <u>ten</u> days a ted. | fter the completion of |
| confidential, only side two will then | file one copy. Information of be held confidential. | on <u>side one</u> will | be of public record and |
| Applications must b | as, Dry SWD, OWWO, Injection e filed for dual completion, | commingling, SW | D and injection, T.A. |
| | logs (i.e. electrical log, so 82-2-105 & 82-2-1 | | ray neutron log, etc.). |
| OPERATOR Anadarko | Production Company | API NO | 15-129-20,594 -00 -00 |
| - | | | |

| OTERATOR TO THE PROPERTY OF TH | ATT NO: 13-129-20,394 00 00 |
|--|---|
| ADDRESS P. O. Box 351 | COUNTYMorton |
| Liberal, Kansas 67901 | FIELD Wildcat |
| **CONTACT PERSON Mr. Paul Gatlin | PROD. FORMATION DRY HOLE |
| PHONE 316-624-6253 | |
| PURCHASER . | LEASE HAYWARD "I" |
| ADDRESS | WELL NO. 2 |
| | WELL LOCATION C SW NE |
| DRILLING Gabbert-Jones, Inc. | 1980 Ft. from North Line and |
| CONTRACTOR , . | 1980 Ft. from East Line of |
| ADDRESS 830 Sutton Place | |
| Wichita, Kansas 67202 | the NE/4 SEC. 10 TWP. 33S RGE.40W WELL PLAT |
| PLUGGING Midwest Casing Pulling Service | |
| CONTRACTOR | KCC |
| ADDRESS P.O. Box F | KGS (Office |
| Sublette, Kansas 67877 | Use) |
| TOTAL DEPTH 6000 PBTD 5450 | 10 |
| SPUD DATE 1/9/82 DATE COMPLETED 4/9/82 | |
| ELEV: GR 3296' DF 3297' KB 3299' | |
| DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS | |
| Amount of surface pipe set and cemented 1464' | . DV Tool Used?No |
| Amount of Surface pipe set and cemented 1404 | 27 1001 05cd |
| AFFIDAVI | <u>T</u> |
| STATE OF KANSAS , COUNTY OF S | SEWARD SS, I, Paul |
| Campbell OF LAWFUL AGE, BE | ING FIRST DULY SWORN UPON HIS OATH, |
| DEPOSES THAT HE ISDivision Operations Manager (FOR) | (OF) Anadarko Production Company |
| OPERATOR OF THE HAYWARD "I" LEASE | , AND IS DULY AUTHORIZED TO MAKE |
| AFFICALLY FOR AND ON THE BEHALF OF SAID OPERATO | or, THAT WELL NO. 2 ON |
| SAID LEASE THAS SEEN COMPLETED AS OF THE 9th DAY ALL INFORMST ON ENTERED HEREIN WITH RESPECT TO SAID FUNDING THE SENT SAITH NOT. | OF April , 19 82 , AND THAT |
| ALL INFORMATION ENTERED HEREIN WITH RESPECT TO SAID | WELL IS TRUE AND CORRECT. |
| FUNDAGE PRESENT SAITH NOT | |
| FUNDAMENTAL ENTERED HEREIN WITH RESPECT TO SAID | |
| ald | (5) HILL Gently !! |
| SUBSCRIBED AND SWORN BEFORE ME THIS 3 Ld DAY OF | May 19 82. |
| HOUSENT BEVERLY J. WILLIAMS | Durelly Helliand |
| MY COMMISS CHARLES Seward County, Kansas MY COMMISS CHARLES IN SEWARD | NOTAPY PUBLIC |
| • • • | • |

**The person who can be reached by phone regarding any questions concerning this information. Within 45 days of completion, a witnessed initial test by the Commission is required if the well produces more than 25 BOPD or is located in a Basic Order Pool.

RATE OF PRODUCTION PER 24 HOURS

Disposition of gas (vented, used on lease or sold)

الرازانين فيواد ويتواهمه فعفر المتراها المعراها الم

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION

CFPB

IDE TWO WELL LOG

Show all Important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, in-

| cluding depth interval tested, cushion used, time tool open, flowing FORMATION DESCRIPTION, CONTENTS, ETC. | ТОР | BOTTOM | NAME DEPTH | | |
|--|----------|----------|-------------------|--|--|
| PORTALION DESCRIPTION, CONTENTS, 270 | | 20110M | NAME SEFIN | | |
| | | <u> </u> | 1 | | |
| Sand | 0' | 646' | i i | | |
| Sand, Redbed | 646' | 1259' | 1 1 | | |
| Sand, Redbed, Anhydrite | 1259' | 1470' | 1 | | |
| Shale, Lime | 1470' | 1510' | | | |
| Lime, Shale | 1510' | 2348' | | | |
| Shale, Lime | 2348' | 2631 ' | | | |
| Lime, Shale | 2631' | 2833' | | | |
| Shale, Lime | 2833 | 3041 | } | | |
| Lime, Shale | 3041' | 6000' | | | |
| מי | 30.72 | 6000' | | | |
| | |] | ! | | |
| • | | 1 | 1 | | |
| | } | 1 | } | | |
| | i | 1 | i | | |
| | | Ì | | | |
| ı | | ļ | i i | | |
| | 1 | J | } | | |
| | | | i i | | |
| | İ | | | | |
| | i | | | | |
| | . | ! | | | |
| | | 1 | 1 | | |
| • | | ì | 1 | | |
| | | l | 1 1 | | |
| | | | 1 | | |
| | j | 1 | i l | | |
| | | | 1 | | |
| | | · | ł . I | | |
| • | | 1 | | | |
| | | | ļ . | | |
| • | | | RELEASED | | |
| | | | | | |
| | | | 1 444 0 0 45 | | |
| | | | MAY 2 0 1984 | | |
| | 1 | ł | 1 | | |
| | | | FROM CONFIDENTIAL | | |
| | | ì | I | | |
| • | 1 | . | Į į | | |
| | ł | 1 | Ŧ | | |

| Purpose of string | Size hole drilled | Size casing set | Weight lbs/ft. | Setting depth | Type cen | nent . | Sacks | Type and parcent additives |
|----------------------------------|-------------------|-----------------|----------------|------------------|------------------------|-----------|-----------------|----------------------------|
| | | | | | Pozmix | | 500 | 4% Gel, 2% Ca(|
| Surface | 12-1/4" | 8-5/8" | 5/8" 24# | | 1464' Common | | 200 | 2% CaCl |
| | | i | | | Litewat | - | 50 | .5% CFR-2 |
| Production | 7-7/8"_ | 4-1/2" | 10.5#_ | 5984' | SS Pozi | nix | 275 | .5% CFR-2 |
| | | | | | | | | <u> </u> |
| | | | | · . | | ł | | |
| | LINER RECOF | | | | | PERFORA. | TION RECO | RD |
| Top, ft. Bottem, ft. | | Sacks co | Sacks coment | | per ft. | Sixe | G type | Depth interval |
| | | | | 2 | 2 | | L | 5919-24' |
| TUBING RECORD | | | 2 | ! | .41 | | 5885-91 | |
| | | | | | ? | .41 | <u>.</u> | _5632-27' |
| ise | Setting depth | | Pocker set at | | 2 .4 | | | 5524-36 |
| None | | l | | | | | | 5362-66 |
| | _ | CID, FRACT | URE, SHOT, | CEMENT SQ | UEEZE RECO | RD | | |
| Amount and kind of material used | | | | | Depth interval treated | | | |
| A/500 gal 15 | % DS-30. | | | | • | | 5919-2 | 4' |
| | 7-1/2% MCA, | 30 BS. | A/1200 g | ral 7-1/2 | % MCA, 3 | 30 BS. | 5524-3 | 6' |
| A/1000 gal 7 | | | | | | | l l | |
| A/1000 gal 7 A/500 gal 7- | | ead. | | | | | 5362-6 | 6 ' |
| | -1/2% Spearh | ead. | g method (flow | ring, pumping, ç | jos lift; etc.) | 2 Mayarin | 5362-6 Gravi | |

Perforations