STATE OF KANSAS STATE CORPORATION COMMISSION

Form CP-4

Notary Public.

Give All Information Completely Make Required Affidavit

WELL PLUGGING RECORD

or Deliver Report to: Conservation Division		• •							
State Corporation Commission 212 No. Market		Pratt	<u></u>	c 23	m 285 n−	10 /85	W7 / 4873		
Wichita, Kansas 67202	Tankin as "NIE	CANTAIN CARTUM			Twp. 28S r ge. NE NE NW				
NORTH	Location as "NE Lease Owner	Raymond	Oil Co	Tno	IN P. IN P. IN W				
	Y >7	Chitwoo	<u> </u>	aş. Illia		Wall No. 1	JS_3		
	Lease Name	Wichita	Kang		Oil	. WEIL NO	<u> </u>		
i	Character of W	ell (completed a	o Oil Con on	Der Volo	Oil				
				•			_19		
							_19		
							_19		
	Plugging comple	Plugging commenced 19 Plugging completed April 16							
	Beason for aban	Plugging completed <u>April 16</u> Depletion 1970 Reason for abandonment of well or producing formation Depletion							
		Treason for abandonment of wen of bronteing formation							
	If a producing	If a producing well is abandoned, date of last production							
					or its agents befo		was com		
Locate well correctly on above Section Flat	manaad2								
Section Plat ne of Conservation Agent who sup	pervised plugging of this	s well	<u>G. Russ</u>	<u>sell Bib</u>	<u>erstein</u>				
ucing formation	D	epth to top	Bottom		. Total Depth of	Well	Fec		
w depth and thickness of all water	er, oil and gas formation	ıs.							
OIL, GAS OR WATER RECOR	RDS				(CASING RE	CORD		
TE, GAS OR WATER IEEOS			 1	 					
FORMATION	CONTENT	FROM	OT .	SIZE	PUT IN	PULLED	DUT		
<u> </u>	 	<u> </u>							
		ļ. ——	}	 		<u> </u>			
									
		<u> </u>							
		 			 				
	- -	 	<u> </u>	 -	 				
					1		_		
Describe in detail the manner introducing it into the hole. If confect for each plug	ement or other plugs we		e character of						
Sanded back to 3	set. 3370° and dum	ped 8 sac	e character of	same and dep	Shot pip	e off rock			
sanded back to 3 at 1578.99. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of	same and dependent.	Shot pip Set 10'	e off rock			
sanded back to 3 at 1578.99. Pu	set. 3370° and dum	ped 8 sacd mudded	e character of	same and dependent.	Shot pip Set 10'	e off rock			
Sanded back to 3 at 1578.99. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of	same and dependent.	Shot pip Set 10'	e off rock			
Sanded back to 3 at 1578.99*. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of	cement. 220°. Shed mud	Shot pip Set 10'	e off rock			
Sanded back to 3 at 1578.99*. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of	same and dependent.	Shot pip Set 10'	e off rock			
Sanded back to 3 at 1578.99*. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of cks of c hole to Finis sacks of	same and der	Shot pip Set 10' ding hole	e off rock			
Sanded back to 3 at 1578.99*. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of cks of c hole to Finis sacks of	same and der	Shot pip Set 10' ding hole	e off rock to			
Sanded back to 3 at 1578.99. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of cks of c hole to Finis sacks of	same and der	Shot pip Set 10' ding hole	e off rock to			
Sanded back to 3 at 1578.99*. Pu	3370° and dumulled pipe and du	ped 8 sacd mudded	e character of cks of c hole to Finis sacks of	same and der	Shot pip Set 10' ding hole	e off rock to			
stroducing it into the hole. If confect for each plug Sanded back to 3 at 1578.99. Pu bridge and dumpe 40. Set rock b	3370° and dum ulled pipe and ed 40 sacks o	ped 8 sacd mudded	e character of cks of c hole to Finis sacks of	same and der	Shot pip Set 10' ding hole	e off rock to			
Sanded back to 3 at 1578.99*. Pu	3370° and dum ulled pipe and ed 40 sacks o	ped 8 sacd mudded	e character of cks of c hole to Finis sacks of	same and der	Shot pip Set 10' ding hole	e off rock to			
stroducing it into the hole. If confect for each plug Sanded back to 3 at 1578.99*. Pu bridge and dumpe 40*. Set rock be	and dumulled pipe and dumulled	ped 8 sacd mudded f cement.	cks of character of the	cement. 220°. Shed mud cement	Shot pip Set 10' ding hole	e off rock to			
Sanded back to 3 at 1578.99 . Pu bridge and dumpe	and dumulled pipe and dumulled	ped 8 sacd mudded f cement.	cks of character of the	cement. 220°. Shed mud cement	Shot pip Set 10' ding hole	e off rock to			
sanded back to 3 at 1578.99*. Pu bridge and dumpe 40*. Set rock E	ement or other plugs we set. 3370° and dum ulled pipe and ed 40 sacks of bridge and dum ert Self	ped 8 sac d mudded f cement. mped 15 s	cks of character of the	cement. 220°. Shed mud cement	Shot pip Set 10' ding hole	e off rock to			
Sanded back to 3 at 1578.99. Pu bridge and dumpe 40. Set rock E	and dumulled pipe and dumulled	ped 8 sac d mudded f cement. mped 15 s	cks of character of the	cement. 220°. Shed mud cement	Shot pip Set 10' ding hole	e off rock to			
sanded back to 3 at 1578.99*. Pu bridge and dumpe 40*. Set rock E	ement or other plugs we set. 3370° and dum ulled pipe and ed 40 sacks of bridge and dum ert Self	ped 8 sac d mudded f cement. mped 15 s	cks of character of the	cement. 220°. Shed mud cement	Shot pip Set 10' ding hole	e off rock to			
sanded back to 3 at 1578.99*. Pu bridge and dumpe 40*. Set rock be ne of Plugging Contractor Hu	and dumulled pipe and dumulled pipe and dumulled pipe and dumulled sacks of bridge sacks o	ped 8 sac d mudded f cement. mped 15 s	e character of cks of c hole to Finis acks of	cement. 220°. Shed mid cement Convert	Shot pip Set 10' ding hole Original Community of the control o	e off rock to			
Sanded back to 3 at 1578.99*. Pu bridge and dumpe 40*. Set rock be ne of Plugging Contractor Hu	and dumulled pipe and dumulled pipe and dumulled pipe and dumulled sacks of the bridge and dumulated sacks of the bridge and dumulated pipe and dumulated sacks of the bridge sack	ped 8 sacd mudded f cement. Imped 15 seription is necessary.	e character of cks of c hole to Finis sacks of	same and depotent. 220°. shed mud cement cement ying from ying from of this sheet)	Shot pip Set 10* ding hole Contact to the contac	e off rock to	feet		
Sanded back to 3 at 1578.99°. Pu bridge and dumpe 40°. Set rock be me of Plugging Contractor Hu ATE OF Kans. Employee	and dum alled pipe and alled pipe and art Self atchinson, Kar	ped 8 sacd mudded freement. Imped 15 section is necessary. Interval of the control of the cont	e character of cks of c hole to Finis acks of	same and der cement. 220°. shed mud cement Coment Villagia of this sheet)	Shot pip Set 10* ding hole Johnson	e off rock to	-describe		
Sanded back to 3 at 1578.99°. Pu bridge and dumpe 40°. Set rock be ne of Plugging Contractor Hu ATE OF Kans. Employee	and dum alled pipe and ad 40 sacks of bridge and dum crt Self atchinson, Kar , cou	ped 8 sacd mudded from the model 15 section is necessarily to the content of the	e character of cks of c hole to Finis sacks of wary, use BACK Reno employee of offacts, statement	same and der cement. 220°. shed mud cement Coment Villagia of this sheet)	Shot pip Set 10* ding hole Johnson	e off rock to	-describe		
sanded back to 3 at 1578.99°. Pu bridge and dumpe 40°. Set rock be me of Plugging Contractor Hu ATE OF Kans. Employee	and dum alled pipe and ad 40 sacks of bridge and dum crt Self atchinson, Kar , cou	ped 8 sacd mudded from the model 15 section is necessarily to the content of the	e character of cks of c hole to Finis sacks of wary, use BACK Reno employee of of facts, statement	same and der cement. 220°. shed mud cement Coment Villagia of this sheet)	Shot pip Set 10* ding hole Johnson	e off rock to	-describe		
Sanded back to 3 at 1578.99°. Pu bridge and dumpe 40°. Set rock be me of Plugging Contractor Hu ATE OF Kans.	and dumulled pipe and dumulled pipe and dumulled pipe and dumulated sacks of the same are true and the same ar	ped 8 sacd mudded from the model 15 section is necessarily to the content of the	e character of cks of c hole to Finis sacks of wary, use BACK Reno employee of of facts, statement	same and der cement. 220°. shed mud cement Coment Villagia of this sheet)	Shot pip Set 10* ding hole Johnson	e off rock to	-describe		
Sanded back to 3 at 1578.99°. Pu bridge and dumpe 40°. Set rock be me of Plugging Contractor Hu ATE OF Kans. Employee	and dumulled pipe and dumulled pipe and dumulled pipe and dumulated sacks of the same are true and the same ar	ped 8 sac d mudded f cement. mped 15 s description is neces ns.	e character of cks of c hole to Finis sacks of wary, use BACK Reno employee of of facts, statement	same and der cement. 220°. shed mid cement Constant (or this sheet) where or (ownts, and matter)	Shot pip Set 10* ding hole Congression Janes Service Tans Service The pip Set 10* Set	e off rock to	-describe		
sanded back to 3 at 1578.99°. Pu bridge and dumpe 40°. Set rock be me of Plugging Contractor Hu ATE OF Kans. Employee	and dumulled pipe and dumulled pipe and dumulled pipe and dumulated sacks of the same are true and the same ar	ped 8 sac d mudded f cement. mped 15 s description is neces ns.	e character of cks of c hole to Finis sacks of wary, use BACK Reno employee of of facts, statement	same and der cement. 220°. shed mud cement cement when the sheet are	Shot pip Set 10* ding hole Johnson	e off rock to	-describe		

INDIAII	DUAL W	ELL RE	CORD	and the second of the second o	TO EST. Se			anamanan yan santa F Salah	AGE NO	D
GENERAL	INFORMA	TION		Assistant American	estru Al	uth: 1-10	90			ر الاستان المستوادة المادي المادي المادي المادي الماد
,		- 500 7-44 TO			٠		•	, ; ;	13. met.	1
		1 Reg. Co			casc	Chitwood		Wel	1 .	,
Lease No.	5648	Sec	23 Tw	vp. 28 I	Rgc. 12	County_	Pratt	State	Kans	88.5
	NE N		• •• • • • • • • • • • • • • • • • • • •	ب <u>ھی</u> مادر ہو۔ مادر ہو	· · · ·					
Location—	4744 444	E3 1748 :			<u> </u>		·		\$ ~ K	
		<u> </u>			·	- ·		x x		· · · ·
Elevation	D. F. 18	76 Flet	vation Ro	t. Table	1878	بينجو وويت باو ميټور يا و و و وه. ده			· · · · · · · · · · · · · · · · · · ·	10 July 10 Jul
Contractor	R.	W. Rine			onax.	- 100 ·	- ,,			
Drilling B	egan	10/4/43	Drilli	ng Ended_	11,		1 25/3	-	, ,	
Maximum	Deviation	of Hole	none	<u> </u>			STATE CORP	CEIVE	<u> </u>	. ,
`T` T'o	1 Factors	4498	Cable	Tool Foo		<u>, ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;</u>	F.E	OKALION CON	MISSIDN	
Drillers T	. D	4498 _	_Schlumb	erger T. D). <u> </u>	463	Wic	nita, Kansas	ISION	
3		tions								
Float Coll	or Size 7th	on le	44	155			*40E		,	; ; ;
I Wat ware		<u> </u>	ਾ ਸਾ <u> = -</u>	±00	Guide S	Shoe Set at _	4480	(Fro	ım Rota:	rv Table)
*	-	<u></u>			-	hoe Set at _				
*	-	<u></u>			-	Shoe Set at _				
ť	oth Drilled	<u></u>			-					
Total Dep	oth Drilled	<u></u>			-					
Total Dep	oth Drilled	<u></u>	44	498	A,					
Total Dep	oth Drilled	<u></u>	44 C	498	ND LIN			(Fron	n Rotar	y Table)
Total Dep	oth Drilled	Out to	C NO. JOINTS	ASING A	ND LIN	VER RECO	DRD	(Fron	CEME WT.	y Table) NT KIND Ideal
Total Dep	oth Drilled	Out to	44 C	ASING A	ND LIN	VER RECO	DRD	(Fron	n Rotar	y Table)
Total Dep	oth Drilled	оцt to	C NO. JOINTS	ASING A	MANI SOC.	VER RECO	DRD	SACKS	CEME WT.	y Table) NT KIND Ideal
Remarks	GRADE H. 40	оцt to	C NO JOINTS	ASING A	MAN SOC.	VER RECO	ORD THREAD	SACKS	CEME WT.	y Table) NT KIND Ideal Postland
Remarks	GRADE H 40	оцt to	C NO JOINTS	ASING A	MANI SOC.	VER RECO	ORD THREAD	SACKS	CEME WT.	y Table) NT KIND Ideal Postland
Remarks	GRADE H 40	оцt to	C NO JOINTS	ASING A	MAN SOC.	VER RECO	ORD THREAD	SACKS	CEME WT.	y Table) NT KIND Ideal Postland
Remarks	GRADE H 40	оцt to	C NO JOINTS	ASING A	MAN SOC.	VER RECOUFACTURER hand hand	ORD THREAD 8 v	SACKS	CEME WT. 100#	y Table) NT KIND Ideal Postland
Remarks	GRADE H 40	оцt to	C NO JOINTS	ASING A AMOUNT 303 4485	MAN SOC.	VER RECOUFACTURER hand hand	ORD THREAD 8 v	(From	CEME WT. 100#	y Table) NT KIND Ideal Postland
Total Dep Remarks SIZE O. D. 10" 7"	GRADE H 40	оцt to	C NO JOINTS	ASING A AMOUNT 303 4485	MAN SOC.	VER RECOUFACTURER hand hand	ORD THREAD 8 v	(From	CEME WT. 100#	y Table) NT KIND Ideal Postland