

STATE OF KANSAS  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION  
200 Colorado Derby Building  
Wichita, Kansas 67202

WELL PLUGGING APPLICATION FORM  
(File One Copy)

API NUMBER \_\_\_\_\_ of this well)  
(This must be listed; if no API# was issued, please note drilling completion date.)

6/90

LEASE OPERATOR Amoco Production Company OPERATORS LICENSE NO. 5952

ADDRESS P.O. Box 800, Rm. 1833, Denver, CO 80201 PHONE # (303) 830-4009

LEASE (FARM) Printz G.U. "B" WELL NO. 2 WELL LOCATION NW/4 NW/4 COUNTY Seward

SEC. 11 TWP. 32S RGE. 33W (E) or (W) TOTAL DEPTH 6013' PLUG BACK TO 2730'

Check One:

ALL WELL  GAS WELL \_\_\_\_\_ D & A \_\_\_\_\_ SWD or INJ WELL \_\_\_\_\_ DOCKET NO. \_\_\_\_\_

SURFACE CASING SIZE 8-5/8" SET AT 1527' CEMENTED WITH 750 SACKS

CASING SIZE 5-1/2" SET AT 2800' CEMENTED WITH 440 SACKS

PERFORMED AT 2665-2675', 2695-2701'

CONDITION OF WELL: GOOD  POOR \_\_\_\_\_ CASING LEAK \_\_\_\_\_ JUNK IN HOLE \_\_\_\_\_

OPERATOR'S SUGGESTED METHOD OF PLUGGING THIS WELL See attached procedures and wellbore sketch.

(If additional space is needed use back of form)

IS WELL LOG ATTACHED TO THIS APPLICATION AS REQUIRED? No (already IS ACC-1 FILED? Yes  
(if not, explain) on file)

DATE AND HOUR PLUGGING IS DESIRED TO BEGIN Upon approval by KCC

PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K.S.A. 55-101 et seq AND THE RULES AND REGULATIONS OF THE STATE CORPORATION COMMISSION.

NAME OF COMPANY REPRESENTATIVE AUTHORIZED TO BE IN CHARGE OF PLUGGING OPERATIONS:

L.D. Bell or C.P. Kennedy PHONE # (316) 856-1237 or 4317

ADDRESS P.O. Box 507, Ulysses, KS 67880

PLUGGING CONTRACTOR Midwest Casing Pulling Service LICENSE NO. 6497

6/90

ADDRESS Box F, Sublette, KS 67877 PHONE # ( ) \_\_\_\_\_

AGREEMENT WILL BE GUARANTEED BY OPERATOR OR AGENT SIGNED: J.L. Hampton jaw  
STATE CORPORATION COMMISSION (Operator or Agent)

FEB 21 1990

DATE: 2/16/90.

CONSERVATION DIVISION  
Wichita, Kansas

①



Amoco Production Company

January 10, 1989

J. L. Hampton  
AB - 1846

File: JWH-102-400.1

Proposed Plugging and Abandonment Procedure  
Printz G.U. "B" No. 2  
Section 11-32S-33W (4620' FSL x 4620' FEL)  
Seward County, Kansas

Detailed below is the proposed plugging and abandonment procedure for the subject well. Depths are relative to the GL elevation of 2880 feet. Please note that this procedure is for KCC permitting purposes only.

1. MIRUSU.
2. Pull pump, rods, and tubing.
3. Set a CIBP at 2500', cap with 2 sacks cement.
4. Pump a 25 sack 35/60 POZ mix plug from 550' to 400' (fresh water plug).
5. Pump a 5 sack cement plug from 40' to 5' (surface plug).
6. Cut off surface and production casing 5' below ground level. Weld on steel cap with lease identification.
7. Restore location.

Place drilling mud with a weight of 9.0 ppg and a viscosity of 36 qt. sec. between all cement plugs. Note that no salvageable casing exists in the wellbore. A wellbore sketch is attached for your reference. Please contact Henry Welch at (303) 830-4145 with questions.

  
Jim R. Dolph

HRW/cp

Attachments

HRW01CP.LTR

RECEIVED  
STATE OF KANSAS  
COMMISSION

FEB 21 1990

CONSERVATION DIVISION  
Wichita, Kansas