

1 050828

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION 100'E C SE SW, SEC. 22, T 29 S, R 18 W
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 097-21,216-0000

TECHNICIAN'S PLUGGING REPORT

Operator License # 5004

Operator: Vincént Oil Corporation
Name & Address 125 N. Market, Suite 1110
Wichita, KS 67202

660 feet from S section line

3200 feet from E section line

Lease Name Schmidt "1" Well # 1

County Kiowa 157.63

Well Total Depth 4850 Marmaton feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 262

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Murfin Drilling Co. License Number 6033

Address 250 North Water, Suite 300, Wichita, KS 67202

Company to plug at: Hour: 7:00 pm Day: 6 Month: July Year: 19 86

Plugging proposal received from Terry McRae

(company name) Murfin (phone) 316-267-3241

were: to fill hole with heavy mud and spot cement through drill pipe Elevation N/A
Anhydrite 1150'

1st plug at the base of the Anhydrite with 50 sx cement

2nd plug 30' below the base of the surface pipe with 50 sx cement

3rd plug from 40' to surface with 10 sx cement

4th plug to circulate rat hole with 15 sx cement

5th plug to circulate mouse hole with 10 sx cement

Plugging Proposal Received by Richard W. Lacey
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 9:00 pm Day: 6 Month: July Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 1150' with 50 sx cement, 2nd plug at 300' with 50 sx
cement, 3rd plug from 40' to surface with 10 sx cement, 4th plug to circulate rat hole
with 10 sx cement, 5th plug to circulate mouse hole with 10 sx cement.

Remarks: Used 60/40 Pozmix 2% gel 3% cc by BJ-Titan
(If additional description is necessary, use BACK of this form.)

INVOICED

STATE CORPORATION COMMISSION

Signed Richard W. Lacey
(TECHNICIAN)

DATE JUL 14 1986

JUL 11 1986

INV. No 14368 7-6

CONSERVATION DIVISION
Wichita, Kansas

FORM CP-2/3
Rev. 01-84

State of Kansas
NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date July 1, 1986
month day year

API Number 15- 097-21,216-0000

OPERATOR: License # 5004
Name Vincent Oil Corporation
Address 125 N. Market, Suite 1110
City/State/Zip Wichita, Kansas 67202
Contact Person Donna Manda
Phone 316/262-3573

100' E of C. SE 1/4 Sec. 22 Twp. 29 S, Rg. 18
660 Ft. from South Line of Section
3200 Ft. from East Line of Section
(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 6033
Name Murfin Drilling
City/State Wichita, Kansas

Nearest lease or unit boundary line 560 feet
County Kiowa
Lease Name Schmidt Well # 1 applied for
Ground surface elevation feet MSL
Domestic well within 330 feet: yes no
Municipal well within one mile: yes no
Surface pipe by Alternate: 1 2
Depth to bottom of fresh water 200 ft.
Depth to bottom of usable water 250 ft. 350
Surface pipe planned to be set 4850 ft.
Projected Total Depth 4850 feet
Formation Marmaton

Well Drilled For: Well Class: Type Equipment:
 Oil SWD Infield Mud Rotary
 Gas Inj Pool Ext. Air Rotary
 OWWO Expl Wildcat Cable

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
cementing will be done immediately upon setting production casing
Date 6-5-86 Signature of Operator or Agent Richard A. Hiebsch Title Vice President

For KCC Use:
Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt.
This Authorization Expires 12-5-86 Approved By 6-5-86

Spud 9/1/86 2185' alt

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 1200 feet depth with 50 sxs of 60/50 pozmix 2% gel, 3% cc
2nd plug @ 600 feet depth with 50 sxs of
3rd plug @ 40 feet depth with 50 sxs of
4th plug @ feet depth with sxs of
5th plug @ 15 feet depth with sxs of
(2) Rathole with sxs (b) Mousehole with 10 sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging.

PUSHER Terry Mcrae
TD 4850 FORMATION Marmaton
SURFACE PIPE 8 5/8 @ 262
HYDRITE 1150 ELEVATION NA
STARTING TIME & DATE 7:00 7/9/84
COMPLETION TIME & DATE 9:00 7/9/84
1st PLUG @ 1150 FT. W/ 50 SX
2nd PLUG @ 700 FT. W/ 50 SX
3rd PLUG @ 40 FT. W/ 10 SX
4th PLUG @ FT. W/ SX
RAT. HOLE CIRCULATED W/ 10 SX
MOUSE HOLE CIRCULATED W/ 10 SX
WATER WELL-PLUGGED W/ SX
CEMENT COMPANY BT Fitts
TECHNICIAN Lacey

RECEIVED
STATE CORPORATION COMMISSION
JUL 11 1986
CONSERVATION DIVISION
Wichita, Kansas