

WELL PLUGGING RECORD

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bittling Building
Wichita, Kansas

Kingman

County, Sec. 16 Twp. 29 Rge. 9 (E) W (W)

Location as "NE/CNW/SW" or footage from lines NE SE SW

Lease Owner Cities Service Oil Company

Lease Name Arensdorf "B" Well No. 1

Office Address Bartlesville, Oklahoma

Character of Well (completed as Oil, Gas or Dry Hole) Dry Hole

Date well completed June 19 19 55

Application for plugging filed June 19 19 55

Application for plugging approved June 19 19 55

Plugging commenced June 19 19 55

Plugging completed June 20 19 55

Reason for abandonment of well or producing formation Dry Hole

If a producing well is abandoned, date of last production _____ 19 _____

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well M. A. Rives

Producing formation Arbuckle Depth to top 4666' Bottom 4694' Total Depth of Well 4694' Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				8 5/8"	340'	NONE

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

4694' to 250' Heavy Mud
250' to 170' Wood plug, rock & hull bridge & 20 sacks cement
170' to 35' Mud & soil
35' to base of cellar - 10 sacks cement

(If additional description is necessary, use BACK of this sheet)
Name of Plugging Contractor Barbour Drilling Company
Address 1612 First National Building, Tulsa, Oklahoma

STATE OF Kansas, COUNTY OF Barton, ss.
V. M. Conover (employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) V. M. Conover
Box 751, Great Bend, Kansas
(Address)

SUBSCRIBED AND SWORN TO before me this 24th day of June, 19 55

My commission expires March 12, 1959
N. J. Smith Notary Public.

JUL 12 1955 7-12-55

CONSERVATION DIVISION
Wichita, Kansas

PLUGGING
FILE SEC 16 T29 R24
BOOK PAGE 128 LINE 23

WELL RECORD

Company Citizen Service Oil Co. Well No. 1 Farm Arensford "B"
 Location 290' North and 330' West of 9/4 Cor. Sec. 16 T. 29 R. 9W
 Elevation 1686 (1681 Cr.) County Kingman State Kansas
 Drlg. Comm. June 3, 1955 Contractor Barbour Drilling Company
 Drlg. Comp. June 20, 1955 Acid None
 T. D. 4694' Initial Prod. Dry Hole - P. & A. 6-20-55

CASING RECORD:

8-5/8" @ 340' con. 250 oz cement

FORMATION RECORD:

clay & sand	0-115
shale & shells	165
sand & clay	250
red bed	465
shale & shells	1365
Anhydrite and shale	1415
shale w/ streaks anhy.	1535
anhydrite	1635
shale, anhydrite & lime	1710
shale & lime	1990
lime & shale	2180
lime	2210
lime & shale	2425
shale	2685
lime & shale	2810
shale & lime	3205
lime	3285
lime & shale	3400
shale & lime	3469
sand	3477
sand & shale	3495
lime	3560
shale & lime	3586
lime	4067
lime & shale	4120
lime	4215
chert	4241
lime	4245
chert & shale	4273
lime	4303
shale & lime	4353
lime & shale	4424
shale	4501
lime	4537
lime & chert	4557
sand	4570

lime	4581
sand	4593
sand & shale	4604
shale	4632
lime	4694 T. D.

Heabner	3372'
Dodge	3388'
Douglas	3402'
Lansing	3575'
Mississippi	4205'
Hinderhook	4302'
Viola	4494'
Simpson Shale	4545'
Simpson Sand	4551'
Arbuckle	4662'
Penetration	32'
Total Depth	4694'

D. S. T. 9932-48, open 1 hr., recovered 40' muddy salt water w/ few spots oil; B. N. P. 12408/30 mins.

D. S. T. 4206-15, open 1 hr., recovered 90' mud and 30' muddy salt water; B. N. P. 9308/30 mins.

D. S. T. 4496-4501, open 1 hr., recovered 60' oily, gassy mud and 870' salt water; B. N. P. 14308/30 mins.

SLOTT TESTS (20700):

370'	3/4"	3000'	3/4"
1000'	1/4"	3500'	1"
1500'	3/4"	2800'	1"
2000'	1/2"	4241'	1-1/2"
2500'	3/4"	4544'	1-1/2"

RECEIVED
 STATE CORPORATION COMMISSION
 JUL 12 1955

PLUGGING
 FILE SEC 16 T 29 R 9W
 BOOK PAGE 28 LINE 38

CONSERVATION DIVISION
 Wichita, Kansas