KANSAS STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

TO:

Jewel M. Ogden, Director 500 Insurance Building

212 North Market

MAR 2 5 1961

CONSERVATION DIVISION
Wichita, Kansas

Wichita 2, Kansas
File No
Location: 1/2 8W. SE. Sec. // Twp. 29 Rge. 9 (E) (W) W
Name of Field: Willodale Total Depth: 4506
I have this date completed supervision of plugging of:
Lease Name: Conrardy Well No. 3
Derator's Full Name: Conrardy Joint Venture 1/0 C.E. Pidley
Complete Address: Bay 484 Great Bend Ransas
Plugging Contractor: Southwest Casing Pulling
Address: Boy 364 Great Bend License No. 399
Oil Well Gas Well Input Well SWD Well D & A
Other well as hereafter indicated:
Was any delay in plugging operations caused by Conservation Division Agent? Yes No
If yes how long? Reason:
Operation Completed: Hour 4:00 Day Month March Year 1961
The above well was plugged as follows:
The above well was plugged as follows:
The above well was plugged as follows: J.D. 4506'-8.P. 856'-145'. C.W.C - 5/2 4500'-100 st. Bottom, sand to 4480'-4 stc
The above well was plugged as follows: J.D. 4506'-8.P. 856'-145'. C.W.C - 5/2 4500'-100 st. Bottom, sand to 4480'-4 stc
The above well was plugged as follows: J.D. 4506'-8.P. 856'-145'. C.W.C - 5/2 4500'-100 SI Bottom, sand to 4480'-49C
The above well was plugged as follows: J. D. 4506'-8.P. 896"-145. C.W.C -5/34500'-100s/ Bottom, sand to 4480'-4 syc Mater Plug at 300', Bailed fluid to 300'. O'-R. B. at 300'- 15 syc mud to 140'-R.B. 10syc
The above well was plugged as follows: J. D. 4506'-8.P. 896"-145. C.W.C -5/34500'-100s/ Bottom, sand to 4480'-4 syc Water Plug at 300', Bailed fluid to 300'. 10'- R. B. at 300'- 15 syc mud to 140'- R.B. 10syc
The above well was plugged as follows: J.D. 4506'-S.P. 856"-145'. C.U.C51/2 4500'-100s/ Bottom, sand to 4480'-49C Water Plug at 300'. Bailed fluid to 300'. 10'. R.B. at 300'-15 ay c mid to 140'. R.B. 10a/C 10' R.B. 3:00'-15a/C R.B. 140-10a/C
The above well was plugged as follows: J. D. 4506'-8.P. 896"-145. C.W.C -5/34500'-100s/ Bottom, sand to 4480'-4 ofc Water Plug at 300', Bailed fluid to 300'. O'-R. B. at 300'- 15 of c mid to 140'-R.B. 10016
The above well was plugged as follows: J. D. 4506'-8.P. 85g''-145'. C.W.C - 5/2 4500'-100s/ Bottom, sand to 4480'-4 s/c Water Plug at 300'. Bailed fluid to 300'. O'. R. B. at 300'-15 s/c mid to 140'. R.B. 10s/c 10' R.B. 3:00'-15 s/C R.B. 140-10s/C R.B. 30-10s/C
The above well was plugged as follows: J.D. 4506'-S.P. 856"-145'. C.U.C51/2 4500'-100s/ Bottom, sand to 4480'-49C Water Plug at 300'. Bailed fluid to 300'. 10'. R.B. at 300'-15 ay c mid to 140'. R.B. 10a/C 10' R.B. 3:00'-15a/C R.B. 140-10a/C
The above well was plugged as follows: J. D. 4506' - S. P. 856''-145'. C.U.C - 51/2 4500'-100 st. Bottom, sand to 4480'-4 syc Water Plug at 300', Bailed fluid to 300'. 10'- R. B. at 300'-15 syc mud to 140'- R. B. 10 syc 10' R. B. 3:00'-15 syc R. B. 30-10 syc
The above well was plugged as follows: J. D. 4506' - S. P. 856''-145'. C.U.C - 51/2 4500'-100 st. Bottom, sand to 4480'-4 syc Water Plug at 300', Bailed fluid to 300'. 10'- R. B. at 300'-15 syc mud to 140'- R. B. 10 syc 10' R. B. 3:00'-15 syc R. B. 30-10 syc

INVOICED

DATE 4/5/61