

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
266 N. Main St., Ste. 220
Wichita, KS 67202-1513

API Well Number: 15-197-20095-00-02
Spot: NWNENE Sec/Twnshp/Rge: 19-12S-11E
4950 feet from S Section Line, 990 feet from E Section Line
Lease Name: STEUWE Well #: 1A SWD
County: WABAUNSEE Total Vertical Depth: 3198 feet

Operator License No.: 34232
Op Name: MUSTANG FUEL CORPORATION
Address: 9800 N. OKLAHOMA AVE.
OKLAHOMA CITY, OK 73114

String	Size	Depth (ft)	Pulled (ft)	Comment
PROD	5.5	3199		100 SX
SURF	8.625	212		140 SX

Well Type: SWD UIC Docket No: _____ Date/Time to Plug: 04/14/2015 12:00 PM
Plug Co. License No.: 34059 Plug Co. Name: HURRICANE SERVICES, INC.
Proposal Rcvd. from: CADE COTTLE Company: MUSTANG FUEL CORPORATION Phone: (405) 748-9400

Proposed Plugging Method: 1. Open well and blow down. If pressure exists, use a pump truck to kill well. MIRU WOR.2.ND WH. NU 7-1/16 $\frac{1}{2}$ 5K hydraulic BOP (w/ blind rams on bottom and 2-3/8 $\frac{1}{2}$ standard pipe rams on top). 3.RIH w/ WL and set 5-1/2 $\frac{1}{2}$ CIBP at +/- 3120 $\frac{1}{2}$. Dump 2 sks of cement on top of plug.4.POOH w/ WL and RIH w/ 3-1/8 $\frac{1}{2}$ perf guns loaded w/ 4 Big Hole charges at 90 degree phasing to shoot the following intervals:i.+/- 1400 $\frac{1}{2}$ (Top of Kansas City)ii.260 $\frac{1}{2}$ (50 $\frac{1}{2}$ below surface casing)5.RIH w/ 2-3/8 $\frac{1}{2}$ tbg to 2500 $\frac{1}{2}$ and pump a gel spacer to +/-1400 $\frac{1}{2}$. Spot 25 sks across perfs at 1400 $\frac{1}{2}$.6.POOH to 1200 $\frac{1}{2}$ and pump gel spacer from 1300-300 $\frac{1}{2}$. Cement 260 $\frac{1}{2}$ -Surface using +/- 70 sks. 60/40 Poz w/ 4% gel additive.7.POOH and LD tubing. ND BOP8.Cut off casing at surface and cap.9.Report results to KCC after operations have ceased.

Plugging Proposal Received By: TAYLOR HERMAN WitnessType: NONE
Date/Time Plugging Completed: 04/15/2015 12:00 PM KCC Agent: TAYLOR HERMAN

Actual Plugging Report:

SET BRIDGE PLUG AT 3120' WITH 2 SACKS OF CEMENT. PERFORATED THE CASING AT 1400' AND 270'. RAN 2 3/8" TUBING DOWN TO 2500' AND PUMPED 40 BARRELS OF GEL. PULLED TUBING UP TO 1410' AND PUMPED 25 SACKS OF CEMENT. PULLED TUBING UP TO 280' AND CIRCULATED CEMENT TO THE SURFACE ON THE INSIDE AND BACKSIDE OF THE PRODUCTION CASING.

Perfs:

Top	Bot	Thru	Comments
3180	3183		
RECEIVED KCC DIST # 3 MAY 14 2015 CHANUTE, KS TH			
Received KANSAS CORPORATION COMMISSION MAY 20 2015			

Remarks:

Plugged through: TBG

District: 03

Signed

Taylor C Herman

(TECHNICIAN)

MAY 27 2015 ckm

CONSERVATION DIVISION
WICHITA, KS