KANSAS

FORE CETYLED STATE COMPLEXION

STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

MAR 1 1 1976 3-11-1976 CONSERVATION DIVISION Wichita, Kansas

J. Lewis Brock Administrator 245 North Market Wichita, Kansas 67202

API Number 15 - 007- 20-395-900 (of this well)

Lease Name Pratt Well No. 1 Location 200! W NE/NE/NE Sec.18 Twp.31s Rge. 1 County Barber Total Depth 4 Abandoned Oil Well Gas Well Input Well SWD Well Other well as hereafter indicated Plugging Contractor Red Tiger Drlg Co Address 1720 Wichita Plaza Wichita, KS License No. Operation Completed: Hour 7:15 PM Day 9 Month 3 The above well was plugged as follows: 317 ft 8 5/8 surface cemented with 230 sacks. Pump plug, cement to 300 ft. Mud to 40 ft, plug, ½ sack hulls, 15 sack	оц рад Х
Abandoned Oil Well Gas Well Input Well SWD Well Other well as hereafter indicated Plugging Contractor Red Tiger Drlg Co Address 1720 Wichita Plaza Wichita, KS License No. Operation Completed: Hour 7:15 PM Day 9 Month 3 The above well was plugged as follows: 317 ft 8 5/8 surface cemented with 230 sacks. Pump plug,	оц рад Х
Abandoned Oil Well Gas Well Input Well SWD Well Other well as hereafter indicated Plugging Contractor Red Tiger Drlg Co Address 1720 Wichita Plaza Wichita, KS License No. Operation Completed: Hour 7:15 PM Day 9 Month 3 The above well was plugged as follows: 317 ft 8 5/8 surface cemented with 230 sacks. Pump plug,	D & A X
Plugging Contractor Red Tiger Drlg Co Address 1720 Wichita Plaza Wichita, KS Departion Completed: Hour 7:15 PM Day 9 Month 3 The above well was plugged as follows: 317 ft 8 5/8 surface cemented with 230 sacks. Pump plug,	_{Year} 1976
Address 1720 Wichita Plaza Wichita, KS Departion Completed: Hour 7:15 PM Day 9 Month 3 The above well was plugged as follows: 317 ft 8 5/8 surface cemented with 230 sacks. Pump plug,	Year 1976
Operation Completed: Hour 7:15 PM Day 9 Month 3 The above well was plugged as follows: 317 ft 8 5/8 surface cemented with 230 sacks. Pump plug,	Year 1976
The above well was plugged as follows: 317 ft 8 5/8 surface cemented with 230 sacks. Pump plug,	Year 1976
317 ft 8 5/8 surface cemented with 230 sacks. Pump plug,	
	35 sacks
Cemetro to journal and the first fir	cks cement
to surface. 2 sacks cement in rat hole.	
Pumped by Allied Cementing Great Bend, KS	
	