

1 020060

FEB 2 2 1987

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-097-21,231-0000
35
SE SW SE, SEC. 25, T 29 S, R 18 W/E

TECHNICIAN'S PLUGGING REPORT

Operator License # 5171

330 feet from S section line

1650 feet from E section line

Operator: TXO Production Corporation
Name & Address 155 North Market, Suite 1000
Wichita, KS 67202

Lease Name Nichols "H" Well # 2

County Kiowa 163.80

Well Total Depth 5040 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 263

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor H-30 Drilling Inc. License Number 5107

Address 251 North Water, Suite 10, Wichita, KS 67202

Company to plug at: Hour: 9 a.m. Day: 22 Month: 2 Year: 19 87

Plugging proposal received from Rex Craven

(company name) H-30 Drilling Inc. (phone) 316-263-2043

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1100'
Elevation 2157' GL

1st plug at 1100' with 50 sx cement,

2nd plug at 300' with 50 sx cement,

3rd plug at 40-0' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement, 5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Paul Luthi
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 12:30 p.m. Day: 22 Month: 2 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 1100' with 50 sx cement,

2nd plug at 300' with 50 sx cement,

3rd plug at 40-0' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 10 sx cement.

STATE CORPORATION COMMISSION
2-25-1987
FEB 25 1987
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.
(If additional description is necessary, use BACK of this form.)

INVOICED
DATE / all work observe this plugging.

DATE 2-26-87
INV. NO. 16240

Signed Glen R. Barlow
(TECHNICIAN)

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date February 12, 1987
 month day year

API Number 15- 097-21,231-0000

OPERATOR: License # 5171
 Name T.O. Production Corp.
 Address 155 N. Market, Ste 1000
 City/State/Zip Wichita, Kansas 67202
 Contact Person Gary E. Wurdeman
 Phone (316) 269-7600

SE SW SE Sec. 35 Twp. 29 S, Rg. 18 East
 330' West
 1650' Ft. from South Line of Section
 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5107
 Name H-30 Inc.
 City/State Wichita, Kansas 67202

Nearest lease or unit boundary line 330' feet
 County Kiowa
 Lease Name NICHOLS 'H' Well # 2
 Ground surface elevation 2157' feet MSL
 Domestic well within 330 feet: —yes X no
 Municipal well within one mile: —yes X no
 Depth to bottom of fresh water 100'
 Depth to bottom of usable water 200' 250'
 Surface pipe by Alternate: 1 X
 Surface pipe planned to be set 250'
 Conductor pipe required NONE
 Projected Total Depth 5100' feet
 Formation Mississippi

Well Drilled For: Well Class: Type Equipment:
 Oil — SWD — Infield Mud Rotary
 Gas — Inj Pool Ext. — Air Rotary
 OWWO — Expl — Wildcat — Cable

If OWWO: old well info as follows:

Operator
 Well Name
 Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq, plus eventually plugging hole to KCC specifications.

Date 2-10-87 Signature of Operator or Agent [Signature] Title Drlg & Prod Engineer

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt. [Signature]

This Authorization Expires 8-11-87 Approved By [Signature]

*Spud 2 12 87
 set 250' 178*

SE SW SE Sec. 25 Twp. 29 S, Rg. 18 East
 West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 1600' feet depth with 15 sxs sxs of 65/35 Poz
 2nd plug @ 350' feet depth with 25 sxs sxs of ..
 3rd plug @ 40' feet depth with 10 sxs + bridge sxs of ..
 4th plug @ feet depth with sxs of ..
 5th plug @ feet depth with sxs of ..
 (2) Rathole with 10 sxs (b) Mousehole with 10 sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging.

PUSHER <u>Ref Cranes</u>	TD <u>5040</u> FORMATION	SURFACE PIPE <u>8 1/8 @ 263'</u>	ANHYDRITE <u>1100'</u> ELEVATION <u>2157'</u>	STARTING TIME & DATE <u>900AM. 2-22-87</u>	COMPLETION TIME & DATE <u>12:30PM 22. 87</u>	1st PLUG @ <u>1100</u> FT. W/ <u>50</u> SX	2nd PLUG @ <u>300</u> FT. W/ <u>50</u> SX	3rd PLUG @ <u>40-0</u> FT. W/ <u>10</u> SX	4th PLUG @ FT. W/ SX	RAT HOLE CIRCULATED W/ <u>15</u> SX	MOUSE HOLE CIRCULATED W/ <u>10</u> SX	WATER WELL PLUGGED W/ .. SX	CEMENT COMPANY <u>Halliburton</u>	TECHNICIAN <u>P.J.</u>	<u>60/40 w/ 69%</u>
--------------------------	--------------------------	----------------------------------	---	--	--	--	---	--	----------------------------------	-------------------------------------	---------------------------------------	-----------------------------	-----------------------------------	------------------------	---------------------

STATE CORPORATION COMMISSION
 FEB 25 1987
 CONSERVATION DIVISION
 Wichita, Kansas

D.R.