

1 070275

DEC 30 1986

API NUMBER 15- 097-21,227-0000

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION 75'E C SE SE, SEC. 36, T 29 S, R 20 W/E  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

660 feet from S section line

585 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Lease Name Ralstin Well # 1-36

Operator License # 4197

County Kiowa 170.14

Operator: Dunne Oil Company

Well Total Depth 5235 feet

Name & Address 100 S. Main, Suite 520

Conductor Pipe: Size \_\_\_\_\_ feet

Wichita, KS 67202

Surface Casing: Size 8 5/8 feet 610

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Red Tiger Drilling Company License Number 5302

Address 1720 KS State Bank Bldg, Wichita, KS 67202

Company to plug at: Hour: 12:30 a.m. Day: 30 Month: 12 Year: 19 86

Plugging proposal received from Mike Rempe

(company name) Red Tiger Drilling Company (phone) 316-862-5952

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2359'

1st plug at 1300' with 50 sx cement, 2nd plug at 660' with 50 sx cement, Anhydrite 1305-1315'

3rd plug at 40' with 10 sx cement, 4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Richard Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 3 a.m. Day: 30 Month: 12 Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 1320' with 50 sx cement,

2nd plug at 660' with 50 sx cement,

3rd plug at 40' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

STATE CORPORATION COMMISSION

DEC 31 1986

CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.  
(If additional description is necessary, use BACK of this form.)

INVOICED (If you did not observe this plugging.)

DATE 1-5-87

Signed Dan Andrew  
(TECHNICIAN)

INV. NO. 15753  
12-30

**NOTICE OF INTENTION TO DRILL**

(see rules on reverse side)

Starting Date ..... 12 month 10 day 86 year

API Number 15- 097-21,227-0000  
 75' E of ..... East  
 C. SE. SE. Sec. 36. Twp. 29. S, Rg. 20W. W West  
 ..... 660 Ft. from South Line of Section  
 ..... 585 Ft. from East Line of Section

OPERATOR: License # 4197  
 Name Dunne Oil Company  
 Address 100 S. Main, Ste. 520  
 City/State/Zip Wichita, Kansas 67202  
 Contact Person Randy Gardner  
 Phone 267-3448

(Note: Locate well on Section Plat on reverse side)  
 Nearest lease or unit boundary line ..... 585 feet  
 County Kiowa

CONTRACTOR: License # 5302  
 Name Red Tiger Drilling Co.  
 City/State Wichita, Kansas 67202

Lease Name Ralstin Well # 1-36  
 Ground surface elevation 2359 feet MSL

Well Drilled For: Well Class: Type Equipment:  
 Oil  SWD  Infield  Mud Rotary  
 Gas  Inj  Pool Ext.  Air Rotary  
 DWWO  Expl  Wildcat  Cable

Domestic well within 330 feet:  yes  no  
 Municipal well within one mile:  yes  no  
 Depth to bottom of fresh water 190  
 Depth to bottom of usable water 250

If OWWO: old well info as follows:  
 Operator .....  
 Well Name .....  
 Comp Date ..... Old Total Depth .....

Surface pipe by Alternate:  2  
 Surface pipe planned to be set 600  
 Conductor pipe required N/A  
 Projected Total Depth 5200 feet  
 Formation Miss

I certify that well will comply with K.S.A. 55-101, et seq., plus any other applicable specifications.  
 Date 12-8-86 Signature of Operator or Agent Title Owner

Signature of Operator or Agent Title Owner

For KCC Use: BY RED TIGER DRILLING CO.  
 Conductor Pipe Required ..... feet; Minimum Surface Pipe Required ..... feet per Alt. 1 &  
 This Authorization Expires 6-8-87 Approved By

Approved By

Set 632' of 8 5/8 on 12/19/86

C SE SE Sec. 36 Twp. 29S S, Rg. 20W X East West

**PLUGGING PROPOSAL IF ABOVE IS D & A**

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 1600' 1300'	feet depth with 50 SX	sxs of 60-40 poz, 6 % gel
2nd plug @ 630' 660'	feet depth with 50 SX	sxs of
3rd plug @ 40'	feet depth with 10 SX	sxs of
4th plug @	feet depth with	sxs of
5th plug @	feet depth with	sxs of
(2) Rathole with 15'	sxs	(b) Mousehole with sxs

PUSHER Mike Rempfe  
 TD 5235' FORMATION Miss.  
 SURFACE PIPE 610' @ 8 5/8"  
 ANHYDRITE 1305'-1315' ELEVATION 2359'  
 STARTING TIME & DATE 12:30 AM 12-30-86  
 COMPLETION TIME & DATE 3:00 AM 12-30-86  
 1st PLUG @ 1320 FT. W/ 50 SX  
 2nd PLUG @ 660 FT. W/ 50 SX  
 3rd PLUG @ 40 FT. W/ 10 SX  
 4th PLUG @ FT. W/ SX  
 RAT HOLE CIRCULATED W/ 15 SX  
 6 1/4" poz. 6% gel  
 MOUSE HOLE CIRCULATED W/ SX  
 WATER WELL PLUGGED W/ To Landowner SX  
 CEMENT COMPANY A.J. Titon  
 TECHNICIAN Dan Goodrow

STATE CORPORATION COMMISSION  
 DEC 31 1986  
 CONSERVATION DIVISION  
 Wichita, Kansas