## STATE OF KANSAS STATE CORPORATION COMMISSION

## WELL PLUGGING RECORD

Give Ail Information Completely		Pratt	( )	méw Caa	13 70 2	<sup>7</sup> Ω 10 [Δ] 12.
Make Required Affidavit Mail or Deliver Report to	· Yosatis				age from 1	28 Rge. 14 K
Conservation Division			CMugang	OP 1000	age from t	THES
State Corporation Comm.	Lease (	NE SW Dwner k:	an – Ex	Inc.	<del> </del>	
245 North Water	Lease N		Robert		W	ell No. #1
Wichita, KS 67202		Address				chita, KS 67
						r Dry Hole)
	Charact	et or wer	-		OII, GES O	r Dry noie)
!!!!!		<del></del>		y Hole		7.77.0
┃		ell comple		<del></del>		1/18 19
		tion for			-	1/18 19
		tion for	_	g approve	·a	<u>1/18</u> 19
		g commend		<del></del>		1/18 19
		g complet		-£ 23 -		1/18 19
	-				_	g formation
	T. NO.	commerc:	<u>lal qua</u>	inities	OL OIT 6	encountered.
	II a pr	Oducing W	err is	вридопеа	, date of	last production
	Was now	mi oai on -	headnad	from the	Concernat	ion Division or
Locale well correctly on above Section Flat	_					
					ommenced?_	yes
Name of Conservation Agent who so	_					
Producing formation		th to top		ottom	Total De	pth of Well
Show depth and thickness of all	water, oil	and gas	formation	ons.		
OTA CAR OR WATER PEROPOR				,		
OIL, GAS OR WATER RECORDS					· · · · · · · · · · · · · · · · · · ·	CASING RECORD
FORMATION C	<u>XO</u> NTENT	_ FROM	TO	SIZE	PUT IN	. PULLED OUT
				1		
						<u> </u>
			1	1		
				<del></del>	<del></del>	<del> </del>
Describe in detail the manner was placed and the method or method plugs were used, state the character feet for each plug  Set first plug at 790	hods used cter of sa set	in introduced and de	ducing in the place of 60/	t into the ced, from 40 pozm	e hold. I	f cement or other feet to
plugs were used, state the character feet for each plug  Set first plug at 790  Set second plug at 42  10 sacks and a bridge	hods used cter of sa set. O' with 525' with 525' sa	in introduced and de	of 60/	t into the ced, from 1/40 pozment third	e hold. I ix 2% ge plug at	f cement or other feet to
plugs were used, state the character feet for each plug  Set first plug at 790  Set second plug at 42	hods used cter of sa set. O' with 525' with 525' sa	in introduced and description in the sacks of the sacks o	of 60/	t into the ced, from 1/40 pozment third	e hold. I ix 2% ge plug at	f cement or other feet to
plugs were used, state the character feet for each plug  Set first plug at 790  Set second plug at 42  10 sacks and a bridge	hods used cter of sa set. O' with 525' with 525' sa	in introduced and description in the sacks of the sacks o	of 60/	t into the ced, from 1/40 pozment third	e hold. I ix 2% ge plug at	f cement or other feet to
plugs were used, state the character feet for each plug  Set first plug at 790  Set second plug at 42  10 sacks and a bridge	hods used cter of sa set. O' with 525' with 525' sa	in introduced and description in the sacks of the sacks o	of 60/	t into the ced, from 1/40 pozment third	e hold. I ix 2% ge plug at	f cement or other feet to
plugs were used, state the character feet for each plug  Set first plug at 790  Set second plug at 42  10 sacks and a bridge	hods used cter of sa set. O' with 525' with 525' sa	in introduced and description in the sacks of the sacks o	of 60/ s. Set	t into the ced, from 1/40 pozment third	e hold. I ix 2% ge plug at	f cement or other feet to
plugs were used, state the character feet for each plug  Set first plug at 790  Set second plug at 42  10 sacks and a bridge	hods used cter of sa set. O' with 525' with 525' sa	in introduced and description in the sacks of the sacks o	of 60/ s. Set	t into the ced, from 1/40 pozment third	e hold. I ix 2% ge plug at	f cement or other feet to
plugs were used, state the character feet for each plug  Set first plug at 790  Set second plug at 42  10 sacks and a bridge	hods used cter of sa set. O' with 525' with 525' sa	in introduced and description in the sacks of the sacks o	of 60/ s. Set	t into the ced, from 1/40 pozment third	e hold. I ix 2% ge plug at	f cement or other feet to
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462	hods used cter of sa set. O' with 525' with 2. 15 sa 20'.	in introduced and description in the second	of 60/s. Set	t into the ced, from 40 pozme third chole.	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des	hods used cter of sa set. O' with 525' with 2. 15 sa 20'. scription	in introduce and description of the sacks of the sack of the sacks of the sack	of 60/s. Set the rat	t into the ced, from 40 pozme third chole.	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462	hods used cter of sa set. O' with 525' with 2. 15 sa 20'. scription	in introduce and description of the sacks of the sack of the sacks of the sack	of 60/s. Set the rat	t into the ced, from 40 pozme third chole.	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des	hods used cter of sa set. O' with 525' with 2. 15 sa 20'. scription	in introduce and description of the sacks of the sack of the sacks of the sack	of 60/s. Set the rat	t into the ced, from 40 pozme third chole.	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Ka	hods used cter of sa set.  O' with 525' with e. 15 sa 20'.  scription aw Drilli	in introduce and description of the sacks in the sacks indicate the sacks in the sacks in the sacks in the sacks in the sa	of 60/s. Set the rate ary, use Inc.	t into the ced, from 40 pozme third chole.	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Ka	hods used cter of sa set. 0' with 5 25' with 15 sa 20'.  scription aw Drilli	in introduce and description of the sacks in the sacks indicate the sacks in the sacks in the sacks in the sacks in the sa	of 60/s. Set the rat	t into the ced, from 40 pozme third chole.	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Karsas K. S. Martin, Preside	hods used cter of sa set. 0' with 5 25' with 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw	in introduce and description of the sacks in the sacks indicated in the sacks in the sacks in the sacks in the sacks in th	of 60/s. Set the rat	t into the ced, from 40 pozme third chole.	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss. (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790 Set second plug at 42 10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kansas  K. S. Martin, Preside of the above-described well, being	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli COUNT ent, Kaw ng first du	in introduce and description of the sacks in the sacks indiction in the sacks in the sacks in the sacks in the sacks in th	of 60/s. Set the rate ary, use Inc.  Sedgwing (MM/M) on oath	t into the ced, from 40 pozme third chole.  BACK of ck	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter	hods used cter of sa set.  O' with 5 25' with  15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first du ss berein of	in introduce and demonstrated and demons	of 60/s. Set the rate ary, use Inc.  Sedgwing Canality on oath and the	t into the ced, from 40 pozme third chole.  BACK of ck	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790 Set second plug at 42 10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kansas  K. S. Martin, Preside of the above-described well, being	hods used cter of sa set.  O' with 5 25' with  15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first du ss berein of	in introduce and demonstrated and demons	of 60/s. Set the rate ary, use Inc.  Sedgwing Canality on oath and the	t into the ced, from 40 pozme third chole.  BACK of ck	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNTAINT Kaw ag first during and containt cont	in introduce and demonstrated and demons	of 60/s. Set the rate ary, use Inc.  Sedgwing Canality on oath and the	t into the ced, from 40 pozme third chole.  BACK of ck	e hold. I	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNTAINT Kaw ag first during and containt cont	in introduce and description of the sacks in	of 60/s. Set the rate ary, use Inc.  Sedgwing Campany on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of ck  WMNXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	this shee	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss.  www.xxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNTAINT Kaw ag first during and containt cont	in introduce and description of the sacks in	of 60/s. Set the rate ary, use Inc.  Sedgwing Campany on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of ck waxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	this shee	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kassas K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are transported with the same are transp	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor (Sign	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat the rat sed will on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of ck WXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	this shee  this shee  That I have above der Wichical	f cement or other feet to  1 3% C.C. 40' wither at 3:30 a.m.  t)  ss.  k k k k k k k k k k k k k k k k k k k
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor (Sign	is necessing Co.,  TY OF Drilling Sworn contained crect. So nature)	of 60/s. Set the rat the rat sed will on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of ck waxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	this shee  this shee  That I have above der Wichical	f cement or other feet to  1 3% c.c. 40' wither at 3:30 a.m.  t)  ss.  www.xxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kassas K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are transported with the same are transp	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor (Sign	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat the rat sed will on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of ck WXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	this shee  this shee  That I have above der Wichical	f cement or other feet to  1 3% C.C. 40' wither at 3:30 a.m.  t)  ss.  k k k k k k k k k k k k k k k k k k k
was placed and the method or method plugs were used, state the character feet for each plug.  Set first plug at 790  Set second plug at 42  10 sacks and a bridge on 1/18/84. T.D. 462  (If additional des Name of Plugging Contractor Kassas K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are transported with the same are transp	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor (Sign	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat the rat sed will on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of ck WXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	this shee  this shee  That I have the above the control of the con	f cement or other feet to  1 3% c.c. 40' withen at 3:30 a.m  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug set first plug at 790 Set second plug at 42 10 sacks and a bridge on 1/18/84. T.D. 462 On 1/18/84. T.D. 462  STATE OF Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are treatments of the same are treatments.	hods used cter of sa set.  O' with 5 25' with 15 sa 20'.  scription aw Drilli  COUNT on Kaw ag first due and cor (Sign or me this	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat the rat sed will on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of ck WXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	this shee  this shee  That I have the above the control of the con	f cement or other feet to  1 3% C.C. 40' wither at 3:30 a.m.  t)  ss.  k k k k k k k k k k k k k k k k k k k
was placed and the method or methology were used, state the character feet for each plug at 790 Set first plug at 790 Set second plug at 42 10 sacks and a bridge on 1/18/84. T.D. 462 On 1/18/84. T.D. 462  STATE OF Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are treatments of the same are treatments. SUBSCRIBED AND SWORN TO before the same are treatments of the same are treatments.	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor (Signature and cor	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rate ary, use Inc.  Sedgwing Company on oath and the control of the pure ary and the control of the pure ary	t into the ced, from 40 pozme third chole.  BACK of EACK of Good, says: log of telegon Center of January	this shee wichi Address)	f cement or other feet to  1 3% c.c. 40' withen at 3:30 a.m  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or method plugs were used, state the character feet for each plug set first plug at 790 Set second plug at 42 10 sacks and a bridge on 1/18/84. T.D. 462 On 1/18/84. T.D. 462  STATE OF Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are treatments of the same are treatments.	hods used cter of sa set.  O' with 5 25' with 2. 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor (Signature and cor	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat ary, use Inc.  Sedgwing Campanion on oath and the bell help model.	t into the ced, from 40 pozme third chole.  BACK of CENTY SAY SAY SAY SAY SAY SAY SAY SAY SAY SA	this shee	f cement or other feet to  1 3% c.c. 40' withen at 3:30 a.m  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or methology were used, state the character feet for each plug at 790 Set first plug at 790 Set second plug at 42 10 sacks and a bridge on 1/18/84. T.D. 462 On 1/18/84. T.D. 462  STATE OF Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are treatments of the same are treatments. SUBSCRIBED AND SWORN TO before the same are treatments of the same are treatments.	hods used cter of sa set.  O' with 5 25' with 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor  (Signature me this	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat the rat sedgwing company on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of CERT SAN XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	this shee  That I have the above der Wichical Address)  That I have the above der Wichical Address that I have the Address that I	f cement or other feet to  1 3% c.c. 40' withen at 3:30 a.m  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or methology were used, state the charactest feet for each plug at 790. Set first plug at 790. Set second plug at 42. 10 sacks and a bridge on 1/18/84. T.D. 462.    Commission expires	hods used cter of sa set.  O' with 5 25' with 15 sa 20'.  scription aw Drilli  COUNT ent, Kaw ag first due and cor (Sign ore me this 7, 1984	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat the rat sedgwing company on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of CENTY SAY SAY SAY SAY SAY SAY SAY SAY SAY SA	this shee  That I have the above der Wichical Address)  That I have the above der Wichical Address that I have the Address that I	f cement or other feet to  1 3% c.c. 40' withen at 3:30 a.m  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
was placed and the method or methology were used, state the character feet for each plug at 790 Set first plug at 790 Set second plug at 42 10 sacks and a bridge on 1/18/84. T.D. 462 On 1/18/84. T.D. 462  STATE OF Kansas  K. S. Martin, Preside of the above-described well, being the facts, statements, and matter as filed and that the same are transfer of the same are transfer of the same are transfer of the facts.	hods used cter of sa set.  O' with 5 25' with 15 sa 20'.  scription aw Drilli  COUNT on Kaw ag first due and cor (Sign ore me this 7, 1984	in introduce and description in the sand description in the sacks in t	of 60/s. Set the rat the rat sedgwing company on oath and the chelp m	t into the ced, from 40 pozme third chole.  BACK of CERT SAN XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	this shee  That I have the above der Wichical Address)  That I have the above der Wichical Address that I have the Address that I	f cement or other feet to  1 3% c.c. 40' withen at 3:30 a.m  t)  ss.  kxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx

CONSERVATION DIVISION
Wichita, Kansas