

To: 1090292
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

6-9 API NUMBER 15- 119-20,790-A0002 12 R
E/2 SE NE, SEC. 12, T. 33 S, R. 26 W&E
3300 feet from S section line
330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # _____
Operator: Kansas Corporation Commission
Name: _____
Address: _____

Lease Name Pyle Well # 2-12A
County Meade
Well Total Depth 6000 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 206

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X
Other well as hereinafter indicated _____

Plugging Contractor Murfin Drilling Company, Inc. License Number 30606
Address 250 N. Water, Ste. 300, Wichita, KS 67202

Company to plug at: Hour: 9 a.m. Day: 7 Month: 6 Year: 19 93

Plugging proposal received from Steve Durrant
(company name) KCC (phone) 316-225-6760

Work: Run tubing in hole and spot plugs as follows:

- 1st plug at 1350' with 50 sx cement,
- 2nd plug at 700' with 50 sx cement,
- 3rd plug at 230' with 50 sx cement,
- 4th plug at 40' with 10 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All X Part _____ None _____

Operations Completed: Hour: 9:30 a.m. Day: 9 Month: 6 Year: 19 93

ACTUAL PLUGGING REPORT 6/7/93-Arrived on location at 9 a.m. Murfin Drilling pulling unit on location. Ran tubing in hole to 468.49'-hit solid bridge. Hooked on to Allied Cementing pump truck to try and wash out bridge. Gained approx. 1". Shut down at 12:30 p.m. Murfin Drilling to bring out pump and power swivel 6/8/93.

6/8/93 Arrived on location at 8 a.m. Murfin Drilling pump & swivel on location. Ran tubing in hole to 458'. Lost 10' of hole in 24 hours. Started drilling at 458'. Had small amount of

Remarks: Used 60/40 Pozmix 6% gel by Allied. No casing recovery.
(If additional description is necessary, use BACK of this form)

I (did / ~~did not~~) observe this plugging.

Signed [Signature] (TECHNICIAN)
JUN 15 1993
CONSERVATION DIVISION
Wichita, Kansas

CONTINUED:

returns, then lost circulation.. Approx. 240 bbls. fresh water. Started pulling tubing, and well started flowing approx. 90 bbls. fresh water to pit. Called Richard Lacey and was instructed to start cementing through tubing at 458'. Allied hooked on to tubing and pumped in 10 sx gel and 160 sx 60/40 Pozmix 6% gel cement. Returned 6 sx gel to pit. Pulled all tubing out of hole and shut down at 5:30 p.m. Well on vacuum. Ordered out 300 sx cement and 400 lbs. hulls for 6/9/93.

6/9/93 Arrived on location at 8 a.m. Ran tubing in hole to tag cement top. Was at 300'. Hooked on to tubing and pumped in 125 sx cement with 300 lbs. hulls. Circulated 10 sx cement to pit. Pulled tubing out of hole and pumped 10 sx cement down 8 5/8" casing. Well is cemented to surface. Job complete at 9:30 a.m.