| To:   | •                                  | API NUMBER 15-C  | 97-21,055-0000    |                      |
|---|------------------------------------|--|-------------------|----------------------|
| STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 |                                    | C SE NW , SEC. 4 , 7 29 S, R 18 W/EX  3300 Follow feet from NXX section line  3300 Follow W SE Corner of MXXX section line |                   |                      |
| TECHNICIA   | N'S PLUGGING REPORT                | 3300 FEL   | feetyfrom txxxx s | ection line          |
| Operator  | License / 5004                     | Lease Name Burg  | hett Well /       | 1                    |
| Operator:<br>Name&  | Vincent Oil Corporation            | County   |                   |                      |
|   | 125 North Market, Suite 1110       | Well Total Dept  | h4969             | 161.49               |
|   | Wichita, KS 67202                  | Conductor Pipe:  | Sizefe            | e†                   |
|   |                                    | Surface Casing:  | Size 8 5/8 feet   | 519                  |
| Abandoned   | Oll Well Gas Well                  | _ Input Well   | SWD Well          | D&AX                 |
| Other wel   | l as hereinafter indicated         |  |                   |                      |
|   | Contractor Wheatstate Oilfield     |  |                   | 5149                 |
| Address   | Box 329, Pratt, KS 67124           |  | <del></del>       |                      |
| Company †   | o plug at: Hour: 9:00 am Day:      | 18 Month:  | August Year:      | 19_84                |
| Plugging  | proposal received from             | Roger Baker  |                   |                      |
| <del>-</del> -  | name) Wheatstate                   |  |                   |                      |
| • ,   | to fill hole with heavy mud and    |  |                   |                      |
|   | at 1200' with 50 sx cement         |  |                   |                      |
| 2nd plug  | at 570' with 50 sx cement          |  | <del></del>       |                      |
| <u></u>   |                                    | •  |                   |                      |
|   | to circulate rat hole with 15 sx   |  |                   | hole with            |
|   | . md                               |  | 7                 |                      |
|   | nent. Plug water well with 5 sx (  | 0347 N0C01704 07   | (TECHNICI)        | AN)                  |
| Plugging  | Operations attended by Agent?: A   | Part_  | None_             | Х                    |
| Operation   | as Completed: Hour: 11:00 am Day:_ | Month:   | August Year       | :19 84               |
| ACTUAL PL   | UGGING REPORT lst plug at 1200'    | with 50 sx cement,   | 2nd plug at 570   | with 50 sx           |
| cement, 3   | 3rd & 4th plugs — solid bridge — 1 | nulls - plug at 40'  | cement to sur     | face with            |
| 10 sx cen   | ment, 5thplug to circulate rat ho  | le with 15 sx cemen  | t, 6th plug to ci | rculate              |
| mouse hol   | le with 10 sx cement. Plugged wat  | er well with 15 sx   | cement. RECEI     | VED<br>ON COMMISSION |
|   |                                    |  | AUG 2 4           |                      |
| Used 60/40 Pozmix 2% gel 3% cc by   |                                    | v Buie   |                   |                      |
| Remarks:_   | Used 60/40 Pozmix 2% gel 3% cc by  | necessary, use BAC   | K of this forman  | ansas                |
|   | did not) observe this plugging.    |  | 0 0 0 -           | <i>1-1</i> 2         |

DATE 8 - 29 84 INV. NO. 3469

FORM CP-2/3 Rev.01-84