

10-19-87

API NUMBER 15- 097-21,252 -0000

To: 1 070446  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

C SW/4 NE/4, SEC. 25, T 29 S, R 16 W/EX  
3300 feet from S section line  
1980 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5428

Lease Name Piester Well # 1

Operator: Graves Drilling Company, Inc.

County Kiowa 163.48

Name & Address 151 North Main, Suite 850

Well Total Depth 5030 feet

Wichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 262

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Duke Drilling Company, Inc. License Number 5929

Address 205 East Central, Suite 120, Wichita, KS 67202

Company to plug at: Hour: 2:13 a.m. Day: 19 Month: 10 Year: 19 87

Plugging proposal received from John Armbruster

(company name) Duke Drilling Company, Inc. (phone) 316-267-1331

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2000' Anhydrite 893-928'

1st plug at 930' with 50 sx cement, 2nd plug at 750' with 40 sx cement,

3rd plug at 310' with 50 sx cement, 4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Duane Rankin (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 4 a.m. Day: 19 Month: 10 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 930' with 50 sx cement,

2nd plug at 750' with 40 sx cement,

3rd plug at 310' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

OCT 21 1987  
10-21-87

CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.

(if additional description is necessary, use BACK of this form.)

INVOICED

(did not) observe this plugging.

DATE 10-22-87

Signed Dan Goodson (TECHNICIAN)

INV. NO. 18615

10-19

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date. October 8, 1987  
month day year

API Number 15- 097-21,252-0000

OPERATOR: License # 5428  
Name Graves Drilling Co., Inc.  
Address 151 N. Main, Suite 850  
City/State/Zip Wichita, KS 67202  
Contact Person Karen L. Seiler  
Phone 316-265-7233

C. SW/4 NE/4 Sec 25 Twp 29 S, Rg. 16 X East  
3300 Ft. from South Line of Section  
1980 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

Nearest lease or unit boundary line 660 feet  
County Kiowa

CONTRACTOR: License # 5929  
Name Duke Drilling Co., Inc.  
City/State Wichita, Ks

Lease Name Plester Well # 1  
Ground surface elevation 1980 Approx. feet MSL

Well Drilled For: Well Class: Type Equipment:  
X Oil — Storage — Infield X Mud Rotary  
— Gas — Inj — Pool Ext. — Air Rotary  
— OWWO — Expl X Wildcat — Cable

Domestic well within 330 feet: — yes X no  
Municipal well within one mile: — yes X no

Depth to bottom of fresh water 80  
Depth to bottom of usable water 100

If OWWO: old well info as follows:  
Operator  
Well Name  
Comp Date Old Total Depth.

Surface pipe by Alternate: 1 X 2  
Surface pipe planned to be set 230

Conductor pipe required None  
Projected Total Depth 5000 feet

Formation Simpson

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KGC specifications.  
Date 9-18-87 Signature of Operator or Agent Richard M. Lusk Title Geologist

For KCC Use:  
Conductor Pipe Required 200 feet; Minimum Surface Pipe Required 200 feet per Alt. (1) X  
This Authorization Expires 4-1-88 Approved By RCH/10-1-87

EFFECTIVE DATE: 10-6-87

Spud 10/9/87 2:00 PM NO OWO  
240' 8 9/8

C SW/4 NE/4 Sec 25 Twp 29 S, Rg. 16 X East  
3300 Ft. from South Line of Section  
1980 Ft. from East Line of Section

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Recommendation: 60/40 Posmix w/6% gel

1st plug @ ft. deep 750' base of Anhydrite or formation with 50 sx. feet of  
2nd plug @ ft. deep 30' below base of surface pipe w/50 sx. feet of  
3rd plug @ ft. deep 40' to 0' or formation with w/10 sx. feet of  
4th plug @ ft. deep 15 sx. in rathole or formation with — feet of  
5th plug @ ft. deep 10 sx. in mousehole or formation with — feet of  
(2) Rathole to surface minus 5 feet (b) Mousehole to surface minus 5 feet

PUSHER Coleman Anderson  
TD 5030' FORMATION Arb.  
SURFACE PIPE 8 1/4" @ 262'  
ANHYDRITE 893' ELEVATION 2000'  
STARTING TIME & DATE 10-19-87 2:13 AM  
COMPLETION TIME & DATE 4:00 AM  
going to Pulverized plug  
1st PLUG @ FT. W/ SX  
2nd PLUG @ 930 FT. W/ 50 SX  
3rd PLUG @ 750 FT. W/ 40 SX  
4th PLUG @ 310 FT. W/ 50 SX  
5th RAT HOLE CIRCULATED W/ 15 10 SX  
MOUSE HOLE CIRCULATED W/ — SX  
WATER WELL PLUGGED W/ — SX  
CEMENT COMPANY B.J. Titan  
TECHNICIAN Deane Rankin D.G.  
60/40 w/6% gel

RECEIVED  
STATE CORPORATION COMMISSION  
OCT 21 1987  
CONSERVATION DIVISION  
Wichita, Kansas