AP NUMBER 15- Drill completion 4/12/81 STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION CONSERVATION DIVISION - PLUGGING SECTION CONSERVATION DIVISION - PLUGGING SECTION CSESE, sec. 2 , 7 28 , 8 16) C*	7 0 10 0 1 5	11-20-27-20141-000	
CONSERVATION DIVISION - PLUGGING SECTION CSE SE, SEC. 2 , T 28 S, R 16 vX 200 COLORADO OSERY BUILDING MICHITA, KANSAS 67202				
TECHNICIANIS PLUGGING REPORT County County	CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		C SE SE, SEC. 2, T 28 S, R 16 W XEX	
Operator: K & K Oil Company County Kiows Soriac Box 176 Chase, KS 67524 Conductor Pipe: Size Surface Cesing: Size 8 5/8 feet S			660 feet from S section line	
Operator: K & K Oil Company Name& Box 176 Chase, KS 67524 Conductor Pipe: Size feet Surface Casing: Size 8 5/8 foot 362 Abandoned Oil Weil X Cas Well Input Well SWD Well OAA Other well as hereinafter indicated Plugging Contractor Kelso Casing Pulling, Inc. License Number 6050 Address P.O. Box 347, Chase, KS 67524 Company to plug at: Hour: 2 P.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 Company name) P.O. Box 347, Chase, KS 67524 Company asse) P.O. Box 347, Chase, KS 67524 Vere: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'GL Ist plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, release wiper plug and pump 100 sx cement. Plugging Operations attended by Agent7: All X Part None Operations Completed: Hour: 2:30 p.m. Day: 20 Month: 11 Year: 19 87 ACTUAL PLUSGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 50 sx cement, 10 sx gel, 50 sx cement, 10 sx gel, 50 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" surface as fig with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" surface as fig with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" surface as fig with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" surface as fig with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" surface as fig with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10			660feet from E section line	
Name& Address Box 176	Operator l	License / 9339	Lease NameStroud Well # 2-2	
Address Rox 176	Operator:	K & K Oil Company	County Kiowa 157.30	
Chase, KS 67524 Conductor Pips: Size feet Surface Casing: Size 8 5/8 feet 362 Abandoned Oli Meil: X Gas Meil: Input Weil: SMD Weil: D&A Other weil as hereinefter Indicated Plugging Contractor Kelso Casing Pulling, Inc. License Number 6050 Address P.O. Box 347, Chase, KS 67524 Company to plug at: Hour: 2 p.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 (phone) 316-938-2457 were: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'CL 1st plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. **Characteristics** **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 350 psi. **Company name 150-600 psi and shut in 3		Box 176	Well Total Depth 4840 feet	
Surface Casing: Size 8 5/8 foot 362 Abandoned Oli Meii X Gas Msii Input Wei! SMD Weii DAA Other weil as hereinafter Indicated Plugging Contractor Kelso Casing Pulling, Inc. License Number 6050 Address P.O. Box 347, Chase, KS 67524 Company to plug at: Hour: 2 p.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 (phone) 316-938-2457 were: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'CI. 1st plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: Ali X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Signed Starkers and Agent 2 starkers and Michiga, Karing Aligning Agent 2 starkers and Michiga, Karing		Chase, KS 67524	Conductor Pipe: Size feet	
Abandoned Oil Weil X Gas Weil Input Weil SWD Weil D&A Other veil as hereinafter indicated Plugging Contractor Kelso Casing Fulling, Inc. License Number 6050 Address P.O. Box 347. Chase, KS 67524 Company to plug at: Hour: 2 p.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 (company name) P.O. Box 347, Chase, KS 67524 (phone) 316-938-2457 vere: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'GI. lst plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Pert None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) **Company to the standard of the		,		
Other well as hereinafter indicated Plugging Confrector Kelso Casing Pulling, Inc. License Number 6050 Address P.O. Box 347, Chase, KS 67524 Company to plug at: Hour: 2 p.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 (phone) 316-938-2457 Were: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'CL 1st plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Pert None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL Plugging REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. **Pumping pressure 150-600 psi and shut in 350 psi.** Remarks: Used 60/40 Poznix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) **Wichita, Kan. Wichita, Kan. Wi	Abandoned	Oll Well X Gas Well		
Plugging Contractor Kelso Casing Pulling, Inc. License Number 6050 Address P.O. Box 347, Chase, KS 67524 Company to plug at: Hour: 2 p.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 (phone) 316-938-2457 were: 4½" at 4839! Perfs at 4650-55, 4670-78, 4743-47! Elevation 2106'GL 1st plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m. Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. **Cl-Oc-S** Pumping pressure 150-600 psi and shut in 350 psi. **Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (!! add tional description is necessary, use BACK of this form.) **Company to plug and pumped 100 sx cement. **C				
Address P.O. Box 347, Chase, KS 67524 Company to plug at: Hour: 2 p.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (compeny name) P.O. Box 347, Chase, KS 67524 (phone) 316-938-2457 were: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'GL lst plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, release wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. (1-26-8) Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (1 additional description is necessary, use BACK of this form.) Company to pumped and pumped 100 sx cement. (1 ATTENTY AND			ng, Inc. 1 Icense Number 6050	
Company to plug at: Hour: 2 p.m. Day: 20 Month: 11 Year: 19 87 Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 (phone) 316-938-2457 were: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'GL lst plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, release wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" winer plug and pumped 100 sx cement. (1-26-8) Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½' casing. (1f additional description is necessary, use BACK of this form.) AXXXXXXX) observe this plugging. Signed Market Park Nontha, Kan		1	CICONSO NOMEDO	
Plugging proposal received from Clay Duntz (company name) P.O. Box 347, Chase, KS 67524 were: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'GL 1st plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations aftended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL Plugging REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. **TATE Company 1 st plug logs 1 st plug and shut in 350 psi.** Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) **TATE Company 1 st plugging.** **TATE Company 1			20 11 87	
(company name) P.O. Box 347, Chase, KS 67524 were: 4½" at 4839' Perfs at 4650-55, 4670-78, 4743-47' Elevation 2106'GL 1st plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour:2:30 p.m.Day: 20 Month: 11 Year:19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (11 additional description is necessary, use BACK of this form.) **Company Michita, Kan Mich	Company to	o plug at: Hour: 2 Pome Day:	Month: 11 Year:19 0'	
Ist plug sand back to 4600' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, releas wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year:19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Current North Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. Signed Altaphary Company of the plugging. Signed Altaphary Company Current North Remarks Rema		:	·	
2nd plug pump 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, release wiper plug and pump 100 sx cement. Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year:19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. (1 - 26-8) Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) CURL MANAXXXXX observe this plugging. Signed Standard Control of the	were: $4\frac{1}{2}$	" at 4839' Perfs at 4650-55, 467	<u>'0-78, 4743-47' Elevation 2106'GL</u>	
Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Nonth: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. **TATE IN TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, **TOTAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sanded back to 4600' and dumped 4 sx cement on top of sanded back to 4600' and dumped 4 sx cement on top of sanded back to 4600' a	1st plug	sand back to 4600° and dump 4 sx	cement on top of sand through bailer,	
Plugging Proposal Received by Richard Lacey (TECHNICIAN) Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour:2:30 p.m.Day: 20 Month: 11 Year:19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. ('(-26-8) Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Managery Wichita, Kan	2nd plug	pump 400 1bs. hulls, 10 sx gel,	50 sx cement, 10 sx gel, 100 lbs. hulls, release	
Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Standard Standard Signed Si	wiper plu	g and pump 100 sx cement.		
Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year:19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Standard Standard Signed Sig	•			
Plugging Operations attended by Agent?: All X Part None Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Ataxixxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx		Plugging Prop	osal Received by Richard Lacey	
Operations Completed: Hour: 2:30 p.m.Day: 20 Month: 11 Year: 19 87 ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. (1-26-8) Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (if additional description is necessary, use BACK of this form.) Signed Afglication Wichita, Kan			(TECHNICIAN)	
ACTUAL PLUGGING REPORT 1st plug sanded back to 4600' and dumped 4 sx cement on top of sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Affairm Committee Wichita, Kan				
sand through bailer, 2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. (1-26-8) Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Statement Wichita, Kan	Operation	s Completed: Hour: $\frac{2:30 \text{ p.m.}}{2:30}$	Month: 11 Year:1987	
2nd plug pumped down 8 5/8" surface casing with 400 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement. (1-26-8) Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Ataphanica Wichita, Kan	ACTUAL PL	UGGING REPORT <u>1st plug sanded ba</u>	ack to 4600 and dumped 4 sx cement on top of	
Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Signed Allied (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	sand thro	ugh bailer,		
Pumping pressure 150-600 psi and shut in 350 psi. Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) Construction Wichita, Kan	2nd plug	pumped down 8 5/8" surface casing	g with 400 lbs. hulls, 10 sx gel, 50 sx cement,	
Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) (CONSTRUCTION Wichita, Kan	10 sx gel	, 100 lbs. hulls, released 8 5/8	wiper plug and pumped 100 sx cement.	
Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 3309' of 4½" casing. (If additional description is necessary, use BACK of this form.) (CONSTRUCTION Wichita, Kan	,		11-26-8	
(If additional description is necessary, use BACK of this form.) Construction Signed Ataphan (Technic Any) Soon on a second of the second o	Pumping p	ressure 150-600 psi and shut in 3	350 psi. \$7ATE (**	
Signed Stephen (Textinion Wichita, Kan	Remarks:_	Used 60/40 Pozmix 6% gel by All:	ied. Recovered 3309' of 4½" casing.	
= 12-3-87 (TECHNIC PANY)	1 Codition 1	•		
= 12-3-87 (TECHNIC PANY)	1 V V 1	CED prugging.	Staned Stand Q Pl. 1. Wichita, Kan	
FORM CP-2/3	12-3	2-87	(TECHNIC DANY)	
NER / / L/ A J / DAI A 1 A	-	Company of the Compan	FORM CP-2/3 Rev.01-84	