

STATE OF KANSAS
STATE CORPORATION COMMISSION
CONSERVATION DIVISION

RECEIVED

FORM CP-1

Rev. 03/92

JAN 03 2003
KCC WICHITA

130 S. Market, Room 2078
Wichita, Kansas 67202

1-3-03

WELL PLUGGING APPLICATION FORM

(PLEASE TYPE FORM and File ONE Copy)

API #: 15-097-21495-0000 (Identifier number of this well). This must be listed for wells drilled since 1967; if no API# was issued, indicate sp or completion date

WELL OPERATOR: Carmen Schmitt, Inc.
(owner/company name)

KCC LICENSE # 5003
(operator's)

ADDRESS: P O Box 47 CITY: Great Bend, KS

STATE: Kansas ZIP CODE 67530-0047 CONTACT PHONE: 620-793-5100

LEASE: Zimmerman WELL#: No. 1 Section 4 Township 28s Range 20w

Se Sw Se SPOT LOCATION/QQQQ COUNTY: Edwards

330 FEET (in exact footage) FROM South LINE OF SECTION (NOT Lease Line)

1650 FEET (in exact footage) FROM East LINE OF SECTION (NOT Lease Line)

Check One: Oil Well Gas Well D&A XX SWD/ENHR WELL Docket #
CONDUCTOR CASING SIZE None SET AT None CEMENTED WITH SACKS
SURFACE CASING SIZE 8-5/8" SET AT 355" KB CEMENTED WITH 275 SACKS
PRODUCTION CASING SIZE None SET AT CEMENTED WITH SACKS

LIST (ALL) PERFORATIONS and BRIDGEPLUG SETS:
ELEVATION 2309 G.L. 2318 K.B. T.D. 4949 PBDT Anhydrite Depth 1297
(Stone Corral Formation)

CONDITION OF WELL: GOOD XX POOR CASING LEAK JUNK IN HOLE

PROPOSED METHOD OF PLUGGING:
Plugged well using 165sx of 60/40 Poz, 6% Gel in the following manner; Heavy mud in hole.
Bottom plug at 1240' - 50sx, 2nd plug at 600' - 40sx, 3rd plug at 360' - 40sx, top plug at 40' with
10sx cemented to surface. Plugged rathole with 15sx and mousehole with 10sx.
Plugging finished at 4:00 am on 01/01/03. Allied ticket # 2530. Reported to KCC 01/02/03.

IS WELL LOG ATTACHED TO THIS APPLICATION AS REQUIRED? Yes (YES,NO) IS ACO-1 FILED? ? (YES,NO)
If not explain why?

PLUGGING OF THIS WELL WILL BE DONE IN ACCORDANCE WITH K.S.A. 55-101 et. seq. AND THE RULES AND REGULATIONS OF THE STATE CORPORATION COMMISSION.

LIST NAME OF COMPANY REPRESENTATIVE AUTHORIZED TO BE IN CHARGE OF PLUGGING OPERATIONS:
Name: Lanny Saloga/Gary M. Talbott Phone#: (620) 672-9508

Address: P.O. Box 1006 City: Pratt State: Kansas

PLUGGING CONTRACTOR : Sterling Drilling Company KCC LICENSE #: 5142
(company name) (contractor's)

Address: P.O. Box 1006 City: Pratt State: Kansas Zip 67124

PROPOSED DATE AND HOUR OF PLUGGING (If Known?) Plugged well at 4:00 am on January 1st, 2003.

PAYMENT OF THE PLUGGING FEE (K.A.R. 82-3-118) WILL BE GUARANTEED BY: Operator X Agent

DATE: 01/02/03 AUTHORIZED OPERATOR OR AGENT: Gary M. Talbott
(signature) Gary M. Talbott, Agent for Operator

RECEIVED
JAN 03 2003
KCC WICHITA

Sterling Drilling Company, Rig #4

Box 1006, Pratt, Kansas 67124-1006
Office Phone (620) 672-9508, Fax 672-9509

SAMPLE LOG

Zimmerman No. 1

LOCATION: Se Sw Se Section 4 T 28s R 20w
API: 15-097-21495-0000 Edwards County, Kansas

OWNER: Carmen Schmitt, Inc.
CONTRACTOR: Sterling Drilling Company, Rig #4

COMMENCED: 12/16/02
COMPLETED: 01/01/03

TOTAL DEPTH: DRILLER 4949 FEET
LOGGER Did not Log FEET

Ground Elevation: 2309
KB Elevation: 2318

LOG

0 -	4 FEET	Top Sand
4 -	12 FEET	Clay
12 -	18 FEET	Sand and Gravel
18 -	40 FEET	Clay
40 -	62 FEET	Sand and Gravel
62 -	318 FEET	Clay, Sand and Gravel
318 -	1297 FEET	Redbeds
1297 -	1314 FEET	Anhydrite
1314	2500 FEET	Shales and Salt
2500	4949 FEET	Limestone/Shales

CASING RECORDS

Surface Casing:

Spud @ 5:30 pm on 12/16/02. Drilled 12-1/4" hole to 360'. Ran 9 joints of new 23# 8-5/8" surface casing tally 343.80' set at 354.80' KB. Cemented with 275 sx 60/40 Poz, 3% CC, 2% Gel. Plug down at 12:30 am on 12/17/02. Cement did circulate. Allied Cementing ticket #10166. Welded straps on bottom 3 joints, welded collars on remaining 6 joints.

Plugging Record:

Plugged well using 165sx of 60/40 Poz, 6% Gel in the following manner; Heavy mud in hole. Bottom plug at 1240' - 50sx, 2nd plug at 600' - 40sx, 3rd plug at 360' - 40sx, top plug at 40' with 10sx cemented to surface. Plugged rathole with 15sx and mousehole with 10sx. Plugging finished at 4:00 am on 01/01/03. Allied ticket # 2530. Reported to KCC 01/02/03.

DEVIATION SURVEYS

3/4 degree(s) at	360	feet
1-1/4 degree(s) at	3570	feet
1-1/4 degree(s) at	4943	feet