

10-20

To: 1 040180  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 151-20,653 -00-00  
NW SW, SEC. 12, T 28 S, R 15 W/E  
1980 feet from S section line  
4620 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 3738  
Operator: Sunrise Oilfield Supply  
Name & Address 621 17th Street, Suite 845  
Denver, CO 80293

Lease Name Rezeau Well # 1  
County Pratt 149.50  
Well Total Depth 4600 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 364

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ O&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Plains Inc. Well Service License Number 4072

Address P.O. Box 346, Ness City, KS 67560

Company to plug at: Hour: 11 a.m. Day: 20 Month: 10 Year: 1988

Plugging proposal received from Clint Base

(company name) Plains Inc. Well Service (phone) 913-798-3995

were: 4 1/2" at 4605' PBTD 4518' Perfs at 4487-4586' (5 sets)

1st plug sand back to 4437' and dump 4 sx cement on top of sand through bailer,

2nd plug pump 3 sx hulls, 15 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"

wiper plug and dump 100 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION  
OCT 27 1988

10-27-88

Plugging Proposal Received by Paul Luthi  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 4:15 p.m. Day: 20 Month: 10 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug sanded back to 4437' and dumped 4 sx cement on top of  
sand through bailer,

2nd plug pumped down 8 5/8" surface pipe with 300 lbs. hulls, 15 sx gel, 50 sx cement,  
10 sx gel, 100 lbs. hulls and 130 sx cement.

Maximum pressure 500 psi and shut in 300 psi.

NOTE: After pumping 300 lbs. of hulls, 15 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls,

Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 1723' of 4 1/2" casing. (over)  
(if additional description is necessary, use BACK of this form.)

INVOICED  
Observe this plugging.

Signed Stephen J. Pfeifer  
(TECHNICIAN)

DATE 10-31-88

INV. NO. 22853 NOV 15 1988

NOTE: Cont.

fluid came up the backside of the 8 5/8" surface pipe. Fluid surfaced at 11:50 a.m. The plugging contractor ordered out back hoe and welder. They dug out the surface pipe. They found 8" split in seam of surface pipe between 10-12' from surface. The welder patched the leak. The pumping pressure before the surface pipe blew out ranged from 200-300 psi. They resumed pumping at 3:45 p.m. with 130 sx cement. They did not release the 8 5/8" wiper plug due to surface pipe's condition.