

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-151 - 2DS97 - 00-01

RECEIVED
N.W. NE, Sec. 12, T 28 S, R 15 W/E

5-17-83 feet from N/S section line

MAY 17 1983 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6809 CONSERVATION DIVISION
Wichita, Kansas Lease Name Bransold Well # 1

Operator: Par Petroleum Inc. County Pratt

Name & Address P.O. Box 280 Well Total Depth 4700 feet 152.75

Liberal, Kansas 67901 Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 345

Abandoned Oil Well Gas Well Input Well SWD Well D&A

Other well as hereinafter indicated

Plugging Contractor H+H Casing pulling License Number 6053

Address 408 circle Drive Box 563 Burrton Kansas 67020

Company to plug at: Hour: 3:00 pm Day: 10 Month: May Year: 1983

VERBAL PLUGGING ORDERS GIVEN TO Don Hersh

(company name), H+H Casing (phone)

were: Squeeze Bottom with 35sx cement

- Pump down 8 5/8" with 3 holls - 10 gel - 50sx

cement - 10 gel - 1 holl - Wiper Plug - 100sx cement

Using 50/50 pozmix 4% gel 3% cc

Signed Richard W. Lacey
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None

Operations Completed: Hour: 5:15 pm Day: 10 Month: May Year: 1983

ACTUAL PLUGGING REPORT Plugged as ordered in above paragraph

Maximum Pump Pressure 400 psi

Shot in Pressure 200

Recovered 1980' of 4 1/2 production casing

Remarks: Mr. Steve Durrant gave plugging orders

I hereby certify that the above plugging instructions were given as herein stated
and that I (did / did not) observe this plugging.

INVOICED

Signed Richard W. Lacey
(TECHNICIAN)

DATE
INV. NO. 4368-W